

---

Documentation for package "reportlab.graphics"  
Generated by: graphdocpy.py version 0.8  
Date generated: 2006-05-23 10:32  
Format: PDF

---

reportlab.graphics	10
areas	10
Classes	10
PlotArea(Widget)	10
Public Attributes	10
axes	11
Classes	11
AdjYValueAxis(YValueAxis)	11
Public Attributes	11
CategoryAxis(_AxisG)	14
Public Attributes	14
NormalDateXValueAxis(XValueAxis)	14
Public Attributes	14
ValueAxis(_AxisG)	17
Public Attributes	17
XCategoryAxis(CategoryAxis)	17
Public Attributes	17
XValueAxis(ValueAxis)	18
Public Attributes	18
YCategoryAxis(CategoryAxis)	21
Public Attributes	21
YValueAxis(ValueAxis)	21
Public Attributes	21
_AxisG(Widget)	24
Public Attributes	24
Functions	25
sample0a( ... )	25
sample0b( ... )	26
sample1( ... )	27
sample4a( ... )	28
sample4b( ... )	29
sample4c( ... )	30
sample4c1( ... )	31
sample4d( ... )	32
sample5a( ... )	33
sample5b( ... )	34
sample5c( ... )	35
sample5d( ... )	36
sample6a( ... )	37
sample6b( ... )	38

---

sample6c( ... )	39
sample6d( ... )	40
sample7a( ... )	41
sample7b( ... )	42
sample7c( ... )	43
sample7d( ... )	44
barcharts	45
Classes	45
BarChart(PlotArea)	45
Public Attributes	45
BarChart3D(BarChart)	45
Public Attributes	46
HorizontalBarChart(BarChart)	46
Public Attributes	46
HorizontalBarChart3D(BarChart3D, HorizontalBarChart)	49
Public Attributes	49
SampleH5c4(Drawing)	52
VerticalBarChart(BarChart)	52
Public Attributes	52
VerticalBarChart3D(BarChart3D, VerticalBarChart)	55
Public Attributes	55
Functions	58
sampleH0a( ... )	58
sampleH0b( ... )	59
sampleH0c( ... )	60
sampleH1( ... )	61
sampleH2a( ... )	62
sampleH2b( ... )	63
sampleH2c( ... )	64
sampleH3( ... )	66
sampleH4a( ... )	68
sampleH4b( ... )	69
sampleH4c( ... )	70
sampleH4d( ... )	71
sampleH5a( ... )	72
sampleH5b( ... )	73
sampleH5c1( ... )	74
sampleH5c2( ... )	75
sampleH5c3( ... )	76
sampleH5c4( ... )	77

---

sampleStacked1( ... )	78
sampleSymbol1( ... )	80
sampleV0a( ... )	82
sampleV0b( ... )	83
sampleV0c( ... )	84
sampleV1( ... )	85
sampleV2a( ... )	86
sampleV2b( ... )	87
sampleV2c( ... )	88
sampleV3( ... )	90
sampleV4a( ... )	92
sampleV4b( ... )	93
sampleV4c( ... )	94
sampleV4d( ... )	95
sampleV5a( ... )	96
sampleV5b( ... )	97
sampleV5c1( ... )	98
sampleV5c2( ... )	99
sampleV5c3( ... )	100
sampleV5c4( ... )	101
dotbox	102
Classes	102
DotBox(Widget)	102
Public Attributes	102
doughnut	104
Classes	104
Doughnut(AbstractPieChart)	104
Public Attributes	104
Functions	106
sample1( ... )	106
sample2( ... )	108
sample3( ... )	109
legends	110
Classes	110
Legend(Widget)	110
Public Attributes	110
LineLegend(Legend)	112
Public Attributes	112
LineSwatch(Widget)	114
Public Attributes	114

---

---

Functions	115
sample1c( ... )	115
sample2c( ... )	116
sample3( ... )	117
sample3a( ... )	118
linecharts	119
Classes	119
AbstractLineChart(PlotArea)	119
Public Attributes	119
HorizontalLineChart(LineChart)	120
Public Attributes	120
HorizontalLineChart3D(HorizontalLineChart)	123
Public Attributes	123
LineChart(AbstractLineChart)	126
Public Attributes	126
SampleHorizontalLineChart(HorizontalLineChart)	127
Public Attributes	127
VerticalLineChart(LineChart)	130
Public Attributes	130
Functions	131
sample1( ... )	131
sample1a( ... )	132
sample2( ... )	133
sample3( ... )	134
lineplots	135
Classes	135
AreaLinePlot(LinePlot)	135
Public Attributes	135
GridLinePlot(LinePlot)	138
Public Attributes	138
LinePlot(AbstractLineChart)	142
Public Attributes	142
LinePlot3D(LinePlot)	145
Public Attributes	145
ScatterPlot(LinePlot)	148
Public Attributes	148
ShadedPolyFiller(Filler, ShadedPolygon)	151
Public Attributes	151
SplitLinePlot(AreaLinePlot)	152
Public Attributes	152

---

Functions	158
sample1a( ... )	158
sample1b( ... )	159
sample1c( ... )	160
sample2( ... )	161
piecharts	163
Classes	163
AbstractPieChart(PlotArea)	163
Public Attributes	163
LegendedPie(Pie)	164
Public Attributes	164
Pie(AbstractPieChart)	166
Public Attributes	166
Pie3d(Pie)	168
Public Attributes	168
WedgeLabel(Label)	170
Public Attributes	170
Functions	172
sample0a( ... )	172
sample0b( ... )	173
sample1( ... )	174
sample2( ... )	175
sample3( ... )	176
sample4( ... )	177
slidebox	178
Classes	178
SlideBox(Widget)	178
Public Attributes	178
spider	180
Classes	180
SpiderChart(PlotArea)	180
Public Attributes	180
SpokeLabel(WedgeLabel)	182
Public Attributes	182
StrandLabel(SpokeLabel)	184
Public Attributes	184
Functions	186
sample1( ... )	186
sample2( ... )	188
textlabels	190

---

Classes	190
BarChartLabel(Label)	190
Public Attributes	190
Label(Widget)	192
Public Attributes	192
NA_Label(BarChartLabel)	194
Public Attributes	194
bubble	196
Classes	196
Bubble(_DrawingEditorMixin, Drawing)	196
clustered_bar	197
Classes	197
ClusteredBar(_DrawingEditorMixin, Drawing)	197
clustered_column	198
Classes	198
ClusteredColumn(_DrawingEditorMixin, Drawing)	198
exploded_pie	200
Classes	200
ExplodedPie(_DrawingEditorMixin, Drawing)	200
filled_radar	201
Classes	201
FilledRadarChart(_DrawingEditorMixin, Drawing)	201
linechart_with_markers	202
Classes	202
LineChartWithMarkers(_DrawingEditorMixin, Drawing)	202
line_chart	204
Classes	204
LineChart(_DrawingEditorMixin, Drawing)	204
radar	205
Classes	205
RadarChart(_DrawingEditorMixin, Drawing)	205
scatter	206
Classes	206
Scatter(_DrawingEditorMixin, Drawing)	206
scatter_lines	207
Classes	207
ScatterLines(_DrawingEditorMixin, Drawing)	207
scatter_lines_markers	209
Classes	209
ScatterLinesMarkers(_DrawingEditorMixin, Drawing)	209

---

simple_pie	210
Classes	210
SimplePie(_DrawingEditorMixin, Drawing)	210
stacked_bar	211
Classes	211
StackedBar(_DrawingEditorMixin, Drawing)	211
stacked_column	213
Classes	213
StackedColumn(_DrawingEditorMixin, Drawing)	213
eventcal	214
Classes	214
EventCalendar(Widget)	214
Public Attributes	214
flags	216
Classes	216
Flag(_Symbol)	216
Public Attributes	216
Star(_Symbol)	217
Public Attributes	217
grids	217
Classes	217
DoubleGrid(Widget)	217
Public Attributes	217
Grid(Widget)	219
Public Attributes	219
ShadedPolygon(Widget, LineShape)	221
Public Attributes	221
ShadedRect(Widget)	222
Public Attributes	222
signsandsymbols	223
Classes	223
ArrowOne(_Symbol)	223
Public Attributes	223
ArrowTwo(ArrowOne)	223
Public Attributes	223
Crossbox(_Symbol)	224
Public Attributes	224
DangerSign(_Symbol)	224
Public Attributes	224
ETriangle(_Symbol)	225



---

Public Attributes	225
FloppyDisk(_Symbol)	225
Public Attributes	225
NoEntry(_Symbol)	225
Public Attributes	225
NoSmoking(NotAllowed)	226
Public Attributes	226
NotAllowed(_Symbol)	226
Public Attributes	226
Octagon(_Symbol)	226
Public Attributes	227
RTriangle(_Symbol)	227
Public Attributes	227
SmileyFace(_Symbol)	227
Public Attributes	227
StopSign(_Symbol)	228
Public Attributes	228
Tickbox(_Symbol)	228
Public Attributes	228
YesNo(_Symbol)	228
Public Attributes	229
_Symbol(Widget)	229
Public Attributes	229

---

## reportlab.graphics

### areas

This module defines a Area mixin classes

### Classes

#### PlotArea(Widget)

Abstract base class representing a chart's plot area, pretty unusable by itself.

### Public Attributes

**background** Handle to background object.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

#### *Example*

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

#### *Properties of Example Widget*

```
background = None
debug = 0
fillColor = None
height = 85
strokeColor = None
strokeWidth = 1
width = 180
x = 20
y = 10
```

## axes

Collection of axes for charts.

The current collection comprises axes for charts using cartesian coordinate systems. All axes might have tick marks and labels. There are two dichotomies for axes: one of X and Y flavours and another of category and value flavours.

Category axes have an ordering but no metric. They are divided into a number of equal-sized buckets. Their tick marks or labels, if available, go BETWEEN the buckets, and the labels are placed below to/left of the X/Y-axis, respectively.

Value axes have an ordering AND metric. They correspond to a numeric quantity. Value axis have a real number quantity associated with it. The chart tells it where to go.

The most basic axis divides the number line into equal spaces and has tickmarks and labels associated with each; later we will add variants where you can specify the sampling interval.

The charts using axis tell them where the labels should be placed.

Axes of complementary X/Y flavours can be connected to each other in various ways, i.e. with a specific reference point, like an x/value axis to a y/value (or category) axis. In this case the connection can be either at the top or bottom of the former or at any absolute value (specified in points) or at some value of the former axes in its own coordinate system.

## Classes

### **AdjYValueAxis(YValueAxis)**

A Y-axis applying additional rules.

Depending on the data and some built-in rules, the axis may choose to adjust its range and origin.

## Public Attributes

**avoidBoundFrac** Fraction of interval to allow above and below.

**forceZero** Ensure zero in range if true.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**joinAxis** Join both axes if true.

**joinAxisMode** Mode used for connecting axis ('left', 'right', 'value', 'points', None).

**joinAxisPos** Position at which to join with other axis.

**labelTextFormat** Formatting string or function used for axis labels.

**labelTextPostFormat** Extra Formatting string.

**labelTextScale** Scaling for label tick values.

**labels** Handle of the axis labels.

**leftAxisOrigShiftIPC** Lowest label shift interval ratio.

**leftAxisOrigShiftMin** Minimum amount to shift.

**leftAxisPercent** When true add percent sign to label values.

**leftAxisSkipLL0** Skip/Keep lowest tick label when true/false. Or skiplist

**maximumTicks** Maximum number of ticks.

**minimumTickSpacing** Minimum value for distance between ticks.

**rangeRound** How to round the axis limits

**requiredRange** Minimum required value range.

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How values are plotted!

**tickLeft** Tick length left of the axis.

**tickRight** Tick length right of the axis.

**valueMax** Maximum value on axis.

**valueMin** Minimum value on axis.

**valueStep** Step size used between ticks.

**valueSteps** List of step sizes used between ticks.

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.


**visibleTicks** Display axis ticks, if true.

**zrangePref** Zero range axis limit preference.

#### *Example*

```
def demo(self):
    data = [(10, 20, 30, 42)]
    self.setPosition(100, 10, 80)
    self.configure(data)

    drawing = Drawing(200, 100)
    drawing.add(self)
    return drawing
```



### *Properties of Example Widget*

```
avoidBoundFrac = None
forceZero = 0
gridEnd = 0
gridStart = 0
gridStrokeColor = Color(0,0,0)
gridStrokeDashArray = None
gridStrokeWidth = 0.25
joinAxis = None
joinAxisMode = None
joinAxisPos = None
labelTextFormat = None
labelTextPostFormat = None
labelTextScale = None
labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x00EE70F8>
leftAxisOrigShiftIPC = 0.14999999999999999
leftAxisOrigShiftMin = 12
leftAxisPercent = 1
leftAxisSkipLL0 = 0
maximumTicks = 7
minimumTickSpacing = 10
rangeRound = 'none'
requiredRange = 30
strokeColor = Color(0,0,0)
strokeDashArray = None
strokeWidth = 1
style = 'normal'
tickLeft = 5
tickRight = 0
valueMax = None
valueMin = None
valueStep = None
valueSteps = [10.0, 15.0, 20.0, 25.0, 30.0, 35.0, 40.0, 45.0]
visible = 1
visibleAxis = 1
visibleGrid = 0
visibleLabels = 1
visibleTicks = 1
zrangePref = 0
```

## CategoryAxis(\_AxisG)

Abstract category axis, unusable in itself.

### Public Attributes

**categoryNames** List of category names.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**joinAxis** Join both axes if true.

**joinAxisPos** Position at which to join with other axis.

**labelAxisMode** Like joinAxisMode, but for the axis labels

**labels** Handle of the axis labels.

**reverseDirection** If true reverse category direction.

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How common category bars are plotted

**tickShift** Tick shift typically

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.

**visibleTicks** Display axis ticks, if true.

## NormalDateXValueAxis(XValueAxis)

An X axis applying additional rules.

Depending on the data and some built-in rules, the axis displays normalDate values as nicely formatted dates.

The client chart should have NormalDate X values.

### Public Attributes

**avoidBoundFrac** Fraction of interval to allow above and below.

**bottomAxisLabelSlack** Fractional amount used to adjust label spacing

**dailyFreq** True if we are to assume daily data to be ticked at end of month.

**dayOfWeekName** Weekday names.

**forceEndDate** Flag for enforced displaying of last date value.

**forceFirstDate** Flag for enforced displaying of first date value.

**forceZero** Ensure zero in range if true.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**joinAxis** Join both axes if true.

**joinAxisMode** Mode used for connecting axis ('bottom', 'top', 'value', 'points', None).

**joinAxisPos** Position at which to join with other axis.

**labelTextFormat** Formatting string or function used for axis labels.

**labelTextPostFormat** Extra Formatting string.

**labelTextScale** Scaling for label tick values.

**labels** Handle of the axis labels.

**maximumTicks** Maximum number of ticks.

**minimumTickSpacing** Minimum value for distance between ticks.

**monthName** Month names.

**niceMonth** Flag for displaying months 'nicely'.

**rangeRound** How to round the axis limits

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How values are plotted!

**tickDown** Tick length down the axis.

**tickUp** Tick length up the axis.

**valueMax** Maximum value on axis.

**valueMin** Minimum value on axis.

**valueStep** Step size used between ticks.

**valueSteps** List of step sizes used between ticks.

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.

**visibleTicks** Display axis ticks, if true.

**xLabelFormat** Label format string (e.g. '{mm}/{yy}') or function.

**zrangePref** Zero range axis limit preference.

*Example*

```
def demo(self):
```

```
self.setPosition(20, 50, 150)
self.configure([(10,20,30,40,50)])

d = Drawing(200, 100)
d.add(self)
return d
```

### *Properties of Example Widget*

```
avoidBoundFrac = None
bottomAxisLabelSlack = 0.10000000000000001
dailyFreq = 0
dayOfWeekName = ['Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday', 'Saturday', 'Sunday']
forceEndDate = 0
forceFirstDate = 0
forceZero = 0
gridEnd = 0
gridStart = 0
gridStrokeColor = Color(0,0,0)
gridStrokeDashArray = None
gridStrokeWidth = 0.25
joinAxis = None
joinAxisMode = None
joinAxisPos = None
labelTextFormat = None
labelTextPostFormat = None
labelTextScale = None
labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x00F19CB0>
maximumTicks = 7
minimumTickSpacing = 10
monthName = ['January',
             'February',
             'March',
             'April',
             'May',
             'June',
             'July',
             'August',
             'September',
             'October',
             'November',
             'December']
niceMonth = 1
rangeRound = 'none'
strokeColor = Color(0,0,0)
strokeDashArray = None
strokeWidth = 1
style = 'normal'
tickDown = 5
tickUp = 0
valueMax = None
valueMin = None
valueStep = None
valueSteps = None
visible = 1
visibleAxis = 1
visibleGrid = 0
visibleLabels = 1
visibleTicks = 1
xlabelFormat = '{mm}/{yy}'
zrangePref = 0
```



## **ValueAxis(\_AxisG)**

Abstract value axis, unusable in itself.

### **Public Attributes**

**avoidBoundFrac** Fraction of interval to allow above and below.

**forceZero** Ensure zero in range if true.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**labelTextFormat** Formatting string or function used for axis labels.

**labelTextPostFormat** Extra Formatting string.

**labelTextScale** Scaling for label tick values.

**labels** Handle of the axis labels.

**maximumTicks** Maximum number of ticks.

**minimumTickSpacing** Minimum value for distance between ticks.

**rangeRound** How to round the axis limits

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How values are plotted!

**valueMax** Maximum value on axis.

**valueMin** Minimum value on axis.

**valueStep** Step size used between ticks.

**valueSteps** List of step sizes used between ticks.

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.

**visibleTicks** Display axis ticks, if true.

**zrangePref** Zero range axis limit preference.

## **XCategoryAxis(CategoryAxis)**

X/category axis

### **Public Attributes**

**categoryNames** List of category names.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**joinAxis** Join both axes if true.

**joinAxisMode** Mode used for connecting axis ('bottom', 'top', 'value', 'points', None).

**joinAxisPos** Position at which to join with other axis.

**labelAxisMode** Like joinAxisMode, but for the axis labels

**labels** Handle of the axis labels.

**reverseDirection** If true reverse category direction.

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How common category bars are plotted

**tickDown** Tick length down the axis.

**tickShift** Tick shift typically

**tickUp** Tick length up the axis.

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.

**visibleTicks** Display axis ticks, if true.

## **XValueAxis(ValueAxis)**

X/value axis

### **Public Attributes**

**avoidBoundFrac** Fraction of interval to allow above and below.

**forceZero** Ensure zero in range if true.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**joinAxis** Join both axes if true.

**joinAxisMode** Mode used for connecting axis ('bottom', 'top', 'value', 'points', None).

**joinAxisPos** Position at which to join with other axis.

**labelTextFormat** Formatting string or function used for axis labels.

**labelTextPostFormat** Extra Formatting string.

**labelTextScale** Scaling for label tick values.

**labels** Handle of the axis labels.

**maximumTicks** Maximum number of ticks.

**minimumTickSpacing** Minimum value for distance between ticks.

**rangeRound** How to round the axis limits

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How values are plotted!

**tickDown** Tick length down the axis.

**tickUp** Tick length up the axis.

**valueMax** Maximum value on axis.

**valueMin** Minimum value on axis.

**valueStep** Step size used between ticks.

**valueSteps** List of step sizes used between ticks.

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.

**visibleTicks** Display axis ticks, if true.

**zrangePref** Zero range axis limit preference.

#### *Example*

```
def demo(self):
    self.setPosition(20, 50, 150)
    self.configure([(10,20,30,40,50)])

    d = Drawing(200, 100)
    d.add(self)
    return d
```

#### *Properties of Example Widget*

```
avoidBoundFrac = None
forceZero = 0
gridEnd = 0
gridStart = 0
gridStrokeColor = Color(0,0,0)
gridStrokeDashArray = None
gridStrokeWidth = 0.25
joinAxis = None
joinAxisMode = None
joinAxisPos = None
labelTextFormat = None
labelTextPostFormat = None
labelTextScale = None
labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x00F2EA80>
maximumTicks = 7
minimumTickSpacing = 10
rangeRound = 'none'
```

```
strokeColor = Color(0,0,0)
strokeDashArray = None
strokeWidth = 1
style = 'normal'
tickDown = 5
tickUp = 0
valueMax = None
valueMin = None
valueStep = None
visible = 1
visibleAxis = 1
visibleGrid = 0
visibleLabels = 1
visibleTicks = 1
zrangePref = 0
```

## **YCategoryAxis (CategoryAxis)**

Y/category axis

### **Public Attributes**

**categoryNames** List of category names.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**joinAxis** Join both axes if true.

**joinAxisMode** Mode used for connecting axis ('left', 'right', 'value', 'points', None).

**joinAxisPos** Position at which to join with other axis.

**labelAxisMode** Like joinAxisMode, but for the axis labels

**labels** Handle of the axis labels.

**reverseDirection** If true reverse category direction.

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How common category bars are plotted

**tickLeft** Tick length left of the axis.

**tickRight** Tick length right of the axis.

**tickShift** Tick shift typically

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.

**visibleTicks** Display axis ticks, if true.

## **YValueAxis (ValueAxis)**

Y/value axis

### **Public Attributes**

**avoidBoundFrac** Fraction of interval to allow above and below.

**forceZero** Ensure zero in range if true.

**gridEnd** End of grid lines wrt axis origin

**gridStart** Start of grid lines wrt axis origin

**gridStrokeColor** Color of grid lines.

**gridStrokeDashArray** Dash array used for grid lines.

**gridStrokeWidth** Width of grid lines.

**joinAxis** Join both axes if true.

**joinAxisMode** Mode used for connecting axis ('left', 'right', 'value', 'points', None).

**joinAxisPos** Position at which to join with other axis.

**labelTextFormat** Formatting string or function used for axis labels.

**labelTextPostFormat** Extra Formatting string.

**labelTextScale** Scaling for label tick values.

**labels** Handle of the axis labels.

**maximumTicks** Maximum number of ticks.

**minimumTickSpacing** Minimum value for distance between ticks.

**rangeRound** How to round the axis limits

**strokeColor** Color of axis line and ticks.

**strokeDashArray** Dash array used for axis line.

**strokeWidth** Width of axis line and ticks.

**style** How values are plotted!

**tickLeft** Tick length left of the axis.

**tickRight** Tick length right of the axis.

**valueMax** Maximum value on axis.

**valueMin** Minimum value on axis.

**valueStep** Step size used between ticks.

**valueSteps** List of step sizes used between ticks.

**visible** Display entire object, if true.

**visibleAxis** Display axis line, if true.

**visibleGrid** Display axis grid, if true.

**visibleLabels** Display axis labels, if true.

**visibleTicks** Display axis ticks, if true.

**zrangePref** Zero range axis limit preference.

#### *Example*

```
def demo(self):
    data = [(10, 20, 30, 42)]
    self.setPosition(100, 10, 80)
    self.configure(data)

    drawing = Drawing(200, 100)
    drawing.add(self)
    return drawing
```

#### *Properties of Example Widget*

```
avoidBoundFrac = None
forceZero = 0
gridEnd = 0
gridStart = 0
```

```
gridStrokeColor = Color(0,0,0)
gridStrokeDashArray = None
gridStrokeWidth = 0.25
joinAxis = None
joinAxisMode = None
joinAxisPos = None
labelTextFormat = None
labelTextPostFormat = None
labelTextScale = None
labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x00F3BFA8>
maximumTicks = 7
minimumTickSpacing = 10
rangeRound = 'none'
strokeColor = Color(0,0,0)
strokeDashArray = None
strokeWidth = 1
style = 'normal'
tickLeft = 5
tickRight = 0
valueMax = None
valueMin = None
valueStep = None
visible = 1
visibleAxis = 1
visibleGrid = 0
visibleLabels = 1
visibleTicks = 1
zrangePref = 0
```

## **`_AxisG(Widget)`**

### **Public Attributes**

#### *Example*

```
def demo(self):  
    msg = "demo() must be implemented for each Widget!"  
    raise shapes.NotImplementedError, msg
```

#### *Properties of Example Widget*



## Functions

### **sample0a( ... )**

Sample drawing with one xcat axis and two buckets.

#### *Example*

```
def sample0a():
    "Sample drawing with one xcat axis and two buckets."


    drawing = Drawing(400, 200)

    data = [(10, 20)]

    xAxis = XCategoryAxis()
    xAxis.setPosition(75, 75, 300)
    xAxis.configure(data)
    xAxis.categoryNames = ['Ying', 'Yang']
    xAxis.labels.boxAnchor = 'n'

    drawing.add(xAxis)

    return drawing
```



**sample0b( ... )**

Sample drawing with one xcat axis and one bucket only.

*Example*

```
def sample0b():
    "Sample drawing with one xcat axis and one bucket only."


    drawing = Drawing(400, 200)

    data = [(10,)]

    xAxis = XCategoryAxis()
    xAxis.setPosition(75, 75, 300)
    xAxis.configure(data)
    xAxis.categoryNames = ['Ying']
    xAxis.labels.boxAnchor = 'n'

    drawing.add(xAxis)

    return drawing
```



**sample1( ... )**

Sample drawing containing two unconnected axes.

*Example*

```
def sample1():
    "Sample drawing containing two unconnected axes."

    drawing = Drawing(400, 200)

    data = [(10, 20, 30, 42)]

    xAxis = XCategoryAxis()
    xAxis.setPosition(75, 75, 300)
    xAxis.configure(data)
    xAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    xAxis.labels.boxAnchor = 'n'
    xAxis.labels[3].dy = -15
    xAxis.labels[3].angle = 30
    xAxis.labels[3].fontName = 'Times-Bold'

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)
    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample4a( ... )**

Sample drawing, xvalue/yvalue axes, y connected at 100 pts to x.

*Example*

```
def sample4a():
    "Sample drawing, xvalue/yvalue axes, y connected at 100 pts to x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'points'
    xAxis.joinAxisPos = 100
    xAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample4b( ... )**

Sample drawing, xvalue/yvalue axes, y connected at value 35 of x.

*Example*

```
def sample4b():
    "Sample drawing, xvalue/yvalue axes, y connected at value 35 of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'value'
    xAxis.joinAxisPos = 35
    xAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample4c( ... )**

Sample drawing, xvalue/yvalue axes, y connected to bottom of x.

*Example*

```
def sample4c():
    "Sample drawing, xvalue/yvalue axes, y connected to bottom of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'bottom'
    xAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample4c1( ... )**

xvalue/yvalue axes, without drawing axis lines/ticks.

*Example*

```
def sample4c1():
    "xvalue/yvalue axes, without drawing axis lines/ticks."

    drawing = Drawing(400, 200)

    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)
    yAxis.visibleAxis = 0
    yAxis.visibleTicks = 0

    xAxis = XValueAxis()
    xAxis.__length = 300
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'bottom'
    xAxis.configure(data)
    xAxis.visibleAxis = 0
    xAxis.visibleTicks = 0

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```

40

30

20

10

10

20

30

40

**sample4d( ... )**

Sample drawing, xvalue/yvalue axes, y connected to top of x.

*Example*

```
def sample4d():
    "Sample drawing, xvalue/yvalue axes, y connected to top of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'top'
    xAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```





**sample5a( ... )**

Sample drawing, xvalue/yvalue axes, y connected at 100 pts to x.

*Example*

```
def sample5a():
    "Sample drawing, xvalue/yvalue axes, y connected at 100 pts to x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis.setPosition(50, 50, 300)
    xAxis.configure(data)

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'points'
    yAxis.joinAxisPos = 100
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample5b( ... )**

Sample drawing, xvalue/yvalue axes, y connected at value 35 of x.

*Example*

```
def sample5b():
    "Sample drawing, xvalue/yvalue axes, y connected at value 35 of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis.setPosition(50, 50, 300)
    xAxis.configure(data)

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'value'
    yAxis.joinAxisPos = 35
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample5c( ... )**

Sample drawing, xvalue/yvalue axes, y connected at right of x.

*Example*

```
def sample5c():
    "Sample drawing, xvalue/yvalue axes, y connected at right of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis.setPosition(50, 50, 300)
    xAxis.configure(data)

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'right'
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample5d( ... )**

Sample drawing, xvalue/yvalue axes, y connected at left of x.

*Example*

```
def sample5d():
    "Sample drawing, xvalue/yvalue axes, y connected at left of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis.setPosition(50, 50, 300)
    xAxis.configure(data)

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'left'
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample6a( ... )**

Sample drawing, xcat/yvalue axes, x connected at top of y.

*Example*

```
def sample6a():
    "Sample drawing, xcat/yvalue axes, x connected at top of y."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XCategoryAxis()
    xAxis._length = 300
    xAxis.configure(data)
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'top'
    xAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    xAxis.labels.boxAnchor = 'n'

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample6b( ... )**

Sample drawing, xcat/yvalue axes, x connected at bottom of y.

*Example*

```
def sample6b():
    "Sample drawing, xcat/yvalue axes, x connected at bottom of y."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XCategoryAxis()
    xAxis._length = 300
    xAxis.configure(data)
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'bottom'
    xAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    xAxis.labels.boxAnchor = 'n'

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample6c( ... )**

Sample drawing, xcat/yvalue axes, x connected at 100 pts to y.

*Example*

```
def sample6c():
    "Sample drawing, xcat/yvalue axes, x connected at 100 pts to y."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XCategoryAxis()
    xAxis._length = 300
    xAxis.configure(data)
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'points'
    xAxis.joinAxisPos = 100
    xAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    xAxis.labels.boxAnchor = 'n'

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample6d( ... )**

Sample drawing, xcat/yvalue axes, x connected at value 20 of y.

*Example*

```
def sample6d():
    "Sample drawing, xcat/yvalue axes, x connected at value 20 of y."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    yAxis = YValueAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.configure(data)

    xAxis = XCategoryAxis()
    xAxis._length = 300
    xAxis.configure(data)
    xAxis.joinAxis = yAxis
    xAxis.joinAxisMode = 'value'
    xAxis.joinAxisPos = 20
    xAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    xAxis.labels.boxAnchor = 'n'

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```





**sample7a( ... )**

Sample drawing, xvalue/ycat axes, y connected at right of x.

*Example*

```
def sample7a():
    "Sample drawing, xvalue/ycat axes, y connected at right of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.configure(data)

    yAxis = YCategoryAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'right'
    yAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    yAxis.labels.boxAnchor = 'e'
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample7b( ... )**

Sample drawing, xvalue/ycat axes, y connected at left of x.

*Example*

```
def sample7b():
    "Sample drawing, xvalue/ycat axes, y connected at left of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.configure(data)

    yAxis = YCategoryAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'left'
    yAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    yAxis.labels.boxAnchor = 'e'
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample7c( ... )**

Sample drawing, xvalue/ycat axes, y connected at value 30 of x.

*Example*

```
def sample7c():
    "Sample drawing, xvalue/ycat axes, y connected at value 30 of x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.configure(data)

    yAxis = YCategoryAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'value'
    yAxis.joinAxisPos = 30
    yAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    yAxis.labels.boxAnchor = 'e'
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



**sample7d( ... )**

Sample drawing, xvalue/ycat axes, y connected at 200 pts to x.

*Example*

```
def sample7d():
    "Sample drawing, xvalue/ycat axes, y connected at 200 pts to x."

    drawing = Drawing(400, 200)


    data = [(10, 20, 30, 42)]

    xAxis = XValueAxis()
    xAxis._length = 300
    xAxis.configure(data)

    yAxis = YCategoryAxis()
    yAxis.setPosition(50, 50, 125)
    yAxis.joinAxis = xAxis
    yAxis.joinAxisMode = 'points'
    yAxis.joinAxisPos = 200
    yAxis.categoryNames = ['Beer', 'Wine', 'Meat', 'Cannelloni']
    yAxis.labels.boxAnchor = 'e'
    yAxis.configure(data)

    drawing.add(xAxis)
    drawing.add(yAxis)

    return drawing
```



## **barcharts**

This module defines a variety of Bar Chart components.

The basic flavors are Side-by-side, available in horizontal and vertical versions.

Stacked and percentile bar charts to follow...

## **Classes**

### **BarChart (PlotArea)**

Abstract base class, unusable by itself.

## **Public Attributes**

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**barLabelArray** explicit array of bar label values, must match size of data if present.

**barLabelCallOut** Callout function(label) label.\_callOutInfo = (self,g,rowNo,colNo,x,y,width,height,x00,y00,x0,y0)

**barLabelFormat** Formatting string or function used for bar labels.

**barLabels** Handle to the list of bar labels.

**barSpacing** Width between individual bars.

**barWidth** The width of an individual bar.

**bars** Handle of the individual bars.

**categoryAxis** Handle of the category axis.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** Width between groups of bars.

**height** Height of the chart.

**naLabel** Label to use for N/A values.

**reversePlotOrder** If true, reverse common category plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### **BarChart3D (BarChart)**

## Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**barLabelArray** explicit array of bar label values, must match size of data if present.

**barLabelCallOut** Callout function(label) label.\_callOutInfo = (self,g,rowNo,colNo,x,y,width,height,x00,y00,x0,y0)

**barLabelFormat** Formatting string or function used for bar labels.

**barLabels** Handle to the list of bar labels.

**barSpacing** Width between individual bars.

**barWidth** The width of an individual bar.

**bars** Handle of the individual bars.

**categoryAxis** Handle of the category axis.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** Width between groups of bars.

**height** Height of the chart.

**naLabel** Label to use for N/A values.

**reversePlotOrder** If true, reverse common category plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**theta\_x** dx/dz

**theta\_y** dy/dz

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

**zDepth** depth of an individual series

**zSpace** z gap around series

## HorizontalBarChart ( BarChart )

Horizontal bar chart with multiple side-by-side bars.

## Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**barLabelArray** explicit array of bar label values, must match size of data if present.

**barLabelCallOut** Callout function(label) label.\_callOutInfo = (self,g,rowNo,colNo,x,y,width,height,x00,y00,x0,y0)

**barLabelFormat** Formatting string or function used for bar labels.

**barLabels** Handle to the list of bar labels.

**barSpacing** Width between individual bars.

**barWidth** The width of an individual bar.

**bars** Handle of the individual bars.

**categoryAxis** Handle of the category axis.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** Width between groups of bars.

**height** Height of the chart.

**naLabel** Label to use for N/A values.

**reversePlotOrder** If true, reverse common category plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

#### *Example*

```
def demo(self):
    """Shows basic use of a bar chart"""
    if self.__class__.__name__=='BarChart':
        raise NotImplementedError, 'Abstract Class BarChart has no demo'
    drawing = Drawing(200, 100)
    bc = self.__class__()
    drawing.add(bc)
    return drawing
```

#### *Properties of Example Widget*

```
background = None
barLabelArray = None
barLabelFormat = None
barLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0106B760>
barSpacing = 0
barWidth = 10
bars = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0106B7B0>
categoryAxis.categoryNames = None
categoryAxis.gridEnd = 0
categoryAxis.gridStart = 0
categoryAxis.gridStrokeColor = Color(0,0,0)
categoryAxis.gridStrokeDashArray = None
categoryAxis.gridStrokeWidth = 0.25
categoryAxis.joinAxis = None
categoryAxis.joinAxisMode = None
categoryAxis.joinAxisPos = None
categoryAxis.labelAxisMode = 'axis'
```

```
categoryAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0106B648>
categoryAxis.reverseDirection = 0
categoryAxis.strokeColor = Color(0,0,0)
categoryAxis.strokeDashArray = None
categoryAxis.strokeWidth = 1
categoryAxis.style = 'parallel'
categoryAxis.tickLeft = 5
categoryAxis.tickRight = 0
categoryAxis.tickShift = 0
categoryAxis.visible = 1
categoryAxis.visibleAxis = 1
categoryAxis.visibleGrid = 0
categoryAxis.visibleLabels = 1
categoryAxis.visibleTicks = 1
data = [(100, 110, 120, 130), (70, 80, 85, 90)]
debug = 0
fillColor = None
groupSpacing = 5
height = 85
naLabel = None
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
useAbsolute = 0
valueAxis.avoidBoundFrac = None
valueAxis.forceZero = 0
valueAxis.gridEnd = 0
valueAxis.gridStart = 0
valueAxis.gridStrokeColor = Color(0,0,0)
valueAxis.gridStrokeDashArray = None
valueAxis.gridStrokeWidth = 0.25
valueAxis.joinAxis = None
valueAxis.joinAxisMode = None
valueAxis.joinAxisPos = None
valueAxis.labelTextFormat = None
valueAxis.labelTextPostFormat = None
valueAxis.labelTextScale = None
valueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0106B710>
valueAxis.maximumTicks = 7
valueAxis.minimumTickSpacing = 10
valueAxis.rangeRound = 'none'
valueAxis.strokeColor = Color(0,0,0)
valueAxis.strokeDashArray = None
valueAxis.strokeWidth = 1
valueAxis.style = 'normal'
valueAxis.tickDown = 5
valueAxis.tickUp = 0
valueAxis.valueMax = None
valueAxis.valueMin = None
valueAxis.valueStep = None
valueAxis.visible = 1
valueAxis.visibleAxis = 1
valueAxis.visibleGrid = 0
valueAxis.visibleLabels = 1
valueAxis.visibleTicks = 1
valueAxis.zrangePref = 0
width = 180
x = 20
y = 10
```



## **HorizontalBarChart3D(BarChart3D, HorizontalBarChart)**

### **Public Attributes**

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**barLabelArray** explicit array of bar label values, must match size of data if present.

**barLabelCallOut** Callout function(label) label.\_callOutInfo =  
(self,g,rowNo,colNo,x,y,width,height,x00,y00,x0,y0)

**barLabelFormat** Formatting string or function used for bar labels.

**barLabels** Handle to the list of bar labels.

**barSpacing** Width between individual bars.

**barWidth** The width of an individual bar.

**bars** Handle of the individual bars.

**categoryAxis** Handle of the category axis.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** Width between groups of bars.

**height** Height of the chart.

**naLabel** Label to use for N/A values.

**reversePlotOrder** If true, reverse common category plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**theta\_x** dx/dz

**theta\_y** dy/dz

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

**zDepth** depth of an individual series

**zSpace** z gap around series

### *Example*

```
def demo(self):
    """Shows basic use of a bar chart"""
    if self.__class__.__name__=='BarChart':
        raise NotImplementedError, 'Abstract Class BarChart has no demo'
    drawing = Drawing(200, 100)
    bc = self.__class__()
    drawing.add(bc)
    return drawing
```

*Properties of Example Widget*

```
background = None
barLabelArray = None
barLabelFormat = None
barLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01073260>
barSpacing = 0
barWidth = 10
bars = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x010732B0>
categoryAxis.categoryNames = None
categoryAxis.gridEnd = 0
categoryAxis.gridStart = 0
categoryAxis.gridStrokeColor = Color(0,0,0)
categoryAxis.gridStrokeDashArray = None
categoryAxis.gridStrokeWidth = 0.25
categoryAxis.joinAxis = None
categoryAxis.joinAxisMode = None
categoryAxis.joinAxisPos = None
categoryAxis.labelAxisMode = 'axis'
categoryAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01073148>
categoryAxis.reverseDirection = 0
categoryAxis.strokeColor = Color(0,0,0)
categoryAxis.strokeDashArray = None
categoryAxis.strokeWidth = 1
categoryAxis.style = 'parallel'
categoryAxis.tickLeft = 5
categoryAxis.tickRight = 0
categoryAxis.tickShift = 0
categoryAxis.visible = 1
categoryAxis.visibleAxis = 1
categoryAxis.visibleGrid = 0
categoryAxis.visibleLabels = 1
categoryAxis.visibleTicks = 1
data = [(100, 110, 120, 130), (70, 80, 85, 90)]
debug = 0
fillColor = None
groupSpacing = 5
height = 85
naLabel = None
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
useAbsolute = 0
valueAxis.avoidBoundFrac = None
valueAxis.forceZero = 0
valueAxis.gridEnd = 0
valueAxis.gridStart = 0
valueAxis.gridStrokeColor = Color(0,0,0)
valueAxis.gridStrokeDashArray = None
valueAxis.gridStrokeWidth = 0.25
valueAxis.joinAxis = None
valueAxis.joinAxisMode = None
valueAxis.joinAxisPos = None
valueAxis.labelTextFormat = None
valueAxis.labelTextPostFormat = None
valueAxis.labelTextScale = None
valueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01073210>
valueAxis.maximumTicks = 7
valueAxis.minimumTickSpacing = 10
valueAxis.rangeRound = 'none'
valueAxis.strokeColor = Color(0,0,0)
valueAxis.strokeDashArray = None
valueAxis.strokeWidth = 1
valueAxis.style = 'normal'
valueAxis.tickDown = 5
valueAxis.tickUp = 0
valueAxis.valueMax = None
valueAxis.valueMin = None
valueAxis.valueStep = None
valueAxis.visible = 1
valueAxis.visibleAxis = 1
valueAxis.visibleGrid = 0
valueAxis.visibleLabels = 1
valueAxis.visibleTicks = 1
valueAxis.zrangePref = 0
```

```
width = 180  
x = 20  
y = 10
```

## SampleH5c4 (Drawing)

Simple bar chart with absolute spacing.

### Example


```
def __init__(self,width=400,height=200,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = dataSample5
    bc.strokeColor = colors.black

    bc.useAbsolute = 1
    bc.barWidth = 10
    bc.groupSpacing = 20
    bc.barSpacing = 10

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    self.add(bc,name='HBC')
```



## VerticalBarChart (BarChart)

Vertical bar chart with multiple side-by-side bars.

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**barLabelArray** explicit array of bar label values, must match size of data if present.

**barLabelCallOut** Callout function(label) label.\_callOutInfo =  
(self,g,rowNo,colNo,x,y,width,height,x00,y00,x0,y0)

**barLabelFormat** Formatting string or function used for bar labels.

**barLabels** Handle to the list of bar labels.

**barSpacing** Width between individual bars.

**barWidth** The width of an individual bar.

**bars** Handle of the individual bars.

**categoryAxis** Handle of the category axis.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** Width between groups of bars.

**height** Height of the chart.

**naLabel** Label to use for N/A values.

**reversePlotOrder** If true, reverse common category plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### *Example*

```
def demo(self):
    """Shows basic use of a bar chart"""
    if self.__class__.__name__=='BarChart':
        raise NotImplementedError, 'Abstract Class BarChart has no demo'
    drawing = Drawing(200, 100)
    bc = self.__class__()
    drawing.add(bc)
    return drawing
```

### *Properties of Example Widget*

```
background = None
barLabelArray = None
barLabelFormat = None
barLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0107C1E8>
barSpacing = 0
barWidth = 10
bars = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0107C238>
categoryAxis.categoryNames = None
categoryAxis.gridEnd = 0
categoryAxis.gridStart = 0
categoryAxis.gridStrokeColor = Color(0,0,0)
categoryAxis.gridStrokeDashArray = None
categoryAxis.gridStrokeWidth = 0.25
categoryAxis.joinAxis = None
categoryAxis.joinAxisMode = None
categoryAxis.joinAxisPos = None
categoryAxis.labelAxisMode = 'axis'
categoryAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0107C0D0>
categoryAxis.reverseDirection = 0
categoryAxis.strokeColor = Color(0,0,0)
```

```
categoryAxis.strokeDashArray = None
categoryAxis.strokeWidth = 1
categoryAxis.style = 'parallel'
categoryAxis.tickDown = 5
categoryAxis.tickShift = 0
categoryAxis.tickUp = 0
categoryAxis.visible = 1
categoryAxis.visibleAxis = 1
categoryAxis.visibleGrid = 0
categoryAxis.visibleLabels = 1
categoryAxis.visibleTicks = 1
data = [(100, 110, 120, 130), (70, 80, 85, 90)]
debug = 0
fillColor = None
groupSpacing = 5
height = 85
naLabel = None
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
useAbsolute = 0
valueAxis.avoidBoundFrac = None
valueAxis.forceZero = 0
valueAxis.gridEnd = 0
valueAxis.gridStart = 0
valueAxis.gridStrokeColor = Color(0,0,0)
valueAxis.gridStrokeDashArray = None
valueAxis.gridStrokeWidth = 0.25
valueAxis.joinAxis = None
valueAxis.joinAxisMode = None
valueAxis.joinAxisPos = None
valueAxis.labelTextFormat = None
valueAxis.labelTextPostFormat = None
valueAxis.labelTextScale = None
valueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0107C198>
valueAxis.maximumTicks = 7
valueAxis.minimumTickSpacing = 10
valueAxis.rangeRound = 'none'
valueAxis.strokeColor = Color(0,0,0)
valueAxis.strokeDashArray = None
valueAxis.strokeWidth = 1
valueAxis.style = 'normal'
valueAxis.tickLeft = 5
valueAxis.tickRight = 0
valueAxis.valueMax = None
valueAxis.valueMin = None
valueAxis.valueStep = None
valueAxis.visible = 1
valueAxis.visibleAxis = 1
valueAxis.visibleGrid = 0
valueAxis.visibleLabels = 1
valueAxis.visibleTicks = 1
valueAxis.zrangePref = 0
width = 180
x = 20
y = 10
```

## VerticalBarChart3D(BarChart3D, VerticalBarChart)

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**barLabelArray** explicit array of bar label values, must match size of data if present.

**barLabelCallOut** Callout function(label) label.\_callOutInfo =  
(self,g,rowNo,colNo,x,y,width,height,x00,y00,x0,y0)

**barLabelFormat** Formatting string or function used for bar labels.

**barLabels** Handle to the list of bar labels.

**barSpacing** Width between individual bars.

**barWidth** The width of an individual bar.

**bars** Handle of the individual bars.

**categoryAxis** Handle of the category axis.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** Width between groups of bars.

**height** Height of the chart.

**naLabel** Label to use for N/A values.

**reversePlotOrder** If true, reverse common category plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**theta\_x** dx/dz

**theta\_y** dy/dz

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

**zDepth** depth of an individual series

**zSpace** z gap around series

### Example

```
def demo(self):
    """Shows basic use of a bar chart"""
    if self.__class__.__name__=='BarChart':
        raise NotImplementedError, 'Abstract Class BarChart has no demo'
    drawing = Drawing(200, 100)
    bc = self.__class__()
    drawing.add(bc)
    return drawing
```

*Properties of Example Widget*

```
background = None
barLabelArray = None
barLabelFormat = None
barLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01081C88>
barSpacing = 0
barWidth = 10
bars = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01081CD8>
categoryAxis.categoryNames = None
categoryAxis.gridEnd = 0
categoryAxis.gridStart = 0
categoryAxis.gridStrokeColor = Color(0,0,0)
categoryAxis.gridStrokeDashArray = None
categoryAxis.gridStrokeWidth = 0.25
categoryAxis.joinAxis = None
categoryAxis.joinAxisMode = None
categoryAxis.joinAxisPos = None
categoryAxis.labelAxisMode = 'axis'
categoryAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01081B70>
categoryAxis.reverseDirection = 0
categoryAxis.strokeColor = Color(0,0,0)
categoryAxis.strokeDashArray = None
categoryAxis.strokeWidth = 1
categoryAxis.style = 'parallel'
categoryAxis.tickDown = 5
categoryAxis.tickShift = 0
categoryAxis.tickUp = 0
categoryAxis.visible = 1
categoryAxis.visibleAxis = 1
categoryAxis.visibleGrid = 0
categoryAxis.visibleLabels = 1
categoryAxis.visibleTicks = 1
data = [(100, 110, 120, 130), (70, 80, 85, 90)]
debug = 0
fillColor = None
groupSpacing = 5
height = 85
naLabel = None
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
useAbsolute = 0
valueAxis.avoidBoundFrac = None
valueAxis.forceZero = 0
valueAxis.gridEnd = 0
valueAxis.gridStart = 0
valueAxis.gridStrokeColor = Color(0,0,0)
valueAxis.gridStrokeDashArray = None
valueAxis.gridStrokeWidth = 0.25
valueAxis.joinAxis = None
valueAxis.joinAxisMode = None
valueAxis.joinAxisPos = None
valueAxis.labelTextFormat = None
valueAxis.labelTextPostFormat = None
valueAxis.labelTextScale = None
valueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01081C38>
valueAxis.maximumTicks = 7
valueAxis.minimumTickSpacing = 10
valueAxis.rangeRound = 'none'
valueAxis.strokeColor = Color(0,0,0)
valueAxis.strokeDashArray = None
valueAxis.strokeWidth = 1
valueAxis.style = 'normal'
valueAxis.tickLeft = 5
valueAxis.tickRight = 0
valueAxis.valueMax = None
valueAxis.valueMin = None
valueAxis.valueStep = None
valueAxis.visible = 1
valueAxis.visibleAxis = 1
valueAxis.visibleGrid = 0
valueAxis.visibleLabels = 1
valueAxis.visibleTicks = 1
valueAxis.zrangePref = 0
width = 180
```



```
x = 20  
y = 10
```

## Functions

### **sampleH0a( ... )**

Make a slightly pathologic bar chart with only TWO data items.

#### *Example*

```
def sampleH0a():
    "Make a slightly pathologic bar chart with only TWO data items."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data

    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'se'
    bc.categoryAxis.labels.angle = 30
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH0b( ... )**

Make a pathologic bar chart with only ONE data item.

*Example*

```
def sampleH0b():
    "Make a pathologic bar chart with only ONE data item."

    drawing = Drawing(400, 200)

    data = [(42,)]


    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 50
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'se'
    bc.categoryAxis.labels.angle = 30
    bc.categoryAxis.categoryNames = ['Jan-99']

    drawing.add(bc)

    return drawing
```



**sampleH0c( ... )**

Make a really pathologic bar chart with NO data items at all!

*Example*

```
def sampleH0c():
    "Make a really pathologic bar chart with NO data items at all!"

    drawing = Drawing(400, 200)

    data = [()]


    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'se'
    bc.categoryAxis.labels.angle = 30
    bc.categoryAxis.categoryNames = []

    drawing.add(bc)

    return drawing
```



**sampleH1( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleH1():
    "Sample of multi-series bar chart."

    drawing = Drawing(400, 200)


    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (14, 6, 21, 23, 38, 46, 20, 5)
    ]

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    catNames = string.split('Jan Feb Mar Apr May Jun Jul Aug', ' ')
    catNames = map(lambda n:n+'-99', catNames)
    bc.categoryAxis.categoryNames = catNames
    drawing.add(bc, 'barchart')

    return drawing
```



**sampleH2a( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleH2a():
    "Sample of multi-series bar chart."

    data = [(2.4, -5.7, 2, 5, 9.2),
            (0.6, -4.9, -3, 4, 6.8)
            ]

    labels = ("Q3 2000", "Year to Date", "12 months",
              "Annualised\n3 years", "Since 07.10.99")

    drawing = Drawing(400, 200)

    bc = HorizontalBarChart()
    bc.x = 80
    bc.y = 50
    bc.height = 120
    bc.width = 300
    bc.data = data


    bc.barSpacing = 0
    bc.groupSpacing = 10
    bc.barWidth = 10

    bc.valueAxis.valueMin = -15
    bc.valueAxis.valueMax = +15
    bc.valueAxis.valueStep = 5
    bc.valueAxis.labels.fontName = 'Helvetica'
    bc.valueAxis.labels.fontSize = 8
    bc.valueAxis.labels.boxAnchor = 'n' # irrelevant (becomes 'c')
    bc.valueAxis.labels.textAnchor = 'middle'
    bc.valueAxis.configure(bc.data)

    bc.categoryAxis.categoryNames = labels
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 8
    bc.categoryAxis.labels.dx = -150

    drawing.add(bc)

    return drawing
```



**sampleH2b( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleH2b():
    "Sample of multi-series bar chart."

    data = [(2.4, -5.7, 2, 5, 9.2),
            (0.6, -4.9, -3, 4, 6.8)
            ]

    labels = ("Q3 2000", "Year to Date", "12 months",
              "Annualised\n3 years", "Since 07.10.99")

    drawing = Drawing(400, 200)

    bc = HorizontalBarChart()
    bc.x = 80
    bc.y = 50
    bc.height = 120
    bc.width = 300
    bc.data = data


    bc.barSpacing = 5
    bc.groupSpacing = 10
    bc.barWidth = 10

    bc.valueAxis.valueMin = -15
    bc.valueAxis.valueMax = +15
    bc.valueAxis.valueStep = 5
    bc.valueAxis.labels.fontName = 'Helvetica'
    bc.valueAxis.labels.fontSize = 8
    bc.valueAxis.labels.boxAnchor = 'n' # irrelevant (becomes 'c')
    bc.valueAxis.labels.textAnchor = 'middle'

    bc.categoryAxis.categoryNames = labels
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 8
    bc.categoryAxis.labels.dx = -150

    drawing.add(bc)

    return drawing
```



**sampleH2c( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleH2c():
    "Sample of multi-series bar chart."

    data = [(2.4, -5.7, 2, 5, 9.99),
            (0.6, -4.9, -3, 4, 9.99)
            ]

    labels = ("Q3 2000", "Year to Date", "12 months",
              "Annualised\n3 years", "Since 07.10.99")

    drawing = Drawing(400, 200)

    bc = HorizontalBarChart()
    bc.x = 80
    bc.y = 50
    bc.height = 120
    bc.width = 300
    bc.data = data

    bc.barSpacing = 2
    bc.groupSpacing = 10
    bc.barWidth = 10

    bc.valueAxis.valueMin = -15
    bc.valueAxis.valueMax = +15
    bc.valueAxis.valueStep = 5
    bc.valueAxis.labels.fontName = 'Helvetica'
    bc.valueAxis.labels.fontSize = 8
    bc.valueAxis.labels.boxAnchor = 'n'
    bc.valueAxis.labels.textAnchor = 'middle'

    bc.categoryAxis.categoryNames = labels
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 8
    bc.categoryAxis.labels.dx = -150


    bc.barLabels.nudge = 10

    bc.barLabelFormat = '%0.2f'
    bc.barLabels.dx = 0
    bc.barLabels.dy = 0
    bc.barLabels.boxAnchor = 'n' # irrelevant (becomes 'c')
    bc.barLabels.fontName = 'Helvetica'
    bc.barLabels.fontSize = 6

    drawing.add(bc)

    return drawing
```





**sampleH3( ... )**

A really horizontal bar chart (compared to the equivalent faked one).

*Example*

```
def sampleH3():
    "A really horizontal bar chart (compared to the equivalent faked one)."
```

```
    names = ("UK Equities", "US Equities", "European Equities", "Japanese Equities",
             "Pacific (ex Japan) Equities", "Emerging Markets Equities",
             "UK Bonds", "Overseas Bonds", "UK Index-Linked", "Cash")

    series1 = (-1.5, 0.3, 0.5, 1.0, 0.8, 0.7, 0.4, 0.1, 1.0, 0.3)
    series2 = (0.0, 0.33, 0.55, 1.1, 0.88, 0.77, 0.44, 0.11, 1.10, 0.33)

    assert len(names) == len(series1), "bad data"
    assert len(names) == len(series2), "bad data"

    drawing = Drawing(400, 200)

    bc = HorizontalBarChart()
    bc.x = 100
    bc.y = 20
    bc.height = 150
    bc.width = 250
    bc.data = (series1,)
    bc.bars.fillColor = colors.green


    bc.barLabelFormat = '%0.2f'
    bc.barLabels.dx = 0
    bc.barLabels.dy = 0
    bc.barLabels.boxAnchor = 'w' # irrelevant (becomes 'c')
    bc.barLabels.fontName = 'Helvetica'
    bc.barLabels.fontSize = 6
    bc.barLabels.nudge = 10

    bc.valueAxis.visible = 0
    bc.valueAxis.valueMin = -2
    bc.valueAxis.valueMax = +2
    bc.valueAxis.valueStep = 1

    bc.categoryAxis.tickLeft = 0
    bc.categoryAxis.tickRight = 0
    bc.categoryAxis.categoryNames = names
    bc.categoryAxis.labels.boxAnchor = 'w'
    bc.categoryAxis.labels.dx = -170
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 6

    g = Group(bc)
    drawing.add(g)

    return drawing
```



**sampleH4a( ... )**

A bar chart showing value axis region starting at *\*exactly\** zero.

*Example*

```
def sampleH4a():
    "A bar chart showing value axis region starting at *exactly* zero."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH4b( ... )**

A bar chart showing value axis region starting *\*below\** zero.

*Example*

```
def sampleH4b():
    "A bar chart showing value axis region starting *below* zero."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = -10
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH4c( ... )**

A bar chart showing value axis region starting *above* zero.

*Example*

```
def sampleH4c():
    "A bar chart showing value axis region starting above zero."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 10
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH4d( ... )**

A bar chart showing value axis region entirely *\*below\** zero.

*Example*

```
def sampleH4d():
    "A bar chart showing value axis region entirely *below* zero."

    drawing = Drawing(400, 200)

    data = [(-13, -20)]

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = -30
    bc.valueAxis.valueMax = -10
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH5a( ... )**

A simple bar chart with no expressed spacing attributes.

*Example*

```
def sampleH5a():
    "A simple bar chart with no expressed spacing attributes."

    drawing = Drawing(400, 200)

    data = dataSample5


    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```





**sampleH5b( ... )**

A simple bar chart with proportional spacing.

*Example*

```
def sampleH5b():
    "A simple bar chart with proportional spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 0
    bc.barWidth = 40
    bc.groupSpacing = 20
    bc.barSpacing = 10

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH5c1( ... )**

A simple bar chart with absolute spacing.

*Example*

```
def sampleH5c1():
    "A simple bar chart with absolute spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 1
    bc.barWidth = 10
    bc.groupSpacing = 0
    bc.barSpacing = 0

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH5c2( ... )**

Simple bar chart with absolute spacing.

*Example*

```
def sampleH5c2():
    "Simple bar chart with absolute spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 1
    bc.barWidth = 10
    bc.groupSpacing = 20
    bc.barSpacing = 0

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleH5c3( ... )**

Simple bar chart with absolute spacing.

*Example*

```
def sampleH5c3():
    "Simple bar chart with absolute spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = HorizontalBarChart()
    bc.x = 50
    bc.y = 20
    bc.height = 155
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 1
    bc.barWidth = 10
    bc.groupSpacing = 0
    bc.barSpacing = 2

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']


    drawing.add(bc)

    return drawing
```



**sampleH5c4( ... )**

Simple bar chart with absolute spacing.

*Example*

**sampleStacked1( ... )**

Simple bar chart using symbol attribute.

*Example*

```
def sampleStacked1():
    "Simple bar chart using symbol attribute."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = VerticalBarChart()
    bc.categoryAxis.style = 'stacked'
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.barWidth = 10
    bc.groupSpacing = 15
    bc.valueAxis.valueMin = 0

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    from reportlab.graphics.widgets.grids import ShadedRect
    bc.bars.symbol = ShadedRect()
    bc.bars.symbol.fillColorStart = colors.red
    bc.bars.symbol.fillColorEnd = colors.white
    bc.bars.symbol.orientation = 'vertical'
    bc.bars.symbol.cylinderMode = 1
    bc.bars.symbol.strokeWidth = 0


    bc.bars[1].symbol = ShadedRect()
    bc.bars[1].symbol.fillColorStart = colors.magenta
    bc.bars[1].symbol.fillColorEnd = colors.white
    bc.bars[1].symbol.orientation = 'vertical'
    bc.bars[1].symbol.cylinderMode = 1
    bc.bars[1].symbol.strokeWidth = 0

    bc.bars[2].symbol = ShadedRect()
    bc.bars[2].symbol.fillColorStart = colors.green
    bc.bars[2].symbol.fillColorEnd = colors.white
    bc.bars[2].symbol.orientation = 'vertical'
    bc.bars[2].symbol.cylinderMode = 1
    bc.bars[2].symbol.strokeWidth = 0

    bc.bars[3].symbol = ShadedRect()
    bc.bars[3].symbol.fillColorStart = colors.blue
    bc.bars[3].symbol.fillColorEnd = colors.white
    bc.bars[3].symbol.orientation = 'vertical'
    bc.bars[3].symbol.cylinderMode = 1
    bc.bars[3].symbol.strokeWidth = 0

    drawing.add(bc)

    return drawing
```



**sampleSymbol1( ... )**

Simple bar chart using symbol attribute.

*Example*

```
def sampleSymbol1():
    "Simple bar chart using symbol attribute."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.barWidth = 10
    bc.groupSpacing = 15
    bc.barSpacing = 3

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'e'
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    from reportlab.graphics.widgets.grids import ShadedRect
    sym1 = ShadedRect()
    sym1.fillColorStart = colors.black
    sym1.fillColorEnd = colors.blue
    sym1.orientation = 'horizontal'
    sym1.strokeWidth = 0

    sym2 = ShadedRect()
    sym2.fillColorStart = colors.black
    sym2.fillColorEnd = colors.pink
    sym2.orientation = 'horizontal'
    sym2.strokeWidth = 0


    sym3 = ShadedRect()
    sym3.fillColorStart = colors.blue
    sym3.fillColorEnd = colors.white
    sym3.orientation = 'vertical'
    sym3.cylinderMode = 1
    sym3.strokeWidth = 0

    bc.bars.symbol = sym1
    bc.bars[2].symbol = sym2
    bc.bars[3].symbol = sym3

    drawing.add(bc)

    return drawing
```





**sampleV0a( ... )**

A slightly pathologic bar chart with only TWO data items.

*Example*

```
def sampleV0a():
    "A slightly pathologic bar chart with only TWO data items."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'ne'
    bc.categoryAxis.labels.dx = 8
    bc.categoryAxis.labels.dy = -2
    bc.categoryAxis.labels.angle = 30
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV0b( ... )**

A pathologic bar chart with only ONE data item.

*Example*

```
def sampleV0b():
    "A pathologic bar chart with only ONE data item."

    drawing = Drawing(400, 200)

    data = [(42,)]


    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 50
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'ne'
    bc.categoryAxis.labels.dx = 8
    bc.categoryAxis.labels.dy = -2
    bc.categoryAxis.labels.angle = 30
    bc.categoryAxis.categoryNames = ['Jan-99']

    drawing.add(bc)

    return drawing
```



**sampleV0c( ... )**

A really pathologic bar chart with NO data items at all!

*Example*

```
def sampleV0c():
    "A really pathologic bar chart with NO data items at all!"

    drawing = Drawing(400, 200)

    data = [()]


    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'ne'
    bc.categoryAxis.labels.dx = 8
    bc.categoryAxis.labels.dy = -2
    bc.categoryAxis.categoryNames = []

    drawing.add(bc)

    return drawing
```



**sampleV1( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleV1():
    "Sample of multi-series bar chart."

    drawing = Drawing(400, 200)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (14, 6, 21, 23, 38, 46, 20, 5)
    ]


    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'ne'
    bc.categoryAxis.labels.dx = 8
    bc.categoryAxis.labels.dy = -2
    bc.categoryAxis.labels.angle = 30

    catNames = string.split('Jan Feb Mar Apr May Jun Jul Aug', ' ')
    catNames = map(lambda n:n+'-99', catNames)
    bc.categoryAxis.categoryNames = catNames
    drawing.add(bc)

    return drawing
```



**sampleV2a( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleV2a():
    "Sample of multi-series bar chart."

    data = [(2.4, -5.7, 2, 5, 9.2),
            (0.6, -4.9, -3, 4, 6.8)
            ]

    labels = ("Q3 2000", "Year to Date", "12 months",
              "Annualised\n3 years", "Since 07.10.99")

    drawing = Drawing(400, 200)

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 120
    bc.width = 300
    bc.data = data


    bc.barSpacing = 0
    bc.groupSpacing = 10
    bc.barWidth = 10

    bc.valueAxis.valueMin = -15
    bc.valueAxis.valueMax = +15
    bc.valueAxis.valueStep = 5
    bc.valueAxis.labels.fontName = 'Helvetica'
    bc.valueAxis.labels.fontSize = 8
    bc.valueAxis.labels.boxAnchor = 'n' # irrelevant (becomes 'c')
    bc.valueAxis.labels.textAnchor = 'middle'

    bc.categoryAxis.categoryNames = labels
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 8
    bc.categoryAxis.labels.dy = -60

    drawing.add(bc)

    return drawing
```



**sampleV2b( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleV2b():
    "Sample of multi-series bar chart."

    data = [(2.4, -5.7, 2, 5, 9.2),
            (0.6, -4.9, -3, 4, 6.8)
            ]

    labels = ("Q3 2000", "Year to Date", "12 months",
              "Annualised\n3 years", "Since 07.10.99")

    drawing = Drawing(400, 200)

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 120
    bc.width = 300
    bc.data = data


    bc.barSpacing = 5
    bc.groupSpacing = 10
    bc.barWidth = 10

    bc.valueAxis.valueMin = -15
    bc.valueAxis.valueMax = +15
    bc.valueAxis.valueStep = 5
    bc.valueAxis.labels.fontName = 'Helvetica'
    bc.valueAxis.labels.fontSize = 8
    bc.valueAxis.labels.boxAnchor = 'n' # irrelevant (becomes 'c')
    bc.valueAxis.labels.textAnchor = 'middle'

    bc.categoryAxis.categoryNames = labels
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 8
    bc.categoryAxis.labels.dy = -60

    drawing.add(bc)

    return drawing
```



**sampleV2c( ... )**

Sample of multi-series bar chart.

*Example*

```
def sampleV2c():
    "Sample of multi-series bar chart."

    data = [(2.4, -5.7, 2, 5, 9.99),
            (0.6, -4.9, -3, 4, 9.99)
            ]

    labels = ("Q3 2000", "Year to Date", "12 months",
             "Annualised\n3 years", "Since 07.10.99")

    drawing = Drawing(400, 200)

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 120
    bc.width = 300
    bc.data = data

    bc.barSpacing = 2
    bc.groupSpacing = 10
    bc.barWidth = 10

    bc.valueAxis.valueMin = -15
    bc.valueAxis.valueMax = +15
    bc.valueAxis.valueStep = 5
    bc.valueAxis.labels.fontName = 'Helvetica'
    bc.valueAxis.labels.fontSize = 8

    bc.categoryAxis.categoryNames = labels
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 8
    bc.valueAxis.labels.boxAnchor = 'n'
    bc.valueAxis.labels.textAnchor = 'middle'
    bc.categoryAxis.labels.dy = -60


    bc.barLabels.nudge = 10

    bc.barLabelFormat = '%0.2f'
    bc.barLabels.dx = 0
    bc.barLabels.dy = 0
    bc.barLabels.boxAnchor = 'n' # irrelevant (becomes 'c')
    bc.barLabels.fontName = 'Helvetica'
    bc.barLabels.fontSize = 6

    drawing.add(bc)

    return drawing
```





**sampleV3( ... )**

Faked horizontal bar chart using a vertical real one (deprecated).

*Example*

```
def sampleV3():
    "Faked horizontal bar chart using a vertical real one (deprecated)."
```

```
    names = ("UK Equities", "US Equities", "European Equities", "Japanese Equities",
             "Pacific (ex Japan) Equities", "Emerging Markets Equities",
             "UK Bonds", "Overseas Bonds", "UK Index-Linked", "Cash")

    series1 = (-1.5, 0.3, 0.5, 1.0, 0.8, 0.7, 0.4, 0.1, 1.0, 0.3)
    series2 = (0.0, 0.33, 0.55, 1.1, 0.88, 0.77, 0.44, 0.11, 1.10, 0.33)

    assert len(names) == len(series1), "bad data"
    assert len(names) == len(series2), "bad data"

    drawing = Drawing(400, 200)

    bc = VerticalBarChart()
    bc.x = 0
    bc.y = 0
    bc.height = 100
    bc.width = 150
    bc.data = (series1,)
    bc.bars.fillColor = colors.green

    bc.barLabelFormat = '%0.2f'
    bc.barLabels.dx = 0
    bc.barLabels.dy = 0
    bc.barLabels.boxAnchor = 'w' # irrelevant (becomes 'c')
    bc.barLabels.angle = 90
    bc.barLabels.fontName = 'Helvetica'
    bc.barLabels.fontSize = 6
    bc.barLabels.nudge = 10


    bc.valueAxis.visible = 0
    bc.valueAxis.valueMin = -2
    bc.valueAxis.valueMax = +2
    bc.valueAxis.valueStep = 1

    bc.categoryAxis.tickUp = 0
    bc.categoryAxis.tickDown = 0
    bc.categoryAxis.categoryNames = names
    bc.categoryAxis.labels.angle = 90
    bc.categoryAxis.labels.boxAnchor = 'w'
    bc.categoryAxis.labels.dx = 0
    bc.categoryAxis.labels.dy = -125
    bc.categoryAxis.labels.fontName = 'Helvetica'
    bc.categoryAxis.labels.fontSize = 6

    g = Group(bc)
    g.translate(100, 175)
    g.rotate(-90)

    drawing.add(g)

    return drawing
```



**sampleV4a( ... )**

A bar chart showing value axis region starting at *\*exactly\** zero.

*Example*

```
def sampleV4a():
    "A bar chart showing value axis region starting at *exactly* zero."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV4b( ... )**

A bar chart showing value axis region starting *\*below\** zero.

*Example*

```
def sampleV4b():
    "A bar chart showing value axis region starting *below* zero."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data

    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = -10
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV4c( ... )**

A bar chart showing value axis region starting *above* zero.

*Example*

```
def sampleV4c():
    "A bar chart showing value axis region starting above zero."

    drawing = Drawing(400, 200)

    data = [(13, 20)]

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 10
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV4d( ... )**

A bar chart showing value axis region entirely *\*below\** zero.

*Example*

```
def sampleV4d():
    "A bar chart showing value axis region entirely *below* zero."

    drawing = Drawing(400, 200)

    data = [(-13, -20)]

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data


    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = -30
    bc.valueAxis.valueMax = -10
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV5a( ... )**

A simple bar chart with no expressed spacing attributes.

*Example*

```
def sampleV5a():
    "A simple bar chart with no expressed spacing attributes."

    drawing = Drawing(400, 200)

    data = dataSample5


    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```





**sampleV5b( ... )**

A simple bar chart with proportional spacing.

*Example*

```
def sampleV5b():
    "A simple bar chart with proportional spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 0
    bc.barWidth = 40
    bc.groupSpacing = 20
    bc.barSpacing = 10

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV5c1( ... )**

Make sampe simple bar chart but with absolute spacing.

*Example*

```
def sampleV5c1():
    "Make sampe simple bar chart but with absolute spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 1
    bc.barWidth = 40
    bc.groupSpacing = 0
    bc.barSpacing = 0

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV5c2( ... )**

Make sampe simple bar chart but with absolute spacing.

*Example*

```
def sampleV5c2():
    "Make sampe simple bar chart but with absolute spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 1
    bc.barWidth = 40
    bc.groupSpacing = 20
    bc.barSpacing = 0

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV5c3( ... )**

Make sampe simple bar chart but with absolute spacing.

*Example*

```
def sampleV5c3():
    "Make sampe simple bar chart but with absolute spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black

    bc.useAbsolute = 1
    bc.barWidth = 40
    bc.groupSpacing = 0
    bc.barSpacing = 10

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



**sampleV5c4( ... )**

Make sampe simple bar chart but with absolute spacing.

*Example*

```
def sampleV5c4():
    "Make sampe simple bar chart but with absolute spacing."

    drawing = Drawing(400, 200)

    data = dataSample5

    bc = VerticalBarChart()
    bc.x = 50
    bc.y = 50
    bc.height = 125
    bc.width = 300
    bc.data = data
    bc.strokeColor = colors.black


    bc.useAbsolute = 1
    bc.barWidth = 40
    bc.groupSpacing = 20
    bc.barSpacing = 10

    bc.valueAxis.valueMin = 0
    bc.valueAxis.valueMax = 60
    bc.valueAxis.valueStep = 15

    bc.categoryAxis.labels.boxAnchor = 'n'
    bc.categoryAxis.labels.dy = -5
    bc.categoryAxis.categoryNames = ['Ying', 'Yang']

    drawing.add(bc)

    return drawing
```



## dotbox

### Classes

#### DotBox(Widget)

Returns a dotbox widget.

### Public Attributes

**dotColor** Colour of the circle on the box

**dotDiameter** Diameter of the circle used for the 'dot'

**dotXPosition** X Position of the circle

**dotYPosition** X Position of the circle

**gridColor** Colour for the box and gridding

**gridDivWidth** Width of each 'box'

**labelFontName** Name of font used for the labels

**labelFontSize** Size of font used for the labels

**labelOffset** Space between label text and grid edge

**strokeWidth** Width of the grid and dot outline

**x** X Position of dotbox


**xlables** List of text labels for boxes on left hand side

**y** Y Position of dotbox

**ylables** Text label for second box on left hand side

#### Example

```
def demo(self,drawing=None):
    if not drawing:
        tx,ty=self._getDrawingDimensions()
        drawing = Drawing(tx,ty)
        drawing.add(self.draw())
    return drawing
```



#### Properties of Example Widget

```
dotColor = Color(.909804,.878431,.466667)
dotDiameter = 11.338582677165356
dotXPosition = 1
dotYPosition = 1
gridColor = Color(.098039,.301961,.529412)
gridDivWidth = 14.173228346456693
labelFontName = 'Helvetica'
labelFontSize = 6
```

```
labelOffset = 5
strokeWidth = 0.5
x = 30
xlabels = ['Value', 'Blend', 'Growth']
y = 5
ylabels = ['Small', 'Medium', 'Large']
```

## doughnut

Doughnut chart

Produces a circular chart like the doughnut charts produced by Excel.  
Can handle multiple series (which produce concentric 'rings' in the chart).

## Classes

### Doughnut (AbstractPieChart)

#### Public Attributes

**data** list of numbers defining sector sizes; need not sum to 1

**direction** 'clockwise' or 'anticlockwise'

**height** height of doughnut bounding box. Need not be same as height.

**labels** optional list of labels to use for each data point

**simpleLabels** If true(default) use String not super duper WedgeLabel

**slices** collection of sector descriptor objects

**startAngle** angle of first slice; like the compass, 0 is due North

**width** width of doughnut bounding box. Need not be same as width.

**x** X position of the chart within its container.

**y** Y position of the chart within its container.

#### Example


```
def demo(self):
    d = Drawing(200, 100)

    dn = Doughnut()
    dn.x = 50
    dn.y = 10
    dn.width = 100
    dn.height = 80
    dn.data = [10,20,30,40,50,60]
    dn.labels = ['a','b','c','d','e','f']

    dn.slices.strokeWidth=0.5
    dn.slices[3].popout = 10
    dn.slices[3].strokeWidth = 2
    dn.slices[3].strokeDashArray = [2,2]
    dn.slices[3].labelRadius = 1.75
    dn.slices[3].fontColor = colors.red
    dn.slices[0].fillColor = colors.darkcyan
    dn.slices[1].fillColor = colors.blueviolet
    dn.slices[2].fillColor = colors.blue
    dn.slices[3].fillColor = colors.cyan
    dn.slices[4].fillColor = colors.aquamarine
    dn.slices[5].fillColor = colors.cadetblue
    dn.slices[6].fillColor = colors.lightcoral

    d.add(dn)
    return d
```





#### *Properties of Example Widget*

```
data = [1, 1]
direction = 'clockwise'
height = 100
labels = None
simpleLabels = 1
slices = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0126A968>
startAngle = 90
width = 100
x = 0
y = 0
```

## Functions

### **sample1( ... )**

Make up something from the individual Sectors

#### *Example*

```
def sample1():
    "Make up something from the individual Sectors"

    d = Drawing(400, 400)
    g = Group()

    s1 = Wedge(centerx=200, centery=200, radius=150, startangleddegrees=0, endangleddegrees=120, radius=150)
    s1.fillColor=colors.red
    s1.strokeColor=None
    d.add(s1)
    s2 = Wedge(centerx=200, centery=200, radius=150, startangleddegrees=120, endangleddegrees=240, radius=150)
    s2.fillColor=colors.green
    s2.strokeColor=None
    d.add(s2)
    s3 = Wedge(centerx=200, centery=200, radius=150, startangleddegrees=240, endangleddegrees=260, radius=150)
    s3.fillColor=colors.blue
    s3.strokeColor=None
    d.add(s3)
    s4 = Wedge(centerx=200, centery=200, radius=150, startangleddegrees=260, endangleddegrees=360, radius=150)
    s4.fillColor=colors.gray
    s4.strokeColor=None
    d.add(s4)

    return d
```




**sample2( ... )**

Make a simple demo

*Example*

```
def sample2():  
    "Make a simple demo"  
  
    d = Drawing(400, 400)  
  
    dn = Doughnut()  
    dn.x = 50  
    dn.y = 50  
    dn.width = 300  
    dn.height = 300  
    dn.data = [10,20,30,40,50,60]  
  
    d.add(dn)  
  
    return d
```




**sample3( ... )**

Make a more complex demo

*Example*

```
def sample3():  
    "Make a more complex demo"  
  
    d = Drawing(400, 400)  
    dn = Doughnut()  
    dn.x = 50  
    dn.y = 50  
    dn.width = 300  
    dn.height = 300  
    dn.data = [[10,20,30,40,50,60], [10,20,30,40]]  
    dn.labels = ['a','b','c','d','e','f']  
  
    d.add(dn)  
  
    return d
```



## legends

This will be a collection of legends to be used with charts.

## Classes

### Legend(Widget)

A simple legend containing rectangular swatches and strings.

The swatches are filled rectangles whenever the respective color object in 'colorNamePairs' is a subclass of Color in reportlab.lib.colors. Otherwise the object passed instead is assumed to have 'x', 'y', 'width' and 'height' attributes.

A legend then tries to set them or catches any error. This lets you plug-in any widget you like as a replacement for the default rectangular swatches.

Strings can be nicely aligned left or right to the swatches.

### Public Attributes

**alignment** Alignment of text with respect to swatches

**autoXPadding** x Padding between columns if deltax=None

**autoYPadding** y Padding between rows if deltax=None

**boxAnchor** Anchor point for the legend area

**callout** a user callout(self,g,x,y,(color,text))

**colEndCallout** a user callout(self,g, x, xt, y,width, lWidth)

**colorNamePairs** List of color/name tuples (color can also be widget)

**columnMaximum** Max. number of items per column

**deltax** x-distance between neighbouring swatches

**deltay** y-distance between neighbouring swatches

**dividerColor** dividerLines color

**dividerDashArray** Dash array for dividerLines.

**dividerLines** If 1 we have dividers between the rows | 2 for extra top | 4 for bottom

**dividerOffsX** divider lines X offsets

**dividerOffsY** dividerLines Y offset

**dividerWidth** dividerLines width

**dx** Width of swatch rectangle

**dxTextSpace** Distance between swatch rectangle and text

**dy** Height of swatch rectangle

**fillColor**

**fontName** Font name of the strings

**fontSize** Font size of the strings

**sepSpace** separator spacing

**strokeColor** Border color of the swatches

**strokeWidth** Width of the border color of the swatches

**swatchMarker** None, Auto() or makeMarker('Diamond') ...

**variColumn** If true column widths may vary (default is false)

**x** x-coordinate of upper-left reference point

**y** y-coordinate of upper-left reference point

**yGap** Additional gap between rows

#### *Example*

```
def demo(self):
    "Make sample legend."

    d = Drawing(200, 100)

    legend = Legend()
    legend.alignment = 'left'
    legend.x = 0
    legend.y = 100
    legend.dxTextSpace = 5
    items = 'red green blue yellow pink black white'.split()
    items = map(lambda i:(getattr(colors, i), i), items)
    legend.colorNamePairs = items

    d.add(legend, 'legend')

    return d
```

#### *Properties of Example Widget*

```
alignment = 'left'
autoXPadding = 5
autoYPadding = 2
boxAnchor = 'nw'
colEndCallout = None
colorNamePairs = [(Color(1,0,0), 'red'),
                  (Color(0,0,1), 'blue'),
                  (Color(0,.501961,0), 'green'),
                  (Color(1,.752941,.796078), 'pink'),
                  (Color(1,1,0), 'yellow')]
columnMaximum = 3
deltax = 75
deltay = 20
dividerColor = Color(0,0,0)
dividerDashArray = None
dividerLines = 0
dividerOffsX = (0, 0)
dividerOffsY = 0
dividerWidth = 0.5
dx = 10
dxTextSpace = 10
dy = 10
fillColor = Color(0,0,0)
fontName = 'Times-Roman'
fontSize = 10
sepSpace = 0
strokeColor = Color(0,0,0)
strokeWidth = 1
swatchMarker = None
variColumn = 0
x = 0
y = 0
yGap = 0
```

## LineLegend ( Legend )

A subclass of Legend for drawing legends with lines as the swatches rather than rectangles. Useful for lineCharts and linePlots. Should be similar in all other ways the the standard Legend class.

### Public Attributes

**alignment** Alignment of text with respect to swatches

**autoXPadding** x Padding between columns if deltax=None

**autoYPadding** y Padding between rows if deltax=None

**boxAnchor** Anchor point for the legend area

**callout** a user callout(self,g,x,y,(color,text))

**colEndCallout** a user callout(self,g, x, xt, y,width, lWidth)

**colorNamePairs** List of color/name tuples (color can also be widget)

**columnMaximum** Max. number of items per column

**deltax** x-distance between neighbouring swatches

**deltay** y-distance between neighbouring swatches

**dividerColor** dividerLines color

**dividerDashArray** Dash array for dividerLines.

**dividerLines** If 1 we have dividers between the rows | 2 for extra top | 4 for bottom

**dividerOffsX** divider lines X offsets

**dividerOffsY** dividerLines Y offset

**dividerWidth** dividerLines width

**dx** Width of swatch rectangle

**dxTextSpace** Distance between swatch rectangle and text

**dy** Height of swatch rectangle

**fillColor**

**fontName** Font name of the strings

**fontSize** Font size of the strings

**sepSpace** separator spacing

**strokeColor** Border color of the swatches

**strokeWidth** Width of the border color of the swatches

**swatchMarker** None, Auto() or makeMarker('Diamond') ...

**variColumn** If true column widths may vary (default is false)

**x** x-coordinate of upper-left reference point

**y** y-coordinate of upper-left reference point

**yGap** Additional gap between rows

#### *Example*

```
def demo(self):
```



```
"Make sample legend."

d = Drawing(200, 100)

legend = Legend()
legend.alignment = 'left'
legend.x = 0
legend.y = 100
legend.dxTextSpace = 5
items = 'red green blue yellow pink black white'.split()
items = map(lambda i:(getattr(colors, i), i), items)
legend.colorNamePairs = items

d.add(legend, 'legend')

return d
```

### *Properties of Example Widget*

```
alignment = 'left'
autoXPadding = 5
autoYPadding = 2
boxAnchor = 'nw'
colEndCallout = None
colorNamePairs = [(Color(1,0,0), 'red'),
                  (Color(0,0,1), 'blue'),
                  (Color(0,.501961,0), 'green'),
                  (Color(1,.752941,.796078), 'pink'),
                  (Color(1,1,0), 'yellow')]
columnMaximum = 3
deltax = 75
deltay = 20
dividerColor = Color(0,0,0)
dividerDashArray = None
dividerLines = 0
dividerOffsX = (0, 0)
dividerOffsY = 0
dividerWidth = 0.5
dx = 10
dxTextSpace = 10
dy = 2
fillColor = Color(0,0,0)
fontName = 'Times-Roman'
fontSize = 10
sepSpace = 0
strokeColor = Color(0,0,0)
strokeWidth = 1
swatchMarker = None
varColumn = 0
x = 0
y = 0
yGap = 0
```

## LineSwatch(Widget)

basically a Line with properties added so it can be used in a LineLegend

### Public Attributes

**height** used for line strokeWidth

**strokeColor** color of swatch line

**strokeDashArray** dash array for swatch line

**width** length of swatch line

**x** x-coordinate for swatch line start point

**y** y-coordinate for swatch line start point

### *Example*

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

### *Properties of Example Widget*

```
height = 1
strokeColor = Color(1,0,0)
strokeDashArray = None
width = 20
x = 0
y = 0
```

## Functions

### **sample1c( ... )**

Make sample legend.

#### *Example*








```
def sample1c():
    "Make sample legend."

    d = Drawing(200, 100)

    legend = Legend()
    legend.alignment = 'right'
    legend.x = 0
    legend.y = 100
    legend.dxTextSpace = 5
    items = 'red green blue yellow pink black white'.split()
    items = map(lambda i:(getattr(colors, i), i), items)
    legend.colorNamePairs = items

    d.add(legend, 'legend')

    return d
```

 red	 yellow	 white
 green	 pink	
 blue	 black	

**sample2c( ... )**

Make sample legend.

*Example*








```
def sample2c():
    "Make sample legend."

    d = Drawing(200, 100)

    legend = Legend()
    legend.alignment = 'right'
    legend.x = 20
    legend.y = 90
    legend.deltax = 60
    legend.dxTextSpace = 10
    legend.columnMaximum = 4
    items = 'red green blue yellow pink black white'.split()
    items = map(lambda i:(getattr(colors, i), i), items)
    legend.colorNamePairs = items

    d.add(legend, 'legend')

    return d
```

	red		pink
	green		black
	blue		white
	yellow		

**sample3( ... )**

Make sample legend with line swatches.







*Example*

```
def sample3():
    "Make sample legend with line swatches."

    d = Drawing(200, 100)

    legend = LineLegend()
    legend.alignment = 'right'
    legend.x = 20
    legend.y = 90
    legend.deltax = 60
    legend.dxTextSpace = 10
    legend.columnMaximum = 4
    items = 'red green blue yellow pink black white'.split()
    items = map(lambda i:(getattr(colors, i), i), items)
    legend.colorNamePairs = items
    d.add(legend, 'legend')

    return d
```

	red		pink
	green		black
	blue		white
	yellow		

**sample3a( ... )**

Make sample legend with line swatches and dasharrays on the lines.

*Example*

```
def sample3a():
    "Make sample legend with line swatches and dasharrays on the lines."

    d = Drawing(200, 100)

    legend = LineLegend()
    legend.alignment = 'right'
    legend.x = 20
    legend.y = 90
    legend.deltax = 60
    legend.dxTextSpace = 10
    legend.columnMaximum = 4
    items = 'red green blue yellow pink black white'.split()
    darrays = ([2,1], [2,5], [2,2,5,5], [1,2,3,4], [4,2,3,4], [1,2,3,4,5,6], [1])
    cnp = []
    for i in range(0, len(items)):
        l = LineSwatch()
        l.strokeColor = getattr(colors, items[i])
        l.strokeDashArray = darrays[i]
        cnp.append((l, items[i]))
    legend.colorNamePairs = cnp
    d.add(legend, 'legend')

    return d
```

...	red	- -	pink
■ ■	green	..	black
■ ■	blue		white
■ ■	yellow		

## linecharts

This module defines a very preliminary Line Chart example.

### Classes

#### AbstractLineChart (PlotArea)

##### Public Attributes

**background** Handle to background object.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

##### *Example*

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

##### *Properties of Example Widget*

```
background = None
debug = 0
fillColor = None
height = 85
strokeColor = None
strokeWidth = 1
width = 180
x = 20
y = 10
```

## HorizontalLineChart (LineChart)

Line chart with multiple lines.

A line chart is assumed to have one category and one value axis. Despite its generic name this particular line chart class has a vertical value axis and a horizontal category one. It may evolve into individual horizontal and vertical variants (like with the existing bar charts).

Available attributes are:

x: x-position of lower-left chart origin

y: y-position of lower-left chart origin

width: chart width

height: chart height

useAbsolute: disables auto-scaling of chart elements (?)

lineLabelNudge: distance of data labels to data points

lineLabels: labels associated with data values

lineLabelFormat: format string or callback function

groupSpacing: space between categories

joinedLines: enables drawing of lines

strokeColor: color of chart lines (?)

fillColor: color for chart background (?)

lines: style list, used cyclically for data series

valueAxis: value axis object

categoryAxis: category axis object

categoryNames: category names

data: chart data, a list of data series of equal length

## Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**categoryAxis** Handle of the category axis.

**categoryNames** List of category names.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** ? - Likely to disappear.

**height** Height of the chart.

**inFill** Whether infilling should be done.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.



**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### *Example*

```
def demo(self):
    """Shows basic use of a line chart."""

    drawing = Drawing(200, 100)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (14, 10, 21, 28, 38, 46, 25, 5)
    ]

    lc = HorizontalLineChart()

    lc.x = 20
    lc.y = 10
    lc.height = 85
    lc.width = 170
    lc.data = data
    lc.lines.symbol = makeMarker('Circle')

    drawing.add(lc)

    return drawing
```

### *Properties of Example Widget*

```
background = None
categoryAxis.categoryNames = None
categoryAxis.gridEnd = 0
categoryAxis.gridStart = 0
categoryAxis.gridStrokeColor = Color(0,0,0)
categoryAxis.gridStrokeDashArray = None
categoryAxis.gridStrokeWidth = 0.25
categoryAxis.joinAxis = None
categoryAxis.joinAxisMode = None
categoryAxis.joinAxisPos = None
categoryAxis.labelAxisMode = 'axis'
categoryAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01319030>
categoryAxis.reverseDirection = 0
categoryAxis.strokeColor = Color(0,0,0)
categoryAxis.strokeDashArray = None
categoryAxis.strokeWidth = 1
categoryAxis.style = 'parallel'
categoryAxis.tickDown = 5
categoryAxis.tickShift = 0
categoryAxis.tickUp = 0
categoryAxis.visible = 1
categoryAxis.visibleAxis = 1
categoryAxis.visibleGrid = 0
categoryAxis.visibleLabels = 1
categoryAxis.visibleTicks = 1
categoryNames = ('North', 'South', 'East', 'West')
data = [(100, 110, 120, 130), (70, 80, 80, 90)]
```

```
debug = 0
fillColor = None
groupSpacing = 1
height = 85
inFill = 0
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01319350>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01319210>
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
useAbsolute = 0
valueAxis.avoidBoundFrac = None
valueAxis.forceZero = 0
valueAxis.gridEnd = 0
valueAxis.gridStart = 0
valueAxis.gridStrokeColor = Color(0,0,0)
valueAxis.gridStrokeDashArray = None
valueAxis.gridStrokeWidth = 0.25
valueAxis.joinAxis = None
valueAxis.joinAxisMode = None
valueAxis.joinAxisPos = None
valueAxis.labelTextFormat = None
valueAxis.labelTextPostFormat = None
valueAxis.labelTextScale = None
valueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013191C0>
valueAxis.maximumTicks = 7
valueAxis.minimumTickSpacing = 10
valueAxis.rangeRound = 'none'
valueAxis.strokeColor = Color(0,0,0)
valueAxis.strokeDashArray = None
valueAxis.strokeWidth = 1
valueAxis.style = 'normal'
valueAxis.tickLeft = 5
valueAxis.tickRight = 0
valueAxis.valueMax = None
valueAxis.valueMin = None
valueAxis.valueStep = None
valueAxis.visible = 1
valueAxis.visibleAxis = 1
valueAxis.visibleGrid = 0
valueAxis.visibleLabels = 1
valueAxis.visibleTicks = 1
valueAxis.zrangePref = 0
width = 180
x = 20
y = 10
```

## HorizontalLineChart3D(HorizontalLineChart)

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**categoryAxis** Handle of the category axis.

**categoryNames** List of category names.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** ? - Likely to disappear.

**height** Height of the chart.

**inFill** Whether infilling should be done.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**theta\_x** dx/dz

**theta\_y** dy/dz

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

**zDepth** depth of an individual series

**zSpace** z gap around series

### Example

```
def demo(self):
    """Shows basic use of a line chart."""
    drawing = Drawing(200, 100)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (14, 10, 21, 28, 38, 46, 25, 5)
    ]

    lc = HorizontalLineChart()
    lc.x = 20
```

```
lc.y = 10
lc.height = 85
lc.width = 170
lc.data = data
lc.lines.symbol = makeMarker('Circle')

drawing.add(lc)

return drawing
```

### *Properties of Example Widget*

```
background = None
categoryAxis.categoryNames = None
categoryAxis.gridEnd = 0
categoryAxis.gridStart = 0
categoryAxis.gridStrokeColor = Color(0,0,0)
categoryAxis.gridStrokeDashArray = None
categoryAxis.gridStrokeWidth = 0.25
categoryAxis.joinAxis = None
categoryAxis.joinAxisMode = None
categoryAxis.joinAxisPos = None
categoryAxis.labelAxisMode = 'axis'
categoryAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0131E878>
categoryAxis.reverseDirection = 0
categoryAxis.strokeColor = Color(0,0,0)
categoryAxis.strokeDashArray = None
categoryAxis.strokeWidth = 1
categoryAxis.style = 'parallel'
categoryAxis.tickDown = 5
categoryAxis.tickShift = 0
categoryAxis.tickUp = 0
categoryAxis.visible = 1
categoryAxis.visibleAxis = 1
categoryAxis.visibleGrid = 0
categoryAxis.visibleLabels = 1
categoryAxis.visibleTicks = 1
categoryNames = ('North', 'South', 'East', 'West')
data = [(100, 110, 120, 130), (70, 80, 80, 90)]
debug = 0
fillColor = None
groupSpacing = 1
height = 85
inFill = 0
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0131EAD0>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0131E990>
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
useAbsolute = 0
valueAxis.avoidBoundFrac = None
valueAxis.forceZero = 0
valueAxis.gridEnd = 0
valueAxis.gridStart = 0
valueAxis.gridStrokeColor = Color(0,0,0)
valueAxis.gridStrokeDashArray = None
valueAxis.gridStrokeWidth = 0.25
valueAxis.joinAxis = None
valueAxis.joinAxisMode = None
valueAxis.joinAxisPos = None
valueAxis.labelTextFormat = None
valueAxis.labelTextPostFormat = None
valueAxis.labelTextScale = None
valueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0131E940>
valueAxis.maximumTicks = 7
valueAxis.minimumTickSpacing = 10
valueAxis.rangeRound = 'none'
valueAxis.strokeColor = Color(0,0,0)
valueAxis.strokeDashArray = None
valueAxis.strokeWidth = 1
valueAxis.style = 'normal'
valueAxis.tickLeft = 5
```

```
valueAxis.tickRight = 0
valueAxis.valueMax = None
valueAxis.valueMin = None
valueAxis.valueStep = None
valueAxis.visible = 1
valueAxis.visibleAxis = 1
valueAxis.visibleGrid = 0
valueAxis.visibleLabels = 1
valueAxis.visibleTicks = 1
valueAxis.zrangePref = 0
width = 180
x = 20
y = 10
```

## LineChart (AbstractLineChart)

### Public Attributes

**background** Handle to background object.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### Example

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

### Properties of Example Widget

```
background = None
debug = 0
fillColor = None
height = 85
strokeColor = None
strokeWidth = 1
width = 180
x = 20
y = 10
```

## SampleHorizontalLineChart(HorizontalLineChart)

Sample class overwriting one method to draw additional horizontal lines.

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**categoryAxis** Handle of the category axis.

**categoryNames** List of category names.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**groupSpacing** ? - Likely to disappear.

**height** Height of the chart.

**inFill** Whether infilling should be done.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**useAbsolute** Flag to use absolute spacing values.

**valueAxis** Handle of the value axis.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### Example

```
def demo(self):
    """Shows basic use of a line chart."""

    drawing = Drawing(200, 100)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (14, 10, 21, 28, 38, 46, 25, 5)
    ]

    lc = SampleHorizontalLineChart()

    lc.x = 20
    lc.y = 10
    lc.height = 85
    lc.width = 170
    lc.data = data
```

```
lc.strokeColor = colors.white
lc.fillColor = colors.HexColor(0xCCCCCC)

drawing.add(lc)

return drawing
```

### *Properties of Example Widget*

```
background = None
categoryAxis.categoryNames = None
categoryAxis.gridEnd = 0
categoryAxis.gridStart = 0
categoryAxis.gridStrokeColor = Color(0,0,0)
categoryAxis.gridStrokeDashArray = None
categoryAxis.gridStrokeWidth = 0.25
categoryAxis.joinAxis = None
categoryAxis.joinAxisMode = None
categoryAxis.joinAxisPos = None
categoryAxis.labelAxisMode = 'axis'
categoryAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01328D50>
categoryAxis.reverseDirection = 0
categoryAxis.strokeColor = Color(0,0,0)
categoryAxis.strokeDashArray = None
categoryAxis.strokeWidth = 1
categoryAxis.style = 'parallel'
categoryAxis.tickDown = 5
categoryAxis.tickShift = 0
categoryAxis.tickUp = 0
categoryAxis.visible = 1
categoryAxis.visibleAxis = 1
categoryAxis.visibleGrid = 0
categoryAxis.visibleLabels = 1
categoryAxis.visibleTicks = 1
categoryNames = ('North', 'South', 'East', 'West')
data = [(100, 110, 120, 130), (70, 80, 80, 90)]
debug = 0
fillColor = None
groupSpacing = 1
height = 85
inFill = 0
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01328FA8>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01328E68>
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
useAbsolute = 0
valueAxis.avoidBoundFrac = None
valueAxis.forceZero = 0
valueAxis.gridEnd = 0
valueAxis.gridStart = 0
valueAxis.gridStrokeColor = Color(0,0,0)
valueAxis.gridStrokeDashArray = None
valueAxis.gridStrokeWidth = 0.25
valueAxis.joinAxis = None
valueAxis.joinAxisMode = None
valueAxis.joinAxisPos = None
valueAxis.labelTextFormat = None
valueAxis.labelTextPostFormat = None
valueAxis.labelTextScale = None
valueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01328E18>
valueAxis.maximumTicks = 7
valueAxis.minimumTickSpacing = 10
valueAxis.rangeRound = 'none'
valueAxis.strokeColor = Color(0,0,0)
valueAxis.strokeDashArray = None
valueAxis.strokeWidth = 1
valueAxis.style = 'normal'
valueAxis.tickLeft = 5
valueAxis.tickRight = 0
valueAxis.valueMax = None
valueAxis.valueMin = None
```



```
valueAxis.valueStep = None
valueAxis.visible = 1
valueAxis.visibleAxis = 1
valueAxis.visibleGrid = 0
valueAxis.visibleLabels = 1
valueAxis.visibleTicks = 1
valueAxis.zrangePref = 0
width = 180
x = 20
y = 10
```

## VerticalLineChart (LineChart)

### Public Attributes

**background** Handle to background object.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### Example

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

### Properties of Example Widget

```
background = None
debug = 0
fillColor = None
height = 85
strokeColor = None
strokeWidth = 1
width = 180
x = 20
y = 10
```

## Functions

**sample1( ... )**

### Example

```
def sample1():
    drawing = Drawing(400, 200)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (5, 20, 46, 38, 23, 21, 6, 14)
    ]

    lc = HorizontalLineChart()

    lc.x = 50
    lc.y = 50
    lc.height = 125
    lc.width = 300
    lc.data = data
    lc.joinedLines = 1
    lc.lines.symbol = makeMarker('FilledDiamond')
    lc.lineLabelFormat = '%2.0f'

    catNames = string.split('Jan Feb Mar Apr May Jun Jul Aug', ' ')
    lc.categoryAxis.categoryNames = catNames
    lc.categoryAxis.labels.boxAnchor = 'n'

    lc.valueAxis.valueMin = 0
    lc.valueAxis.valueMax = 60
    lc.valueAxis.valueStep = 15

    drawing.add(lc)

    return drawing
```



**sample1a( ... )***Example*

```
def sample1a():
    drawing = Drawing(400, 200)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (5, 20, 46, 38, 23, 21, 6, 14)
    ]

    lc = SampleHorizontalLineChart()


    lc.x = 50
    lc.y = 50
    lc.height = 125
    lc.width = 300
    lc.data = data
    lc.joinedLines = 1
    lc.strokeColor = colors.white
    lc.fillColor = colors.HexColor(0xCCCCCC)
    lc.lines.symbol = makeMarker('FilledDiamond')
    lc.lineLabelFormat = '%2.0f'

    catNames = string.split('Jan Feb Mar Apr May Jun Jul Aug', ' ')
    lc.categoryAxis.categoryNames = catNames
    lc.categoryAxis.labels.boxAnchor = 'n'

    lc.valueAxis.valueMin = 0
    lc.valueAxis.valueMax = 60
    lc.valueAxis.valueStep = 15

    drawing.add(lc)

    return drawing
```



**sample2( ... )***Example*

```
def sample2():
    drawing = Drawing(400, 200)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (5, 20, 46, 38, 23, 21, 6, 14)
    ]

    lc = HorizontalLineChart()


    lc.x = 50
    lc.y = 50
    lc.height = 125
    lc.width = 300
    lc.data = data
    lc.joinedLines = 1
    lc.lines.symbol = makeMarker('Smiley')
    lc.lineLabelFormat = '%2.0f'
    lc.strokeColor = colors.black
    lc.fillColor = colors.lightblue

    catNames = string.split('Jan Feb Mar Apr May Jun Jul Aug', ' ')
    lc.categoryAxis.categoryNames = catNames
    lc.categoryAxis.labels.boxAnchor = 'n'

    lc.valueAxis.valueMin = 0
    lc.valueAxis.valueMax = 60
    lc.valueAxis.valueStep = 15

    drawing.add(lc)

    return drawing
```



**sample3( ... )***Example*

```
def sample3():
    drawing = Drawing(400, 200)

    data = [
        (13, 5, 20, 22, 37, 45, 19, 4),
        (5, 20, 46, 38, 23, 21, 6, 14)
    ]

    lc = HorizontalLineChart()

    lc.x = 50
    lc.y = 50
    lc.height = 125
    lc.width = 300
    lc.data = data
    lc.joinedLines = 1
    lc.lineLabelFormat = '%2.0f'
    lc.strokeColor = colors.black


    lc.lines[0].symbol = makeMarker('Smiley')
    lc.lines[1].symbol = NoEntry
    lc.lines[0].strokeWidth = 2
    lc.lines[1].strokeWidth = 4

    catNames = string.split('Jan Feb Mar Apr May Jun Jul Aug', ' ')
    lc.categoryAxis.categoryNames = catNames
    lc.categoryAxis.labels.boxAnchor = 'n'

    lc.valueAxis.valueMin = 0
    lc.valueAxis.valueMax = 60
    lc.valueAxis.valueStep = 15

    drawing.add(lc)

    return drawing
```



## lineplots

This module defines a very preliminary Line Plot example.

### Classes

#### AreaLinePlot(LinePlot)

we're given data in the form [(X1,Y11,..Y1M)....(Xn,Yn1,...YnM)]

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**data** Data to be plotted, list of (lists of) x/y tuples.

**debug** Used only for debugging.

**fillColor** Color used for background interior of plot area.

**height** Height of the chart.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**strokeColor** Color used for background border of plot area.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**xValueAxis** Handle of the x axis.

**y** Y position of the lower-left corner of the chart.

**yValueAxis** Handle of the y axis.

#### Example

```
def demo(self):
    """Shows basic use of a line chart."""

    drawing = Drawing(400, 200)

    data = [
        ((1,1), (2,2), (2.5,1), (3,3), (4,5)),
        ((1,2), (2,3), (2.5,2), (3.5,5), (4,6))
    ]

    lp = LinePlot()

    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
```

```
lp.data = data
lp.joinedLines = 1
lp.lineLabelFormat = '%2.0f'
lp.strokeColor = colors.black

lp.lines[0].strokeColor = colors.red
lp.lines[0].symbol = makeMarker('FilledCircle')
lp.lines[1].strokeColor = colors.blue
lp.lines[1].symbol = makeMarker('FilledDiamond')

lp.xValueAxis.valueMin = 0
lp.xValueAxis.valueMax = 5
lp.xValueAxis.valueStep = 1

lp.yValueAxis.valueMin = 0
lp.yValueAxis.valueMax = 7
lp.yValueAxis.valueStep = 1

drawing.add(lp)

return drawing
```

### *Properties of Example Widget*

```
background = None
data = [(1, 20, 100, 30), (2, 11, 50, 15), (3, 15, 70, 40)]
debug = 0
fillColor = None
height = 85
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B37B0>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B3698>
reversePlotOrder = 1
strokeColor = None
strokeWidth = 1
width = 180
x = 20
xValueAxis.avoidBoundFrac = None
xValueAxis.forceZero = 0
xValueAxis.gridEnd = 0
xValueAxis.gridStart = 0
xValueAxis.gridStrokeColor = Color(0,0,0)
xValueAxis.gridStrokeDashArray = None
xValueAxis.gridStrokeWidth = 0.25
xValueAxis.joinAxis = None
xValueAxis.joinAxisMode = None
xValueAxis.joinAxisPos = None
xValueAxis.labelTextFormat = None
xValueAxis.labelTextPostFormat = None
xValueAxis.labelTextScale = None
xValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B35A8>
xValueAxis.maximumTicks = 7
xValueAxis.minimumTickSpacing = 10
xValueAxis.rangeRound = 'none'
xValueAxis.strokeColor = Color(0,0,0)
xValueAxis.strokeDashArray = None
xValueAxis.strokeWidth = 1
xValueAxis.style = 'normal'
xValueAxis.tickDown = 5
xValueAxis.tickUp = 0
xValueAxis.valueMax = None
xValueAxis.valueMin = None
xValueAxis.valueStep = None
xValueAxis.visible = 1
xValueAxis.visibleAxis = 1
xValueAxis.visibleGrid = 0
xValueAxis.visibleLabels = 1
xValueAxis.visibleTicks = 1
xValueAxis.zrangePref = 0
y = 10
yValueAxis.avoidBoundFrac = None
yValueAxis.forceZero = 0
yValueAxis.gridEnd = 0
```



```
yValueAxis.gridStart = 0
yValueAxis.gridStrokeColor = Color(0,0,0)
yValueAxis.gridStrokeDashArray = None
yValueAxis.gridStrokeWidth = 0.25
yValueAxis.joinAxis = None
yValueAxis.joinAxisMode = None
yValueAxis.joinAxisPos = None
yValueAxis.labelTextFormat = None
yValueAxis.labelTextPostFormat = None
yValueAxis.labelTextScale = None
yValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B3648>
yValueAxis.maximumTicks = 7
yValueAxis.minimumTickSpacing = 10
yValueAxis.rangeRound = 'none'
yValueAxis.strokeColor = Color(0,0,0)
yValueAxis.strokeDashArray = None
yValueAxis.strokeWidth = 1
yValueAxis.style = 'normal'
yValueAxis.tickLeft = 5
yValueAxis.tickRight = 0
yValueAxis.valueMax = None
yValueAxis.valueMin = None
yValueAxis.valueStep = None
yValueAxis.visible = 1
yValueAxis.visibleAxis = 1
yValueAxis.visibleGrid = 0
yValueAxis.visibleLabels = 1
yValueAxis.visibleTicks = 1
yValueAxis.zrangePref = 0
```

## GridLinePlot(LinePlot)

A customized version of LinePlot.

It uses NormalDateXValueAxis() and AdjYValueAxis() for the X and Y axes.

The chart has a default grid background with thin horizontal lines aligned with the tickmarks (and labels). You can change the background to be any Grid or ShadedRect, or scale the whole chart.

If you do provide a background, you can specify the colours of the stripes with 'background.stripeColors'.

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Background for chart area (now Grid or ShadedRect).

**data** Data to be plotted, list of (lists of) x/y tuples.

**debug** Used only for debugging.

**fillColor** Color used for background interior of plot area.

**height** Height of the chart.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**scaleFactor** Scalefactor to apply to whole drawing.

**strokeColor** Color used for background border of plot area.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**xValueAxis** Handle of the x axis.

**y** Y position of the lower-left corner of the chart.

**yValueAxis** Handle of the y axis.

### Example

```
def demo(self,drawing=None):
    from reportlab.lib import colors
    if not drawing:
        drawing = Drawing(400, 200)
    lp = AdjLinePlot()
    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = _monthlyIndexData
    lp.joinedLines = 1
    lp.strokeColor = colors.black
    c0 = colors.PCMYKColor(100,65,0,30, spotName='PANTONE 288 CV', density=100)
    lp.lines[0].strokeColor = c0
    lp.lines[0].strokeWidth = 2
```

```
lp.lines[0].strokeDashArray = None
c1 = colors.PCMYKColor(0,79,91,0, spotName='PANTONE Wm Red CV', density=100)
lp.lines[1].strokeColor = c1
lp.lines[1].strokeWidth = 1
lp.lines[1].strokeDashArray = [3,1]
lp.xValueAxis.labels.fontSize = 10
lp.xValueAxis.labels.textAnchor = 'start'
lp.xValueAxis.labels.boxAnchor = 'w'
lp.xValueAxis.labels.angle = -45
lp.xValueAxis.labels.dx = 0
lp.xValueAxis.labels.dy = -8
lp.xValueAxis.xLabelFormat = '{mm}/{yy}'
lp.yValueAxis.labelTextFormat = '%5d%% '
lp.yValueAxis.tickLeft = 5
lp.yValueAxis.labels.fontSize = 10
lp.background = Grid()
lp.background.stripeColors = [colors.pink, colors.lightblue]
lp.background.orientation = 'vertical'
drawing.add(lp, 'plot')
return drawing
```

### *Properties of Example Widget*

```
background.delta = 20
background.delta0 = 0
background.deltaSteps = []
background.fillColor = Color(1,1,1)
background.height = 100
background.orientation = 'horizontal'
background.stripeColors = [Color(1,0,0), Color(0,.501961,0), Color(0,0,1)]
background.strokeColor = Color(0,0,0)
background.strokeWidth = 0.5
background.useLines = 1
background.useRects = 0
background.width = 100
background.x = 0
background.y = 0
data = [(19971202, 100.0),
        (19971231, 100.1704367),
        (19980131, 101.5639577),
        (19980228, 102.1879927),
        (19980331, 101.6337257),
        (19980430, 102.76404460000001),
        (19980531, 102.9198038),
        (19980630, 103.25938789999999),
        (19980731, 103.2516421),
        (19980831, 105.4744329),
        (19980930, 109.3242705),
        (19981031, 111.98592910000001),
        (19981130, 110.9184642),
        (19981231, 110.9184642),
        (19990131, 111.9882532),
        (19990228, 109.7912614),
        (19990331, 110.24189629999999),
        (19990430, 110.42793210000001),
        (19990531, 109.33955469999999),
        (19990630, 108.23417480000001),
        (19990731, 110.21294469999999),
        (19990831, 110.9683062),
        (19990930, 112.4425371),
        (19991031, 112.7314032),
        (19991130, 112.3509645),
        (19991231, 112.3660659),
        (20000131, 110.92552480000001),
        (20000229, 110.5266306),
        (20000331, 113.3116101),
        (20000430, 111.0449133),
        (20000531, 111.70271700000001),
        (20000630, 113.5832178)],
        [(19971202, 100.0),
        (19971231, 100.0),
        (19980131, 100.8),
        (19980228, 102.0),
        (19980331, 101.90000000000001),
        (19980430, 103.0),
        (19980531, 103.0),
```

```
(19980630, 103.09999999999999),
(19980731, 103.09999999999999),
(19980831, 102.8),
(19980930, 105.59999999999999),
(19981031, 108.3),
(19981130, 108.09999999999999),
(19981231, 111.90000000000001),
(19990131, 113.09999999999999),
(19990228, 110.2),
(19990331, 111.8),
(19990430, 112.3),
(19990531, 110.09999999999999),
(19990630, 109.3),
(19990731, 111.2),
(19990831, 111.7),
(19990930, 112.59999999999999),
(19991031, 113.2),
(19991130, 113.90000000000001),
(19991231, 115.40000000000001),
(20000131, 112.7),
(20000229, 113.90000000000001),
(20000331, 115.8),
(20000430, 112.2),
(20000531, 112.59999999999999),
(20000630, 114.59999999999999)]
debug = 0
fillColor = None
height = 85
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B7940>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B7828>
reversePlotOrder = 0
scaleFactor = None
strokeColor = None
strokeWidth = 1
width = 180
x = 20
xValueAxis.avoidBoundFrac = None
xValueAxis.bottomAxisLabelSlack = 0.10000000000000001
xValueAxis.dailyFreq = 0
xValueAxis.dayOfWeekName = ['Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday', 'Saturday', 'Sunday']
xValueAxis.forceEndDate = 0
xValueAxis.forceFirstDate = 0
xValueAxis.forceZero = 0
xValueAxis.gridEnd = 0
xValueAxis.gridStart = 0
xValueAxis.gridStrokeColor = Color(0,0,0)
xValueAxis.gridStrokeDashArray = None
xValueAxis.gridStrokeWidth = 0.25
xValueAxis.joinAxis = None
xValueAxis.joinAxisMode = None
xValueAxis.joinAxisPos = None
xValueAxis.labelTextFormat = None
xValueAxis.labelTextPostFormat = None
xValueAxis.labelTextScale = None
xValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B78C8>
xValueAxis.maximumTicks = 7
xValueAxis.minimumTickSpacing = 10
xValueAxis.monthName = ['January',
                        'February',
                        'March',
                        'April',
                        'May',
                        'June',
                        'July',
                        'August',
                        'September',
                        'October',
                        'November',
                        'December']
xValueAxis.niceMonth = 1
xValueAxis.rangeRound = 'none'
xValueAxis.strokeColor = Color(0,0,0)
xValueAxis.strokeDashArray = None
xValueAxis.strokeWidth = 1
xValueAxis.style = 'normal'
```

```
xValueAxis.tickDown = 5
xValueAxis.tickUp = 0
xValueAxis.valueMax = None
xValueAxis.valueMin = None
xValueAxis.valueStep = None
xValueAxis.valueSteps = None
xValueAxis.visible = 1
xValueAxis.visibleAxis = 1
xValueAxis.visibleGrid = 0
xValueAxis.visibleLabels = 1
xValueAxis.visibleTicks = 1
xValueAxis.xLabelFormat = '{mm}/{yy}'
xValueAxis.zrangePref = 0
y = 10
yValueAxis.avoidBoundFrac = None
yValueAxis.forceZero = 0
yValueAxis.gridEnd = 0
yValueAxis.gridStart = 0
yValueAxis.gridStrokeColor = Color(0,0,0)
yValueAxis.gridStrokeDashArray = None
yValueAxis.gridStrokeWidth = 0.25
yValueAxis.joinAxis = None
yValueAxis.joinAxisMode = None
yValueAxis.joinAxisPos = None
yValueAxis.labelTextFormat = None
yValueAxis.labelTextPostFormat = None
yValueAxis.labelTextScale = None
yValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013B7738>
yValueAxis.leftAxisOrigShiftIPC = 0.14999999999999999
yValueAxis.leftAxisOrigShiftMin = 12
yValueAxis.leftAxisPercent = 1
yValueAxis.leftAxisSkipLL0 = 0
yValueAxis.maximumTicks = 7
yValueAxis.minimumTickSpacing = 10
yValueAxis.rangeRound = 'none'
yValueAxis.requiredRange = 30
yValueAxis.strokeColor = Color(0,0,0)
yValueAxis.strokeDashArray = None
yValueAxis.strokeWidth = 1
yValueAxis.style = 'normal'
yValueAxis.tickLeft = 5
yValueAxis.tickRight = 0
yValueAxis.valueMax = None
yValueAxis.valueMin = None
yValueAxis.valueStep = None
yValueAxis.valueSteps = None
yValueAxis.visible = 1
yValueAxis.visibleAxis = 1
yValueAxis.visibleGrid = 0
yValueAxis.visibleLabels = 1
yValueAxis.visibleTicks = 1
yValueAxis.zrangePref = 0
```

## LinePlot(AbstractLineChart)

Line plot with multiple lines.

Both x- and y-axis are value axis (so there are no separate X and Y versions of this class).

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**data** Data to be plotted, list of (lists of) x/y tuples.

**debug** Used only for debugging.

**fillColor** Color used for background interior of plot area.

**height** Height of the chart.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**strokeColor** Color used for background border of plot area.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**xValueAxis** Handle of the x axis.

**y** Y position of the lower-left corner of the chart.

**yValueAxis** Handle of the y axis.

### Example

```
def demo(self):
    """Shows basic use of a line chart."""

    drawing = Drawing(400, 200)

    data = [
        ((1,1), (2,2), (2.5,1), (3,3), (4,5)),
        ((1,2), (2,3), (2.5,2), (3.5,5), (4,6))
    ]

    lp = LinePlot()

    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = data
    lp.joinedLines = 1
    lp.lineLabelFormat = '%2.0f'
    lp.strokeColor = colors.black
    lp.lines[0].strokeColor = colors.red
```

```
lp.lines[0].symbol = makeMarker('FilledCircle')
lp.lines[1].strokeColor = colors.blue
lp.lines[1].symbol = makeMarker('FilledDiamond')

lp.xValueAxis.valueMin = 0
lp.xValueAxis.valueMax = 5
lp.xValueAxis.valueStep = 1

lp.yValueAxis.valueMin = 0
lp.yValueAxis.valueMax = 7
lp.yValueAxis.valueStep = 1

drawing.add(lp)

return drawing
```

### *Properties of Example Widget*

```
background = None
data = [(1, 1), (2, 2), (2.5, 1), (3, 3), (4, 5)),
        ((1, 2), (2, 3), (2.5, 2), (3, 4), (4, 6))]
debug = 0
fillColor = None
height = 85
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013D8B70>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013D8A58>
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
width = 180
x = 20
xValueAxis.avoidBoundFrac = None
xValueAxis.forceZero = 0
xValueAxis.gridEnd = 0
xValueAxis.gridStart = 0
xValueAxis.gridStrokeColor = Color(0,0,0)
xValueAxis.gridStrokeDashArray = None
xValueAxis.gridStrokeWidth = 0.25
xValueAxis.joinAxis = None
xValueAxis.joinAxisMode = None
xValueAxis.joinAxisPos = None
xValueAxis.labelTextFormat = None
xValueAxis.labelTextPostFormat = None
xValueAxis.labelTextScale = None
xValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013D8940>
xValueAxis.maximumTicks = 7
xValueAxis.minimumTickSpacing = 10
xValueAxis.rangeRound = 'none'
xValueAxis.strokeColor = Color(0,0,0)
xValueAxis.strokeDashArray = None
xValueAxis.strokeWidth = 1
xValueAxis.style = 'normal'
xValueAxis.tickDown = 5
xValueAxis.tickUp = 0
xValueAxis.valueMax = None
xValueAxis.valueMin = None
xValueAxis.valueStep = None
xValueAxis.visible = 1
xValueAxis.visibleAxis = 1
xValueAxis.visibleGrid = 0
xValueAxis.visibleLabels = 1
xValueAxis.visibleTicks = 1
xValueAxis.zrangePref = 0
y = 10
yValueAxis.avoidBoundFrac = None
yValueAxis.forceZero = 0
yValueAxis.gridEnd = 0
yValueAxis.gridStart = 0
yValueAxis.gridStrokeColor = Color(0,0,0)
yValueAxis.gridStrokeDashArray = None
yValueAxis.gridStrokeWidth = 0.25
yValueAxis.joinAxis = None
```

```
yValueAxis.joinAxisMode = None
yValueAxis.joinAxisPos = None
yValueAxis.labelTextFormat = None
yValueAxis.labelTextPostFormat = None
yValueAxis.labelTextScale = None
yValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013D8A08>
yValueAxis.maximumTicks = 7
yValueAxis.minimumTickSpacing = 10
yValueAxis.rangeRound = 'none'
yValueAxis.strokeColor = Color(0,0,0)
yValueAxis.strokeDashArray = None
yValueAxis.strokeWidth = 1
yValueAxis.style = 'normal'
yValueAxis.tickLeft = 5
yValueAxis.tickRight = 0
yValueAxis.valueMax = None
yValueAxis.valueMin = None
yValueAxis.valueStep = None
yValueAxis.visible = 1
yValueAxis.visibleAxis = 1
yValueAxis.visibleGrid = 0
yValueAxis.visibleLabels = 1
yValueAxis.visibleTicks = 1
yValueAxis.zrangePref = 0
```



## LinePlot3D(LinePlot)

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**data** Data to be plotted, list of (lists of) x/y tuples.

**debug** Used only for debugging.

**fillColor** Color used for background interior of plot area.

**height** Height of the chart.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**strokeColor** Color used for background border of plot area.

**strokeWidth** Width plot area border.

**theta\_x** dx/dz

**theta\_y** dy/dz

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**xValueAxis** Handle of the x axis.

**y** Y position of the lower-left corner of the chart.

**yValueAxis** Handle of the y axis.

**zDepth** depth of an individual series

**zSpace** z gap around series

### Example

```
def demo(self):
    """Shows basic use of a line chart."""

    drawing = Drawing(400, 200)

    data = [
        ((1,1), (2,2), (2.5,1), (3,3), (4,5)),
        ((1,2), (2,3), (2.5,2), (3.5,5), (4,6))
    ]

    lp = LinePlot()

    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = data
    lp.joinedLines = 1
    lp.lineLabelFormat = '%2.0f'
    lp.strokeColor = colors.black
```

```
lp.lines[0].strokeColor = colors.red
lp.lines[0].symbol = makeMarker('FilledCircle')
lp.lines[1].strokeColor = colors.blue
lp.lines[1].symbol = makeMarker('FilledDiamond')

lp.xValueAxis.valueMin = 0
lp.xValueAxis.valueMax = 5
lp.xValueAxis.valueStep = 1

lp.yValueAxis.valueMin = 0
lp.yValueAxis.valueMax = 7
lp.yValueAxis.valueStep = 1

drawing.add(lp)

return drawing
```

### *Properties of Example Widget*

```
background = None
data = [(1, 1), (2, 2), (2.5, 1), (3, 3), (4, 5)),
        ((1, 2), (2, 3), (2.5, 2), (3, 4), (4, 6))]
debug = 0
fillColor = None
height = 85
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013DF300>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013DF1E8>
reversePlotOrder = 0
strokeColor = None
strokeWidth = 1
width = 180
x = 20
xValueAxis.avoidBoundFrac = None
xValueAxis.forceZero = 0
xValueAxis.gridEnd = 0
xValueAxis.gridStart = 0
xValueAxis.gridStrokeColor = Color(0,0,0)
xValueAxis.gridStrokeDashArray = None
xValueAxis.gridStrokeWidth = 0.25
xValueAxis.joinAxis = None
xValueAxis.joinAxisMode = None
xValueAxis.joinAxisPos = None
xValueAxis.labelTextFormat = None
xValueAxis.labelTextPostFormat = None
xValueAxis.labelTextScale = None
xValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013DF0D0>
xValueAxis.maximumTicks = 7
xValueAxis.minimumTickSpacing = 10
xValueAxis.rangeRound = 'none'
xValueAxis.strokeColor = Color(0,0,0)
xValueAxis.strokeDashArray = None
xValueAxis.strokeWidth = 1
xValueAxis.style = 'normal'
xValueAxis.tickDown = 5
xValueAxis.tickUp = 0
xValueAxis.valueMax = None
xValueAxis.valueMin = None
xValueAxis.valueStep = None
xValueAxis.visible = 1
xValueAxis.visibleAxis = 1
xValueAxis.visibleGrid = 0
xValueAxis.visibleLabels = 1
xValueAxis.visibleTicks = 1
xValueAxis.zrangePref = 0
y = 10
yValueAxis.avoidBoundFrac = None
yValueAxis.forceZero = 0
yValueAxis.gridEnd = 0
yValueAxis.gridStart = 0
yValueAxis.gridStrokeColor = Color(0,0,0)
yValueAxis.gridStrokeDashArray = None
yValueAxis.gridStrokeWidth = 0.25
```

```
yValueAxis.joinAxis = None
yValueAxis.joinAxisMode = None
yValueAxis.joinAxisPos = None
yValueAxis.labelTextFormat = None
yValueAxis.labelTextPostFormat = None
yValueAxis.labelTextScale = None
yValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013DF198>
yValueAxis.maximumTicks = 7
yValueAxis.minimumTickSpacing = 10
yValueAxis.rangeRound = 'none'
yValueAxis.strokeColor = Color(0,0,0)
yValueAxis.strokeDashArray = None
yValueAxis.strokeWidth = 1
yValueAxis.style = 'normal'
yValueAxis.tickLeft = 5
yValueAxis.tickRight = 0
yValueAxis.valueMax = None
yValueAxis.valueMin = None
yValueAxis.valueStep = None
yValueAxis.visible = 1
yValueAxis.visibleAxis = 1
yValueAxis.visibleGrid = 0
yValueAxis.visibleLabels = 1
yValueAxis.visibleTicks = 1
yValueAxis.zrangePref = 0
```

## ScatterPlot(LinePlot)

A scatter plot widget

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**axisStrokeWidth** Stroke width for both axes

**axisTickLengths** Lenth of the ticks on both axes

**background** Background color (if any)

**bottomPadding** Padding at bottom of drawing

**data** Data points - a list of x/y tuples.

**debug** Used only for debugging.

**fillColor** Color used for background interior of plot area.

**height** Height of the area inside the axes

**joinedLines** Display data points joined with lines if true.

**labelOffset** Space between label and Axis (or other labels)

**leftPadding** Padding on left of drawing

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**outerBorderColor** Color of outer border (if any)

**outerBorderOn** Is there an outer border (continuation of axes)

**reversePlotOrder** If true reverse plot order.

**rightPadding** Padding on right of drawing

**strokeColor** Color used for border of plot area.

**strokeWidth** Width plot area border.

**topPadding** Padding at top of drawing

**width** Width of the area inside the axes

**x** X position of the lower-left corner of the chart.

**xLabel** Label for the whole X-Axis

**xValueAxis** Handle of the x axis.

**y** Y position of the lower-left corner of the chart.

**yLabel** Label for the whole Y-Axis

**yValueAxis** Handle of the y axis.

### Example

```
def demo(self, drawing=None):
    if not drawing:
        tx, ty = self._getDrawingDimensions()
```

```
        drawing = Drawing(tx,ty)
        drawing.add(self.draw())
        return drawing
```

### *Properties of Example Widget*

```
background = None
bottomPadding = 5
data = [(0.029999999999999999, 62.729999999999997),
        (0.073999999999999996, 54.363),
        (1.216, 17.963999999999999),
        ((1.3600000000000001, 11.621),
         (1.387, 50.011000000000003),
         (1.4279999999999999, 68.953000000000003)),
        ((1.444, 86.888000000000005),
         (1.754, 35.579999999999998),
         (1.766, 36.049999999999997))]
debug = 0
fillColor = None
height = 77
joinedLines = 0
leftPadding = 5
lineLabelArray = None
lineLabelFormat = '%.2f'
lineLabelNudge = 0
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013EA120>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013E6FD0>
outerBorderColor = Color(0,0,0)
outerBorderOn = 1
reversePlotOrder = 0
rightPadding = 10
strokeColor = None
strokeWidth = 1
topPadding = 5
width = 142
x = 25.996000000000002
xLabel = 'X Lable'
xValueAxis.avoidBoundFrac = None
xValueAxis.forceZero = 0
xValueAxis.gridEnd = 0
xValueAxis.gridStart = 0
xValueAxis.gridStrokeColor = Color(0,0,0)
xValueAxis.gridStrokeDashArray = None
xValueAxis.gridStrokeWidth = 0.25
xValueAxis.joinAxis = None
xValueAxis.joinAxisMode = None
xValueAxis.joinAxisPos = None
xValueAxis.labelTextFormat = None
xValueAxis.labelTextPostFormat = None
xValueAxis.labelTextScale = None
xValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013E6EB8>
xValueAxis.maximumTicks = 7
xValueAxis.minimumTickSpacing = 10
xValueAxis.rangeRound = 'both'
xValueAxis.strokeColor = Color(0,0,0)
xValueAxis.strokeDashArray = None
xValueAxis.strokeWidth = 0.5
xValueAxis.style = 'normal'
xValueAxis.tickDown = 2
xValueAxis.tickUp = 0
xValueAxis.valueMax = None
xValueAxis.valueMin = None
xValueAxis.valueStep = None
xValueAxis.visible = 1
xValueAxis.visibleAxis = 1
xValueAxis.visibleGrid = 0
xValueAxis.visibleLabels = 1
xValueAxis.visibleTicks = 1
xValueAxis.zrangePref = 0
y = 16
yLabel = 'Y Lable'
yValueAxis.avoidBoundFrac = None
yValueAxis.forceZero = 0
yValueAxis.gridEnd = 0
yValueAxis.gridStart = 0
yValueAxis.gridStrokeColor = Color(0,0,0)
```

```
yValueAxis.gridStrokeDashArray = None
yValueAxis.gridStrokeWidth = 0.25
yValueAxis.joinAxis = None
yValueAxis.joinAxisMode = None
yValueAxis.joinAxisPos = None
yValueAxis.labelTextFormat = '%s'
yValueAxis.labelTextPostFormat = None
yValueAxis.labelTextScale = None
yValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013E6F80>
yValueAxis.maximumTicks = 7
yValueAxis.minimumTickSpacing = 10
yValueAxis.rangeRound = 'both'
yValueAxis.strokeColor = Color(0,0,0)
yValueAxis.strokeDashArray = None
yValueAxis.strokeWidth = 0.5
yValueAxis.style = 'normal'
yValueAxis.tickLeft = 2
yValueAxis.tickRight = 0
yValueAxis.valueMax = None
yValueAxis.valueMin = None
yValueAxis.valueStep = None
yValueAxis.visible = 1
yValueAxis.visibleAxis = 1
yValueAxis.visibleGrid = 0
yValueAxis.visibleLabels = 1
yValueAxis.visibleTicks = 1
yValueAxis.zrangePref = 0
```

## **ShadedPolyFiller(Filler, ShadedPolygon)**

### **Public Attributes**

**fillColor** filler interior color

**strokeColor** filler edge color

**strokeWidth** filler edge width

### *Example*

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

### *Properties of Example Widget*

## SplitLinePlot (AreaLinePlot)

### Public Attributes

**annotations** list of callables, will be called with self, xscale, yscale.

**background** Handle to background object.

**data** Data to be plotted, list of (lists of) x/y tuples.

**debug** Used only for debugging.

**fillColor** Color used for background interior of plot area.

**height** Height of the chart.

**joinedLines** Display data points joined with lines if true.

**lineLabelArray** explicit array of line label values, must match size of data if present.

**lineLabelFormat** Formatting string or function used for data point labels.

**lineLabelNudge** Distance between a data point and its label.

**lineLabels** Handle to the list of data point labels.

**lines** Handle of the lines.

**reversePlotOrder** If true reverse plot order.

**strokeColor** Color used for background border of plot area.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**xValueAxis** Handle of the x axis.

**y** Y position of the lower-left corner of the chart.

**yValueAxis** Handle of the y axis.

### Example

```
def demo(self):
    """Shows basic use of a line chart."""

    drawing = Drawing(400, 200)

    data = [
        ((1,1), (2,2), (2.5,1), (3,3), (4,5)),
        ((1,2), (2,3), (2.5,2), (3.5,5), (4,6))
    ]

    lp = LinePlot()

    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = data
    lp.joinedLines = 1
    lp.lineLabelFormat = '%2.0f'
    lp.strokeColor = colors.black

    lp.lines[0].strokeColor = colors.red
    lp.lines[0].symbol = makeMarker('FilledCircle')
    lp.lines[1].strokeColor = colors.blue
    lp.lines[1].symbol = makeMarker('FilledDiamond')

    lp.xValueAxis.valueMin = 0
    lp.xValueAxis.valueMax = 5
```



```
background = None
```

[illegible]

154

```
(20150401, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20150501, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20150601, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20150701, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20150801, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20150901, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20151001, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20151101, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20151201, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20160101, 0.29999999999999999, 0.40999999999999998, 0.28999999999999998),
(20160201, 0.26000000000000001, 0.35999999999999999, 0.38),
(20160301, 0.26000000000000001, 0.35999999999999999, 0.38),
(20160401, 0.26000000000000001, 0.35999999999999999, 0.38),
(20160501, 0.26000000000000001, 0.35999999999999999, 0.38),
(20160601, 0.26000000000000001, 0.35999999999999999, 0.38),
(20160701, 0.26000000000000001, 0.35999999999999999, 0.38),
(20160801, 0.26000000000000001, 0.35999999999999999, 0.38),
(20160901, 0.26000000000000001, 0.35999999999999999, 0.38),
(20161001, 0.26000000000000001, 0.35999999999999999, 0.38),
(20161101, 0.26000000000000001, 0.35999999999999999, 0.38),
(20161201, 0.26000000000000001, 0.35999999999999999, 0.38),
(20170101, 0.26000000000000001, 0.35999999999999999, 0.38),
(20170201, 0.20000000000000001, 0.29999999999999999, 0.5),
(20170301, 0.20000000000000001, 0.29999999999999999, 0.5),
(20170401, 0.20000000000000001, 0.29999999999999999, 0.5),
(20170501, 0.20000000000000001, 0.29999999999999999, 0.5),
(20170601, 0.20000000000000001, 0.29999999999999999, 0.5),
(20170701, 0.20000000000000001, 0.29999999999999999, 0.5),
(20170801, 0.20000000000000001, 0.29999999999999999, 0.5),
(20170901, 0.20000000000000001, 0.29999999999999999, 0.5),
(20171001, 0.20000000000000001, 0.29999999999999999, 0.5),
(20171101, 0.20000000000000001, 0.29999999999999999, 0.5),
(20171201, 0.20000000000000001, 0.29999999999999999, 0.5),
(20180101, 0.20000000000000001, 0.29999999999999999, 0.5),
(20180201, 0.13, 0.37, 0.5),
(20180301, 0.13, 0.37, 0.5),
(20180401, 0.13, 0.37, 0.5),
(20180501, 0.13, 0.37, 0.5),
(20180601, 0.13, 0.37, 0.5),
(20180701, 0.13, 0.37, 0.5),
(20180801, 0.13, 0.37, 0.5),
(20180901, 0.13, 0.37, 0.5),
(20181001, 0.13, 0.37, 0.5),
(20181101, 0.13, 0.37, 0.5),
(20181201, 0.13, 0.37, 0.5),
(20190101, 0.13, 0.37, 0.5),
(20190201, 0.10000000000000001, 0.40000000000000002, 0.5),
(20190301, 0.10000000000000001, 0.40000000000000002, 0.5),
(20190401, 0.10000000000000001, 0.40000000000000002, 0.5),
(20190501, 0.10000000000000001, 0.40000000000000002, 0.5),
(20190601, 0.10000000000000001, 0.40000000000000002, 0.5),
(20190701, 0.10000000000000001, 0.40000000000000002, 0.5),
(20190801, 0.10000000000000001, 0.40000000000000002, 0.5),
(20190901, 0.10000000000000001, 0.40000000000000002, 0.5),
(20191001, 0.10000000000000001, 0.40000000000000002, 0.5),
(20191101, 0.10000000000000001, 0.40000000000000002, 0.5),
(20191201, 0.10000000000000001, 0.40000000000000002, 0.5),
(20200101, 0.10000000000000001, 0.40000000000000002, 0.5)]
debug = 0
fillColor = None
height = 85
joinedLines = 1
lineLabelArray = None
lineLabelFormat = None
lineLabelNudge = 10
lineLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013ECBE8>
lines = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013ECAD0>
reversePlotOrder = 1
strokeColor = None
strokeWidth = 1
width = 180
x = 20
xValueAxis.avoidBoundFrac = None
xValueAxis.bottomAxisLabelSlack = 0.10000000000000001
xValueAxis.dailyFreq = 0
xValueAxis.dayOfWeekName = ['Monday', 'Tuesday', 'Wednesday', 'Thursday', 'Friday', 'Saturday', 'Sunday']
xValueAxis.forceEndDate = 0
xValueAxis.forceFirstDate = 0
xValueAxis.forceZero = 0
```

```
xValueAxis.gridEnd = 0
xValueAxis.gridStart = 0
xValueAxis.gridStrokeColor = Color(0,0,0)
xValueAxis.gridStrokeDashArray = None
xValueAxis.gridStrokeWidth = 0.25
xValueAxis.joinAxis = None
xValueAxis.joinAxisMode = None
xValueAxis.joinAxisPos = None
xValueAxis.labelTextFormat = None
xValueAxis.labelTextPostFormat = None
xValueAxis.labelTextScale = None
xValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013ECB70>
xValueAxis.maximumTicks = 7
xValueAxis.minimumTickSpacing = 10
xValueAxis.monthName = ['January',
                        'February',
                        'March',
                        'April',
                        'May',
                        'June',
                        'July',
                        'August',
                        'September',
                        'October',
                        'November',
                        'December']
xValueAxis.niceMonth = 1
xValueAxis.rangeRound = 'none'
xValueAxis.strokeColor = Color(0,0,0)
xValueAxis.strokeDashArray = None
xValueAxis.strokeWidth = 1
xValueAxis.style = 'normal'
xValueAxis.tickDown = 5
xValueAxis.tickUp = 0
xValueAxis.valueMax = None
xValueAxis.valueMin = None
xValueAxis.valueStep = None
xValueAxis.valueSteps = None
xValueAxis.visible = 1
xValueAxis.visibleAxis = 1
xValueAxis.visibleGrid = 0
xValueAxis.visibleLabels = 1
xValueAxis.visibleTicks = 1
xValueAxis.xLabelFormat = '{mm}/{yy}'
xValueAxis.zrangePref = 0
y = 10
yValueAxis.avoidBoundFrac = None
yValueAxis.forceZero = 0
yValueAxis.gridEnd = 0
yValueAxis.gridStart = 0
yValueAxis.gridStrokeColor = Color(0,0,0)
yValueAxis.gridStrokeDashArray = None
yValueAxis.gridStrokeWidth = 0.25
yValueAxis.joinAxis = None
yValueAxis.joinAxisMode = None
yValueAxis.joinAxisPos = None
yValueAxis.labelTextFormat = None
yValueAxis.labelTextPostFormat = None
yValueAxis.labelTextScale = None
yValueAxis.labels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x013EC9B8>
yValueAxis.leftAxisOrigShiftIPC = 0
yValueAxis.leftAxisOrigShiftMin = 0
yValueAxis.leftAxisPercent = 0
yValueAxis.leftAxisSkipLL0 = 0
yValueAxis.maximumTicks = 7
yValueAxis.minimumTickSpacing = 10
yValueAxis.rangeRound = 'none'
yValueAxis.requiredRange = None
yValueAxis.strokeColor = Color(0,0,0)
yValueAxis.strokeDashArray = None
yValueAxis.strokeWidth = 1
yValueAxis.style = 'normal'
yValueAxis.tickLeft = 5
yValueAxis.tickRight = 0
yValueAxis.valueMax = None
yValueAxis.valueMin = None
yValueAxis.valueStep = None
yValueAxis.valueSteps = None
yValueAxis.visible = 1
```

```
yValueAxis.visibleAxis = 1  
yValueAxis.visibleGrid = 0  
yValueAxis.visibleLabels = 1  
yValueAxis.visibleTicks = 1  
yValueAxis.zrangePref = 0
```

## Functions

### `sample1a( ... )`

A line plot with non-equidistant points in x-axis.

#### *Example*

```
def sample1a():
    "A line plot with non-equidistant points in x-axis."

    drawing = Drawing(400, 200)

    data = [
        ((1,1), (2,2), (2.5,1), (3,3), (4,5)),
        ((1,2), (2,3), (2.5,2), (3.5,5), (4,6))
    ]

    lp = LinePlot()

    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = data
    lp.joinedLines = 1
    lp.strokeColor = colors.black

    lp.lines.symbol = makeMarker('UK_Flag')


    lp.lines[0].strokeWidth = 2
    lp.lines[1].strokeWidth = 4

    lp.xValueAxis.valueMin = 0
    lp.xValueAxis.valueMax = 5
    lp.xValueAxis.valueStep = 1

    lp.yValueAxis.valueMin = 0
    lp.yValueAxis.valueMax = 7
    lp.yValueAxis.valueStep = 1

    drawing.add(lp)

    return drawing
```



**sample1b( ... )**

A line plot with non-equidistant points in x-axis.

*Example*

```
def sample1b():
    "A line plot with non-equidistant points in x-axis."

    drawing = Drawing(400, 200)

    data = [
        ((1,1), (2,2), (2.5,1), (3,3), (4,5)),
        ((1,2), (2,3), (2.5,2), (3.5,5), (4,6))
    ]

    lp = LinePlot()


    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = data
    lp.joinedLines = 1
    lp.lines.symbol = makeMarker('Circle')
    lp.lineLabelFormat = '%2.0f'
    lp.strokeColor = colors.black

    lp.xValueAxis.valueMin = 0
    lp.xValueAxis.valueMax = 5
    lp.xValueAxis.valueSteps = [1, 2, 2.5, 3, 4, 5]
    lp.xValueAxis.labelTextFormat = '%2.1f'

    lp.yValueAxis.valueMin = 0
    lp.yValueAxis.valueMax = 7
    lp.yValueAxis.valueStep = 1

    drawing.add(lp)

    return drawing
```



**sample1c( ... )**

A line plot with non-equidistant points in x-axis.

*Example*

```
def sample1c():
    "A line plot with non-equidistant points in x-axis."

    drawing = Drawing(400, 200)

    data = [
        ((1,1), (2,2), (2.5,1), (3,3), (4,5)),
        ((1,2), (2,3), (2.5,2), (3.5,5), (4,6))
    ]

    lp = LinePlot()


    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = data
    lp.joinedLines = 1
    lp.lines[0].symbol = makeMarker('FilledCircle')
    lp.lines[1].symbol = makeMarker('Circle')
    lp.lineLabelFormat = '%2.0f'
    lp.strokeColor = colors.black

    lp.xValueAxis.valueMin = 0
    lp.xValueAxis.valueMax = 5
    lp.xValueAxis.valueSteps = [1, 2, 2.5, 3, 4, 5]
    lp.xValueAxis.labelTextFormat = '%2.1f'

    lp.yValueAxis.valueMin = 0
    lp.yValueAxis.valueMax = 7
    lp.yValueAxis.valueSteps = [1, 2, 3, 5, 6]

    drawing.add(lp)

    return drawing
```





**sample2( ... )**

A line plot with non-equidistant points in x-axis.

*Example*

```
def sample2():
    "A line plot with non-equidistant points in x-axis."

    drawing = Drawing(400, 200)

    data = [
        ('25/11/1991',1),
        ('30/11/1991',1.000933333),
        ('31/12/1991',1.0062),
        ('31/01/1992',1.0112),
        ('29/02/1992',1.0158),
        ('31/03/1992',1.020733333),
        ('30/04/1992',1.026133333),
        ('31/05/1992',1.030266667),
        ('30/06/1992',1.034466667),
        ('31/07/1992',1.038733333),
        ('31/08/1992',1.0422),
        ('30/09/1992',1.045533333),
        ('31/10/1992',1.049866667),
        ('30/11/1992',1.054733333),
        ('31/12/1992',1.061),
    ],
    ]

    data[0] = preprocessData(data[0])

    lp = LinePlot()


    lp.x = 50
    lp.y = 50
    lp.height = 125
    lp.width = 300
    lp.data = data
    lp.joinedLines = 1
    lp.lines.symbol = makeMarker('FilledDiamond')
    lp.strokeColor = colors.black

    start = mktime(mkTimeTuple('25/11/1991'))
    t0 = mktime(mkTimeTuple('30/11/1991'))
    t1 = mktime(mkTimeTuple('31/12/1991'))
    t2 = mktime(mkTimeTuple('31/03/1992'))
    t3 = mktime(mkTimeTuple('30/06/1992'))
    t4 = mktime(mkTimeTuple('30/09/1992'))
    end = mktime(mkTimeTuple('31/12/1992'))
    lp.xValueAxis.valueMin = start
    lp.xValueAxis.valueMax = end
    lp.xValueAxis.valueSteps = [start, t0, t1, t2, t3, t4, end]
    lp.xValueAxis.labelTextFormat = seconds2str
    lp.xValueAxis.labels[1].dy = -20
    lp.xValueAxis.labels[2].dy = -35

    lp.yValueAxis.labelTextFormat = '%4.2f'
    lp.yValueAxis.valueMin = 100
    lp.yValueAxis.valueMax = 110
    lp.yValueAxis.valueStep = 2

    drawing.add(lp)

    return drawing
```



## piecharts

Basic Pie Chart class.

This permits you to customize and pop out individual wedges;  
supports elliptical and circular pies.

## Classes

### AbstractPieChart(PlotArea)

#### Public Attributes

**background** Handle to background object.

**debug** Used only for debugging.

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

#### *Example*

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

#### *Properties of Example Widget*

```
background = None
debug = 0
fillColor = None
height = 85
strokeColor = None
strokeWidth = 1
width = 180
x = 20
y = 10
```

## LegendedPie(Pie)

Pie with a two part legend (one editable with swatches, one hidden without swatches).

### Public Attributes

**background** Handle to background object.

**bottomPadding** Padding at bottom of drawing

**checkLabelOverlap** If true check and attempt to fix label overlaps(default off)

**data** list of numbers defining wedge sizes; need not sum to 1

**debug** Used only for debugging.

**direction** 'clockwise' or 'anticlockwise'

**drawLegend** If true then create and draw legend

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**labels** optional list of labels to use for each data point

**leftPadding** Padding on left of drawing

**legend1** Handle to legend for pie

**legendNumberFormat** Formatting routine for number on right hand side of legend.

**legendNumberOffset** Horizontal space between legend and numbers on r/hand side

**legend\_data** Numbers used on r/hand side of legend (or None)

**legend\_names** Names used in legend (or None)

**other\_threshold** A value for doing threshholding, not used yet.

**pieAndLegend\_colors** Colours used for both swatches and pie

**rightPadding** Padding on right of drawing

**simpleLabels** If true(default) use String not super duper WedgeLabel

**slices** collection of wedge descriptor objects

**startAngle** angle of first slice; like the compass, 0 is due North

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**topPadding** Padding at top of drawing

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### Example

```
def demo(self, drawing=None):
    if not drawing:
        tx,ty = self._getDrawingDimensions()
        drawing = Drawing(tx, ty)
    drawing.add(self.draw())
    return drawing
```

*Properties of Example Widget*

```
bottomPadding = 5
checkLabelOverlap = 0
data = [38.39999999999999,
        20.69999999999999,
        18.89999999999999,
        15.4,
        6.599999999999996]
direction = 'clockwise'
drawLegend = 1
height = 100
labels = None
leftPadding = 5
legend1.alignment = 'right'
legend1.autoXPadding = 5
legend1.autoYPadding = 2
legend1.boxAnchor = 'nw'
legend1.colEndCallout = None
legend1.colorNamePairs = [(Color(1,0,0), 'red'),
                           (Color(0,0,1), 'blue'),
                           (Color(0,.501961,0), 'green'),
                           (Color(1,.752941,.796078), 'pink'),
                           (Color(1,1,0), 'yellow'),
                           (PCMYKColor(11,11,72,0,spotName='PANTONE 458 CV'), 'AAA:'),
                           (PCMYKColor(100,65,0,30,spotName='PANTONE 288 CV'), 'AA:'),
                           (PCMYKColor(11,11,72,0,spotName='PANTONE 458 CV',density=75), 'A:'),
                           (PCMYKColor(100,65,0,30,spotName='PANTONE 288 CV',density=75), 'BBB:'),
                           (PCMYKColor(11,11,72,0,spotName='PANTONE 458 CV',density=50), 'NR:')]
legend1.columnMaximum = 7
legend1.deltax = 5.669999999999999
legend1.deltay = 14.17
legend1.dividerColor = Color(0,0,0)
legend1.dividerDashArray = None
legend1.dividerLines = 0
legend1.dividerOffsX = (0, 0)
legend1.dividerOffsY = 0
legend1.dividerWidth = 0.5
legend1.dx = 5.669999999999999
legend1.dxTextSpace = 11.390000000000001
legend1.dy = 5.669999999999999
legend1.fillColor = Color(0,0,0)
legend1.fontName = 'Helvetica-Bold'
legend1.fontSize = 6
legend1.sepSpace = 0
legend1.strokeColor = Color(0,0,0)
legend1.strokeWidth = 0.5
legend1.swatchMarker = None
legend1.variColumn = 0
legend1.x = 117
legend1.y = 100
legend1.yGap = 0
legendNumberFormat = '%.1f%%'
legendNumberOffset = 51
legend_data = [38.39999999999999,
               20.69999999999999,
               18.89999999999999,
               15.4,
               6.599999999999996]
legend_names = ['AAA:', 'AA:', 'A:', 'BBB:', 'NR:']
pieAndLegend_colors = [PCMYKColor(11,11,72,0,spotName='PANTONE 458 CV'),
                        PCMYKColor(100,65,0,30,spotName='PANTONE 288 CV'),
                        PCMYKColor(11,11,72,0,spotName='PANTONE 458 CV',density=75),
                        PCMYKColor(100,65,0,30,spotName='PANTONE 288 CV',density=75),
                        PCMYKColor(11,11,72,0,spotName='PANTONE 458 CV',density=50),
                        PCMYKColor(100,65,0,30,spotName='PANTONE 288 CV',density=50)]

rightPadding = 5
simpleLabels = 1
slices = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0146F440>
startAngle = 90
topPadding = 5
width = 100
x = 0
y = 0
```

## Pie(AbstractPieChart)

### Public Attributes

- background** Handle to background object.
- checkLabelOverlap** If true check and attempt to fix label overlaps(default off)
- data** list of numbers defining wedge sizes; need not sum to 1
- debug** Used only for debugging.
- direction** 'clockwise' or 'anticlockwise'
- fillColor** Color of the plot area interior.
- height** Height of the chart.
- labels** optional list of labels to use for each data point
- other\_threshold** A value for doing thresholding, not used yet.
- simpleLabels** If true(default) use String not super duper WedgeLabel
- slices** collection of wedge descriptor objects
- startAngle** angle of first slice; like the compass, 0 is due North
- strokeColor** Color of the plot area border.
- strokeWidth** Width plot area border.
- width** Width of the chart.
- x** X position of the lower-left corner of the chart.
- y** Y position of the lower-left corner of the chart.

### Example

```
def demo(self):
    d = Drawing(200, 100)

    pc = Pie()
    pc.x = 50
    pc.y = 10
    pc.width = 100
    pc.height = 80
    pc.data = [10,20,30,40,50,60]
    pc.labels = ['a','b','c','d','e','f']

    pc.slices.strokeWidth=0.5
    pc.slices[3].popout = 10
    pc.slices[3].strokeWidth = 2
    pc.slices[3].strokeDashArray = [2,2]
    pc.slices[3].labelRadius = 1.75
    pc.slices[3].fontColor = colors.red
    pc.slices[0].fillColor = colors.darkcyan
    pc.slices[1].fillColor = colors.blueviolet
    pc.slices[2].fillColor = colors.blue
    pc.slices[3].fillColor = colors.cyan
    pc.slices[4].fillColor = colors.aquamarine
    pc.slices[5].fillColor = colors.cadetblue
    pc.slices[6].fillColor = colors.lightcoral

    d.add(pc)
    return d
```

### Properties of Example Widget

```
checkLabelOverlap = 0
```

```
data = [1, 2.2999999999999998, 1.7, 4.2000000000000002]
direction = 'clockwise'
height = 100
labels = None
simpleLabels = 1
slices = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x0147C3C8>
startAngle = 90
width = 100
x = 0
y = 0
```

## Pie3d(Pie)

### Public Attributes

**angle\_3d** The view angle.

**background** Handle to background object.

**checkLabelOverlap** If true check and attempt to fix label overlaps(default off)

**data** list of numbers defining wedge sizes; need not sum to 1

**debug** Used only for debugging.

**depth\_3d** depth of the pie.

**direction** 'clockwise' or 'anticlockwise'

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**labels** optional list of labels to use for each data point

**other\_threshold** A value for doing thresholding, not used yet.

**perspective** A flattening parameter.

**simpleLabels** If true(default) use String not super duper WedgeLabel

**slices** collection of wedge descriptor objects

**startAngle** angle of first slice; like the compass, 0 is due North

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.

**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

### Example

```
def demo(self):
    d = Drawing(200, 100)

    pc = Pie()
    pc.x = 50
    pc.y = 10
    pc.width = 100
    pc.height = 80
    pc.data = [10,20,30,40,50,60]
    pc.labels = ['a','b','c','d','e','f']

    pc.slices.strokeWidth=0.5
    pc.slices[3].popout = 10
    pc.slices[3].strokeWidth = 2
    pc.slices[3].strokeDashArray = [2,2]
    pc.slices[3].labelRadius = 1.75
    pc.slices[3].fontColor = colors.red
    pc.slices[0].fillColor = colors.darkcyan
    pc.slices[1].fillColor = colors.blueviolet
    pc.slices[2].fillColor = colors.blue
    pc.slices[3].fillColor = colors.cyan
    pc.slices[4].fillColor = colors.aquamarine
    pc.slices[5].fillColor = colors.cadetblue
    pc.slices[6].fillColor = colors.lightcoral
    self.slices[1].visible = 0
    self.slices[3].visible = 1
    self.slices[4].visible = 1
    self.slices[5].visible = 1
```



```
self.slices[6].visible = 0

d.add(pc)
return d
```

#### *Properties of Example Widget*

```
checkLabelOverlap = 0
data = [12.5, 20.100000000000001, 2.0, 22.0, 5.0, 18.0, 13.0]
direction = 'clockwise'
height = 200
labels = None
simpleLabels = 1
slices = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x01481878>
startAngle = 90
width = 300
x = 0
y = 0
```

## **WedgeLabel (Label)**

### **Public Attributes**

**angle** None

**bottomPadding** padding at bottom of box

**boxAnchor** None

**boxFillColor** None

**boxStrokeColor** None

**boxStrokeWidth** None

**boxTarget** None

**dx** None

**dy** None

**fillColor** None

**fontName** None

**fontSize** None

**height** None

**leading** None

**leftPadding** padding at left of box

**maxWidth** None

**rightPadding** padding at right of box

**strokeColor** None

**strokeWidth** None

**text** None

**textAnchor** None

**topPadding** padding at top of box

**visible** True if the label is to be drawn

**width** None

**x** None

**y** None

### *Example*

```
def demo(self):
    """This shows a label positioned with its top right corner
    at the top centre of the drawing, and rotated 45 degrees."""

    d = Drawing(200, 100)

    # mark the origin of the label
    d.add(Circle(100,90, 5, fillColor=colors.green))

    lab = Label()
    lab.setOrigin(100,90)
    lab.boxAnchor = 'ne'
    lab.angle = 45
    lab.dx = 0
    lab.dy = -20
    lab.boxStrokeColor = colors.green
```

```
lab.setText('Another\nMulti-Line\nString')
d.add(lab)

return d
```

#### *Properties of Example Widget*

```
angle = 0
bottomPadding = 0
boxAnchor = 'c'
boxFillColor = None
boxStrokeColor = None
boxStrokeWidth = 0.5
boxTarget = 'normal'
dx = 0
dy = 0
fillColor = Color(0,0,0)
fontName = 'Times-Roman'
fontSize = 10
height = None
leading = None
leftPadding = 0
maxWidth = None
rightPadding = 0
strokeColor = None
strokeWidth = 0.10000000000000001
textAnchor = 'start'
topPadding = 0
visible = 1
width = None
x = 0
y = 0
```

## Functions

### **sample0a( ... )**

Make a degenerated pie chart with only one slice.

#### *Example*


```
def sample0a():
    "Make a degenerated pie chart with only one slice."

    d = Drawing(400, 200)

    pc = Pie()
    pc.x = 150
    pc.y = 50
    pc.data = [10]
    pc.labels = ['a']
    pc.slices.strokeWidth=1#0.5

    d.add(pc)

    return d
```




**sample0b( ... )**

Make a degenerated pie chart with only one slice.

*Example*

```
def sample0b():  
    "Make a degenerated pie chart with only one slice."  
  
    d = Drawing(400, 200)  
  
    pc = Pie()  
    pc.x = 150  
    pc.y = 50  
    pc.width = 120  
    pc.height = 100  
    pc.data = [10]  
    pc.labels = ['a']  
    pc.slices.strokeWidth=1#0.5  
  
    d.add(pc)  
  
    return d
```



**sample1( ... )**

Make a typical pie chart with with one slice treated in a special way.

*Example*

```
def sample1():
    "Make a typical pie chart with with one slice treated in a special way."


    d = Drawing(400, 200)

    pc = Pie()
    pc.x = 150
    pc.y = 50
    pc.data = [10, 20, 30, 40, 50, 60]
    pc.labels = ['a', 'b', 'c', 'd', 'e', 'f']

    pc.slices.strokeWidth=1#0.5
    pc.slices[3].popout = 20
    pc.slices[3].strokeWidth = 2
    pc.slices[3].strokeDashArray = [2,2]
    pc.slices[3].labelRadius = 1.75
    pc.slices[3].fontColor = colors.red

    d.add(pc)

    return d
```



**sample2( ... )**

Make a pie chart with nine slices.

*Example*

```
def sample2():
    "Make a pie chart with nine slices."

    d = Drawing(400, 200)


    pc = Pie()
    pc.x = 125
    pc.y = 25
    pc.data = [0.31, 0.148, 0.108,
               0.076, 0.033, 0.03,
               0.019, 0.126, 0.15]
    pc.labels = ['1', '2', '3', '4', '5', '6', '7', '8', 'X']

    pc.width = 150
    pc.height = 150
    pc.slices.strokeWidth=1#0.5

    pc.slices[0].fillColor = colors.steelblue
    pc.slices[1].fillColor = colors.thistle
    pc.slices[2].fillColor = colors.cornflower
    pc.slices[3].fillColor = colors.lightsteelblue
    pc.slices[4].fillColor = colors.aquamarine
    pc.slices[5].fillColor = colors.cadetblue
    pc.slices[6].fillColor = colors.lightcoral
    pc.slices[7].fillColor = colors.tan
    pc.slices[8].fillColor = colors.darkseagreen

    d.add(pc)

    return d
```



**sample3( ... )**

Make a pie chart with a very slim slice.

*Example*

```
def sample3():
    "Make a pie chart with a very slim slice."

    d = Drawing(400, 200)


    pc = Pie()
    pc.x = 125
    pc.y = 25

    pc.data = [74, 1, 25]

    pc.width = 150
    pc.height = 150
    pc.slices.strokeWidth=1#0.5
    pc.slices[0].fillColor = colors.steelblue
    pc.slices[1].fillColor = colors.thistle
    pc.slices[2].fillColor = colors.cornflower

    d.add(pc)

    return d
```





**sample4( ... )**

Make a pie chart with several very slim slices.

*Example*

```
def sample4():
    "Make a pie chart with several very slim slices."

    d = Drawing(400, 200)


    pc = Pie()
    pc.x = 125
    pc.y = 25

    pc.data = [74, 1, 1, 1, 1, 22]

    pc.width = 150
    pc.height = 150
    pc.slices.strokeWidth=1#0.5
    pc.slices[0].fillColor = colors.steelblue
    pc.slices[1].fillColor = colors.thistle
    pc.slices[2].fillColor = colors.cornflower
    pc.slices[3].fillColor = colors.lightsteelblue
    pc.slices[4].fillColor = colors.aquamarine
    pc.slices[5].fillColor = colors.cadetblue

    d.add(pc)

    return d
```



## slidebox

### Classes

#### SlideBox(Widget)

Returns a slidebox widget

### Public Attributes

**background** Colour of the background to the drawing (if any)

**bottomPadding** Padding at bottom of drawing

**boxHeight** Height of the boxes

**boxOutlineColor** Colour used to outline the boxes (if any)

**boxOutlineWidth** Width of the box outline (if any)

**boxSpacing** Space between the boxes

**boxWidth** Width of the boxes

**endColor** Color of last box

**labelFillColor** Colour for number insides

**labelFontName** Name of font used for the labels

**labelFontSize** Size of font used for the labels

**labelStrokeColor** Colour for for number outlines

**leftPadding** Padding on left of drawing

**numberOfBoxes** How many boxes there are

**rightPadding** Padding on right of drawing

**sourceLabelFillColor** Colour ink for the 'source' label (bottom right)

**sourceLabelFontName** Name of font used for the 'source' label

**sourceLabelFontSize** Font size for the 'source' label

**sourceLabelOffset** Padding at bottom of drawing

**sourceLabelText** Text used for the 'source' label (can be empty)

**startColor** Color of first box

**topPadding** Padding at top of drawing

**triangleFillColor** Colour of indicator triangles

**triangleHeight** Height of indicator triangles

**trianglePosition** Which box is highlighted by the triangles

**triangleStrokeColor** Colour of indicator triangle outline

**triangleStrokeWidth** Colour of indicator triangle outline

**triangleWidth** Width of indicator triangles

#### Example

```
def demo(self, drawing=None):
```

```
from reportlab.lib import colors
if not drawing:
    tx,ty=self._getDrawingDimensions()
    drawing = Drawing(tx,ty)
drawing.add(self.draw())
return drawing
```



Source: ReportLab

### *Properties of Example Widget*

```
background = None
bottomPadding = 5
boxHeight = 15.590551181102363
boxOutlineColor = Color(0,0,0)
boxOutlineWidth = 0.5799999999999996
boxSpacing = 2.1259842519685037
boxWidth = 20.69291338582677
endColor = Color(.098039,.301961,.529412)
labelFillColor = Color(1,1,1)
labelFontName = 'Helvetica-Bold'
labelFontSize = 10
labelStrokeColor = Color(0,0,0)
leftPadding = 5
numberOfBoxes = 7
rightPadding = 5
sourceLabelFillColor = Color(0,0,0)
sourceLabelFontName = 'Helvetica-Oblique'
sourceLabelFontSize = 6
sourceLabelOffset = 5.6692913385826778
sourceLabelText = 'Source: ReportLab'
startColor = Color(.909804,.878431,.466667)
topPadding = 5
triangleFillColor = Color(1,1,1)
triangleHeight = 3.401574803149606
trianglePosition = 7
triangleStrokeColor = Color(0,0,0)
triangleStrokeWidth = 0.5799999999999996
triangleWidth = 10.771653543307087
```

## spider

Spider Chart

Normal use shows variation of 5-10 parameters against some 'norm' or target. When there is more than one series, place the series with the largest numbers first, as it will be overdrawn by each successive one.

## Classes

### SpiderChart(PlotArea)

#### Public Attributes

**background** Handle to background object.

**data** Data to be plotted, list of (lists of) numbers.

**debug** Used only for debugging.

**direction** 'clockwise' or 'anticlockwise'

**fillColor** Color of the plot area interior.

**height** Height of the chart.

**labels** optional list of labels to use for each data point

**spokeLabels** collection of spoke label descriptor objects

**spokes** collection of spoke descriptor objects

**startAngle** angle of first slice; like the compass, 0 is due North

**strandLabels** collection of strand label descriptor objects

**strands** collection of strand descriptor objects

**strokeColor** Color of the plot area border.

**strokeWidth** Width plot area border.


**width** Width of the chart.

**x** X position of the lower-left corner of the chart.

**y** Y position of the lower-left corner of the chart.

#### Example

```
def demo(self):
    d = Drawing(200, 200)
    d.add(SpiderChart())
    return d
```



#### *Properties of Example Widget*

```
background = None
data = [[10, 12, 14, 16, 14, 12], [6, 8, 10, 12, 9, 11]]
debug = 0
direction = 'clockwise'
fillColor = None
height = 180
labels = ['a', 'b', 'c', 'd', 'e', 'f']
spokeLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x014F2418>
spokes = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x014F23C8>
startAngle = 90
strandLabels = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x014F2468>
strands = <reportlab.graphics.widgetbase.TypedPropertyCollection instance at 0x014F2350>
strokeColor = None
strokeWidth = 1
width = 180
x = 10
y = 10
```

## **SpokeLabel (WedgeLabel)**

### **Public Attributes**

**angle** None

**bottomPadding** padding at bottom of box

**boxAnchor** None

**boxFillColor** None

**boxStrokeColor** None

**boxStrokeWidth** None

**boxTarget** None

**dx** None

**dy** None

**fillColor** None

**fontName** None

**fontSize** None

**height** None

**leading** None

**leftPadding** padding at left of box

**maxWidth** None

**rightPadding** padding at right of box

**strokeColor** None

**strokeWidth** None

**text** None

**textAnchor** None

**topPadding** padding at top of box

**visible** True if the label is to be drawn

**width** None

**x** None

**y** None

### *Example*

```
def demo(self):
    """This shows a label positioned with its top right corner
    at the top centre of the drawing, and rotated 45 degrees."""

    d = Drawing(200, 100)

    # mark the origin of the label
    d.add(Circle(100,90, 5, fillColor=colors.green))

    lab = Label()
    lab.setOrigin(100,90)
    lab.boxAnchor = 'ne'
    lab.angle = 45
    lab.dx = 0
    lab.dy = -20
    lab.boxStrokeColor = colors.green
```

```
lab.setText('Another\nMulti-Line\nString')
d.add(lab)

return d
```

### *Properties of Example Widget*

```
angle = 0
bottomPadding = 0
boxAnchor = 'c'
boxFillColor = None
boxStrokeColor = None
boxStrokeWidth = 0.5
boxTarget = 'normal'
dx = 0
dy = 0
fillColor = Color(0,0,0)
fontName = 'Times-Roman'
fontSize = 10
height = None
leading = None
leftPadding = 0
maxWidth = None
rightPadding = 0
strokeColor = None
strokeWidth = 0.10000000000000001
textAnchor = 'start'
topPadding = 0
visible = 1
width = None
x = 0
y = 0
```

## **StrandLabel ( SpokeLabel )**

### **Public Attributes**

**angle** None

**bottomPadding** padding at bottom of box

**boxAnchor** None

**boxFillColor** None

**boxStrokeColor** None

**boxStrokeWidth** None

**boxTarget** None

**dR** radial shift for label

**dx** None

**dy** None

**fillColor** None

**fontName** None

**fontSize** None

**format** Format for the label

**height** None

**leading** None

**leftPadding** padding at left of box

**maxWidth** None

**rightPadding** padding at right of box

**strokeColor** None

**strokeWidth** None

**text** None

**textAnchor** None

**topPadding** padding at top of box

**visible** True if the label is to be drawn

**width** None

**x** None

**y** None

### *Example*

```
def demo(self):
    """This shows a label positioned with its top right corner
    at the top centre of the drawing, and rotated 45 degrees."""

    d = Drawing(200, 100)

    # mark the origin of the label
    d.add(Circle(100,90, 5, fillColor=colors.green))

    lab = Label()
    lab.setOrigin(100,90)
    lab.boxAnchor = 'ne'
```



```
lab.angle = 45
lab.dx = 0
lab.dy = -20
lab.boxStrokeColor = colors.green
lab.setText('Another\nMulti-Line\nString')
d.add(lab)

return d
```

#### *Properties of Example Widget*

```
angle = 0
bottomPadding = 0
boxAnchor = 'c'
boxFillColor = None
boxStrokeColor = None
boxStrokeWidth = 0.5
boxTarget = 'normal'
dR = 0
dx = 0
dy = 0
fillColor = Color(0,0,0)
fontName = 'Times-Roman'
fontSize = 10
format = ''
height = None
leading = None
leftPadding = 0
maxWidth = None
rightPadding = 0
strokeColor = None
strokeWidth = 0.10000000000000001
textAnchor = 'start'
topPadding = 0
visible = 1
width = None
x = 0
y = 0
```


## Functions

### `sample1( ... )`

Make a simple spider chart

#### *Example*

```
def sample1():
    "Make a simple spider chart"
    d = Drawing(400, 400)
    sp = SpiderChart()
    sp.x = 50
    sp.y = 50
    sp.width = 300
    sp.height = 300
    sp.data = [[10,12,14,16,14,12], [6,8,10,12,9,15],[7,8,17,4,12,8]]
    sp.labels = ['a','b','c','d','e','f']
    sp.strands[0].strokeColor = colors.cornsilk
    sp.strands[1].strokeColor = colors.cyan
    sp.strands[2].strokeColor = colors.palegreen
    sp.strands[0].fillColor = colors.cornsilk
    sp.strands[1].fillColor = colors.cyan
    sp.strands[2].fillColor = colors.palegreen
    sp.spokes.strokeDashArray = (2,2)
    d.add(sp)
    return d
```






**sample2( ... )**

Make a spider chart with markers, but no fill

*Example*

```
def sample2():
    "Make a spider chart with markers, but no fill"
    d = Drawing(400, 400)
    sp = SpiderChart()
    sp.x = 50
    sp.y = 50
    sp.width = 300
    sp.height = 300
    sp.data = [[10,12,14,16,14,12], [6,8,10,12,9,15],[7,8,17,4,12,8]]
    sp.labels = ['U','V','W','X','Y','Z']
    sp.strands.strokeWidth = 1
    sp.strands[0].fillColor = colors.pink
    sp.strands[1].fillColor = colors.lightblue
    sp.strands[2].fillColor = colors.palegreen
    sp.strands[0].strokeColor = colors.red
    sp.strands[1].strokeColor = colors.blue
    sp.strands[2].strokeColor = colors.green
    sp.strands.symbol = "FilledDiamond"
    sp.strands[1].symbol = makeMarker("Circle")
    sp.strands[1].symbol.strokeWidth = 0.5
    sp.strands[1].symbol.fillColor = colors.yellow
    sp.strands.symbolSize = 6
    sp.strandLabels[0,3]._text = 'special'
    sp.strandLabels[0,1]._text = 'one'
    sp.strandLabels[0,0]._text = 'zero'
    sp.strandLabels[1,0]._text = 'Earth'
    sp.strandLabels[2,2]._text = 'Mars'
    sp.strandLabels.format = 'values'
    sp.strandLabels.dR = -5
    d.add(sp)
    return d
```



## textlabels

#Copyright ReportLab Europe Ltd. 2000-2004

#see license.txt for license details

#history <http://www.reportlab.co.uk/cgi-bin/viewcvs.cgi/public/reportlab/trunk/reportlab/graphics/charts/textlabels.py>

## Classes

### BarChartLabel (Label)

An extended Label allowing for nudging, lines visibility etc

## Public Attributes

**angle** None

**bottomPadding** padding at bottom of box

**boxAnchor** None

**boxFillColor** None

**boxStrokeColor** None

**boxStrokeWidth** None

**boxTarget** None

**dx** None

**dy** None

**fillColor** None

**fixedEnd** None or fixed draw ends +/-

**fixedStart** None or fixed draw starts +/-

**fontName** None

**fontSize** None

**height** None

**leading** None

**leftPadding** padding at left of box

**lineStrokeColor** Color for a drawn line

**lineStrokeWidth** Non-zero for a drawn line

**maxWidth** None

**nudge** Non-zero sign dependent nudge

**rightPadding** padding at right of box

**strokeColor** None

**strokeWidth** None

**text** None

**textAnchor** None

**topPadding** padding at top of box

**visible** True if the label is to be drawn

**width** None

**x** None

**y** None

### *Example*

```
def demo(self):
    """This shows a label positioned with its top right corner
    at the top centre of the drawing, and rotated 45 degrees."""

    d = Drawing(200, 100)

    # mark the origin of the label
    d.add(Circle(100,90, 5, fillColor=colors.green))

    lab = Label()
    lab.setOrigin(100,90)
    lab.boxAnchor = 'ne'
    lab.angle = 45
    lab.dx = 0
    lab.dy = -20
    lab.boxStrokeColor = colors.green
    lab.setText('Another\nMulti-Line\nString')
    d.add(lab)

    return d
```

### *Properties of Example Widget*

```
angle = 0
bottomPadding = 0
boxAnchor = 'c'
boxFillColor = None
boxStrokeColor = None
boxStrokeWidth = 0.5
boxTarget = 'normal'
dx = 0
dy = 0
fillColor = Color(0,0,0)
fixedEnd = None
fixedStart = None
fontName = 'Times-Roman'
fontSize = 10
height = None
leading = None
leftPadding = 0
lineStrokeColor = None
lineStrokeWidth = 0
maxWidth = None
nudge = 0
rightPadding = 0
strokeColor = None
strokeWidth = 0.10000000000000001
textAnchor = 'start'
topPadding = 0
visible = 1
width = None
x = 0
y = 0
```

## Label (Widget)

A text label to attach to something else, such as a chart axis.

This allows you to specify an offset, angle and many anchor properties relative to the label's origin. It allows, for example, angled multiline axis labels.

## Public Attributes

**angle** None

**bottomPadding** padding at bottom of box

**boxAnchor** None

**boxFillColor** None

**boxStrokeColor** None

**boxStrokeWidth** None

**boxTarget** None

**dx** None

**dy** None

**fillColor** None

**fontName** None

**fontSize** None

**height** None

**leading** None

**leftPadding** padding at left of box

**maxWidth** None

**rightPadding** padding at right of box

**strokeColor** None

**strokeWidth** None

**text** None

**textAnchor** None

**topPadding** padding at top of box

**visible** True if the label is to be drawn

**width** None

**x** None

**y** None

### Example

```
def demo(self):
    """This shows a label positioned with its top right corner
    at the top centre of the drawing, and rotated 45 degrees."""

    d = Drawing(200, 100)

    # mark the origin of the label
    d.add(Circle(100,90, 5, fillColor=colors.green))
```



```
lab = Label()
lab.setOrigin(100,90)
lab.boxAnchor = 'ne'
lab.angle = 45
lab.dx = 0
lab.dy = -20
lab.boxStrokeColor = colors.green
lab.setText('Another\nMulti-Line\nString')
d.add(lab)

return d
```

#### *Properties of Example Widget*

```
angle = 0
bottomPadding = 0
boxAnchor = 'c'
boxFillColor = None
boxStrokeColor = None
boxStrokeWidth = 0.5
boxTarget = 'normal'
dx = 0
dy = 0
fillColor = Color(0,0,0)
fontName = 'Times-Roman'
fontSize = 10
height = None
leading = None
leftPadding = 0
maxWidth = None
rightPadding = 0
strokeColor = None
strokeWidth = 0.10000000000000001
textAnchor = 'start'
topPadding = 0
visible = 1
width = None
x = 0
y = 0
```

## **NA\_Label ( BarChartLabel )**

An extended Label allowing for nudging, lines visibility etc

### **Public Attributes**

**angle** None

**bottomPadding** padding at bottom of box

**boxAnchor** None

**boxFillColor** None

**boxStrokeColor** None

**boxStrokeWidth** None

**boxTarget** None

**dx** None

**dy** None

**fillColor** None

**fixedEnd** None or fixed draw ends +/-

**fixedStart** None or fixed draw starts +/-

**fontName** None

**fontSize** None

**height** None

**leading** None

**leftPadding** padding at left of box

**lineStrokeColor** Color for a drawn line

**lineStrokeWidth** Non-zero for a drawn line

**maxWidth** None

**nudge** Non-zero sign dependent nudge

**rightPadding** padding at right of box

**strokeColor** None

**strokeWidth** None

**text** Text to be used for N/A values

**textAnchor** None

**topPadding** padding at top of box

**visible** True if the label is to be drawn

**width** None

**x** None

**y** None

### *Example*


```
def demo(self):
    """This shows a label positioned with its top right corner
    at the top centre of the drawing, and rotated 45 degrees."""
```

```
d = Drawing(200, 100)

# mark the origin of the label
d.add(Circle(100,90, 5, fillColor=colors.green))

lab = Label()
lab.setOrigin(100,90)
lab.boxAnchor = 'ne'
lab.angle = 45
lab.dx = 0
lab.dy = -20
lab.boxStrokeColor = colors.green
lab.setText('Another\nMulti-Line\nString')
d.add(lab)

return d
```



#### *Properties of Example Widget*

```
angle = 0
bottomPadding = 0
boxAnchor = 'c'
boxFillColor = None
boxStrokeColor = None
boxStrokeWidth = 0.5
boxTarget = 'normal'
dx = 0
dy = 0
fillColor = Color(0,0,0)
fixedEnd = None
fixedStart = None
fontName = 'Times-Roman'
fontSize = 10
height = None
leading = None
leftPadding = 0
lineStrokeColor = None
lineStrokeWidth = 0
maxWidth = None
nudge = 0
rightPadding = 0
strokeColor = None
strokeWidth = 0.10000000000000001
text = 'n/a'
textAnchor = 'start'
topPadding = 0
visible = 1
width = None
x = 0
y = 0
```

## bubble

#Autogenerated by ReportLab guiedit do not edit


## Classes

### Bubble(\_DrawingEditorMixin, Drawing)

#### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,ScatterPlot(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.lines[0].strokeColor = color01
    self.chart.lines[1].strokeColor = color02
    self.chart.lines[2].strokeColor = color03
    self.chart.lines[3].strokeColor = color04
    self.chart.lines[4].strokeColor = color05
    self.chart.lines[5].strokeColor = color06
    self.chart.lines[6].strokeColor = color07
    self.chart.lines[7].strokeColor = color08
    self.chart.lines[8].strokeColor = color09
    self.chart.lines[9].strokeColor = color10
    self.chart.lines.symbol.kind = 'Circle'
    self.chart.lines.symbol.size = 15
    self.chart.fillColor = backgroundGrey
    self.chart.lineLabels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontSize = 7
    self.chart.xValueAxis.forceZero = 0
    self.chart.data = [((100,100), (200,200), (250,210), (300,300), (350,450))]
    self.chart.xValueAxis.avoidBoundFrac = 1
    self.chart.xValueAxis.gridEnd = 115
    self.chart.xValueAxis.tickDown = 3
    self.chart.xValueAxis.visibleGrid = 1
    self.chart.yValueAxis.tickLeft = 3
    self.chart.yValueAxis.labels.fontName = 'Helvetica'
    self.chart.yValueAxis.labels.fontSize = 7
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
    self.Title.textAnchor = 'middle'
    self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
    self.Legend.colorNamePairs = [(color01, 'Widgets')]
    self.Legend.fontName = 'Helvetica'
    self.Legend.fontSize = 7
    self.Legend.x = 153
    self.Legend.y = 85
    self.Legend.dxTextSpace = 5
    self.Legend.dy = 5
    self.Legend.dx = 5
    self.Legend.deltay = 5
    self.Legend.alignment = 'right'
    self.chart.lineLabelFormat = None
    self.chart.xLabel = 'X Axis'
    self.chart.y = 30
    self.chart.yLabel = 'Y Axis'
    self.chart.yValueAxis.labelTextFormat = '%d'
    self.chart.yValueAxis.forceZero = 1
    self.chart.xValueAxis.forceZero = 1

    self._add(self,0,name='preview',validate=None,desc=None)
```



## clustered\_bar

#Autogenerated by ReportLab guiedit do not edit

## Classes

### ClusteredBar(\_DrawingEditorMixin, Drawing)


#### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,HorizontalBarChart(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.bars[0].fillColor = color01
    self.chart.bars[1].fillColor = color02
    self.chart.bars[2].fillColor = color03
    self.chart.bars[3].fillColor = color04
    self.chart.bars[4].fillColor = color05
    self.chart.bars[5].fillColor = color06
    self.chart.bars[6].fillColor = color07
    self.chart.bars[7].fillColor = color08
    self.chart.bars[8].fillColor = color09
    self.chart.bars[9].fillColor = color10
    self.chart.fillColor = backgroundGrey
    self.chart.barLabels.fontName = 'Helvetica'
    self.chart.valueAxis.labels.fontName = 'Helvetica'
    self.chart.valueAxis.labels.fontSize = 6
    self.chart.valueAxis.forceZero = 1
    self.chart.data = [(100, 150, 180), (125, 180, 200)]
    self.chart.groupSpacing = 15
    self.chart.valueAxis.avoidBoundFrac = 1
    self.chart.valueAxis.gridEnd = 80
    self.chart.valueAxis.tickDown = 3
    self.chart.valueAxis.visibleGrid = 1
    self.chart.categoryAxis.categoryNames = ['North', 'South', 'Central']
    self.chart.categoryAxis.tickLeft = 3
    self.chart.categoryAxis.labels.fontName = 'Helvetica'
    self.chart.categoryAxis.labels.fontSize = 6
    self.chart.categoryAxis.labels.dx = -3
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
    self.Title.textAnchor = 'middle'
```

```

self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
self.Legend.fontName      = 'Helvetica'
self.Legend.fontSize       = 7
self.Legend.x              = 153
self.Legend.y              = 85
self.Legend.dxTextSpace   = 5
self.Legend.dy             = 5
self.Legend.dx             = 5
self.Legend.deltay        = 5
self.Legend.alignment      = 'right'
self._add(self,Label(),name='XLabel',validate=None,desc="The label on the horizontal axis")
self.XLabel.fontName       = 'Helvetica'
self.XLabel.fontSize       = 7
self.XLabel.x              = 85
self.XLabel.y              = 10
self.XLabel.textAnchor     = 'middle'
self.XLabel.maxWidth       = 100
self.XLabel.height         = 20
self.XLabel._text          = "X Axis"
self._add(self,Label(),name='YLabel',validate=None,desc="The label on the vertical axis")
self.YLabel.fontName       = 'Helvetica'
self.YLabel.fontSize       = 7
self.YLabel.x              = 12
self.YLabel.y              = 80
self.YLabel.angle          = 90
self.YLabel.textAnchor     = 'middle'
self.YLabel.maxWidth       = 100
self.YLabel.height         = 20
self.YLabel._text          = "Y Axis"
self._add(self,0,name='preview',validate=None,desc=None)

```



## clustered\_column

#Autogenerated by ReportLab guiedit do not edit

## Classes

### ClusteredColumn(\_DrawingEditorMixin, Drawing)


#### Example

```

def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,VerticalBarChart(),name='chart',validate=None,desc="The main chart")
    self.chart.width      = 115
    self.chart.height     = 80
    self.chart.x          = 30
    self.chart.y          = 40
    self.chart.bars[0].fillColor = color01
    self.chart.bars[1].fillColor = color02

```

```
self.chart.bars[2].fillColor = color03
self.chart.bars[3].fillColor = color04
self.chart.bars[4].fillColor = color05
self.chart.bars[5].fillColor = color06
self.chart.bars[6].fillColor = color07
self.chart.bars[7].fillColor = color08
self.chart.bars[8].fillColor = color09
self.chart.bars[9].fillColor = color10
self.chart.fillColor = backgroundGrey
self.chart.barLabels.fontName = 'Helvetica'
self.chart.valueAxis.labels.fontName = 'Helvetica'
self.chart.valueAxis.labels.fontSize = 7
self.chart.valueAxis.forceZero = 1
self.chart.data = [(100, 150, 180), (125, 180, 200)]
self.chart.groupSpacing = 15
self.chart.valueAxis.avoidBoundFrac = 1
self.chart.valueAxis.gridEnd = 115
self.chart.valueAxis.tickLeft = 3
self.chart.valueAxis.visibleGrid = 1
self.chart.categoryAxis.categoryNames = ['North', 'South', 'Central']
self.chart.categoryAxis.tickDown = 3
self.chart.categoryAxis.labels.fontName = 'Helvetica'
self.chart.categoryAxis.labels.fontSize = 7
self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
self.Title.fontName = 'Helvetica-Bold'
self.Title.fontSize = 7
self.Title.x = 100
self.Title.y = 135
self.Title._text = 'Chart Title'
self.Title.maxWidth = 180
self.Title.height = 20
self.Title.textAnchor = 'middle'
self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
self.Legend.fontName = 'Helvetica'
self.Legend.fontSize = 7
self.Legend.x = 153
self.Legend.y = 85
self.Legend.dxTextSpace = 5
self.Legend.dy = 5
self.Legend.dx = 5
self.Legend.deltay = 5
self.Legend.alignment = 'right'
self._add(self,Label(),name='XLabel',validate=None,desc="The label on the horizontal axis")
self.XLabel.fontName = 'Helvetica'
self.XLabel.fontSize = 7
self.XLabel.x = 85
self.XLabel.y = 10
self.XLabel.textAnchor = 'middle'
self.XLabel.maxWidth = 100
self.XLabel.height = 20
self.XLabel._text = "X Axis"
self._add(self,Label(),name='YLabel',validate=None,desc="The label on the vertical axis")
self.YLabel.fontName = 'Helvetica'
self.YLabel.fontSize = 7
self.YLabel.x = 12
self.YLabel.y = 80
self.YLabel.angle = 90
self.YLabel.textAnchor = 'middle'
self.YLabel.maxWidth = 100
self.YLabel.height = 20
self.YLabel._text = "Y Axis"
self._add(self,0,name='preview',validate=None,desc=None)
```



## exploded\_pie

#Autogenerated by ReportLab guiedit do not edit

## Classes


### ExplodedPie(\_DrawingEditorMixin, Drawing)

#### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,Pie(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 100
    self.chart.height = 100
    self.chart.x = 25
    self.chart.y = 25
    self.chart.slices[0].fillColor = color01
    self.chart.slices[1].fillColor = color02
    self.chart.slices[2].fillColor = color03
    self.chart.slices[3].fillColor = color04
    self.chart.slices[4].fillColor = color05
    self.chart.slices[5].fillColor = color06
    self.chart.slices[6].fillColor = color07
    self.chart.slices[7].fillColor = color08
    self.chart.slices[8].fillColor = color09
    self.chart.slices[9].fillColor = color10
    self.chart.data = (100, 150, 180)
    self.chart.startAngle = -90
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
    self.Title.textAnchor = 'middle'
    self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
    self.Legend.colorNamePairs = [(color01, 'North'), (color02, 'South'), (color03, 'Central')]
    self.Legend.fontName = 'Helvetica'
    self.Legend.fontSize = 7
    self.Legend.x = 160
    self.Legend.y = 85
    self.Legend.dxTextSpace = 5
    self.Legend.dy = 5
    self.Legend.dx = 5
    self.Legend.deltay = 5
    self.Legend.alignment = 'right'
    self.Legend.columnMaximum = 10
    self.chart.slices.strokeWidth = 1
    self.chart.slices.fontName = 'Helvetica'
    self.background = ShadedRect()
```



```
self.background.fillColorStart = backgroundGrey
self.background.fillColorEnd   = backgroundGrey
self.background.numShades      = 1
self.background.strokeWidth     = 0.5
self.background.x               = 20
self.background.y               = 20
self.chart.slices.popout        = 5
self.background.height          = 110
self.background.width           = 110
self._add(self,0,name='preview',validate=None,desc=None)
```



## filled\_radar

#Autogenerated by ReportLab guiedit do not edit


## Classes

### FilledRadarChart(\_DrawingEditorMixin, Drawing)

#### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,SpiderChart(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 90
    self.chart.height = 90
    self.chart.x = 45
    self.chart.y = 25
    self.chart.strands[0].fillColor = color01
    self.chart.strands[1].fillColor = color02
    self.chart.strands[2].fillColor = color03
    self.chart.strands[3].fillColor = color04
    self.chart.strands[4].fillColor = color05
    self.chart.strands[5].fillColor = color06
    self.chart.strands[6].fillColor = color07
    self.chart.strands[7].fillColor = color08
    self.chart.strands[8].fillColor = color09
    self.chart.strands[9].fillColor = color10
    self.chart.strandLabels.fontName = 'Helvetica'
    self.chart.strandLabels.fontSize = 6
    self.chart.fillColor = backgroundGrey
    self.chart.data = [(125, 180, 200), (100, 150, 180)]
    self.chart.labels = ['North', 'South', 'Central']
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
```

```
self.Title.textAnchor = 'middle'
self._add(self, Legend(), name='Legend', validate=None, desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
self.Legend.fontName = 'Helvetica'
self.Legend.fontSize = 7
self.Legend.x = 153
self.Legend.y = 85
self.Legend.dxTextSpace = 5
self.Legend.dy = 5
self.Legend.dx = 5
self.Legend.deltay = 5
self.Legend.alignment = 'right'
self._add(self, 0, name='preview', validate=None, desc=None)
```



## linechart\_with\_markers

#Autogenerated by ReportLab guiedit do not edit

### Classes

#### LineChartWithMarkers(\_DrawingEditorMixin, Drawing)


##### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,LinePlot(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.lines[0].strokeColor = color01
    self.chart.lines[1].strokeColor = color02
    self.chart.lines[2].strokeColor = color03
    self.chart.lines[3].strokeColor = color04
    self.chart.lines[4].strokeColor = color05
    self.chart.lines[5].strokeColor = color06
    self.chart.lines[6].strokeColor = color07
    self.chart.lines[7].strokeColor = color08
    self.chart.lines[8].strokeColor = color09
    self.chart.lines[9].strokeColor = color10
    self.chart.lines[0].symbol = makeMarker('FilledSquare')
    self.chart.lines[1].symbol = makeMarker('FilledDiamond')
    self.chart.lines[2].symbol = makeMarker('FilledStarFive')
    self.chart.lines[3].symbol = makeMarker('FilledTriangle')
    self.chart.lines[4].symbol = makeMarker('FilledCircle')
    self.chart.lines[5].symbol = makeMarker('FilledPentagon')
    self.chart.lines[6].symbol = makeMarker('FilledStarSix')
    self.chart.lines[7].symbol = makeMarker('FilledHeptagon')
```

```

self.chart.lines[8].symbol = makeMarker('FilledOctagon')
self.chart.lines[9].symbol = makeMarker('FilledCross')
self.chart.fillColor = backgroundGrey
self.chart.lineLabels.fontName = 'Helvetica'
self.chart.xValueAxis.labels.fontName = 'Helvetica'
self.chart.xValueAxis.labels.fontSize = 7
self.chart.xValueAxis.forceZero = 0
self.chart.data = [(0, 50), (100,100), (200,200), (250,210), (300,300), (400,500)]
self.chart.xValueAxis.avoidBoundFrac = 1
self.chart.xValueAxis.gridEnd = 115
self.chart.xValueAxis.tickDown = 3
self.chart.xValueAxis.visibleGrid = 1
self.chart.yValueAxis.tickLeft = 3
self.chart.yValueAxis.labels.fontName = 'Helvetica'
self.chart.yValueAxis.labels.fontSize = 7
self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
self.Title.fontName = 'Helvetica-Bold'
self.Title.fontSize = 7
self.Title.x = 100
self.Title.y = 135
self.Title._text = 'Chart Title'
self.Title.maxWidth = 180
self.Title.height = 20
self.Title.textAnchor = 'middle'
self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
self.Legend.fontName = 'Helvetica'
self.Legend.fontSize = 7
self.Legend.x = 153
self.Legend.y = 85
self.Legend.dxTextSpace = 5
self.Legend.dy = 5
self.Legend.dx = 5
self.Legend.deltay = 5
self.Legend.alignment = 'right'
self._add(self,Label(),name='XLabel',validate=None,desc="The label on the horizontal axis")
self.XLabel.fontName = 'Helvetica'
self.XLabel.fontSize = 7
self.XLabel.x = 85
self.XLabel.y = 10
self.XLabel.textAnchor = 'middle'
self.XLabel.maxWidth = 100
self.XLabel.height = 20
self.XLabel._text = "X Axis"
self._add(self,Label(),name='YLabel',validate=None,desc="The label on the vertical axis")
self.YLabel.fontName = 'Helvetica'
self.YLabel.fontSize = 7
self.YLabel.x = 12
self.YLabel.y = 80
self.YLabel.angle = 90
self.YLabel.textAnchor = 'middle'
self.YLabel.maxWidth = 100
self.YLabel.height = 20
self.YLabel._text = "Y Axis"
self.chart.yValueAxis.forceZero = 1
self.chart.xValueAxis.forceZero = 1
self._add(self,0,name='preview',validate=None,desc=None)

```



## line\_chart

#Autogenerated by ReportLab guiedit do not edit

### Classes

#### LineChart(\_DrawingEditorMixin, Drawing)


##### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,LinePlot(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.lines[0].strokeColor = color01
    self.chart.lines[1].strokeColor = color02
    self.chart.lines[2].strokeColor = color03
    self.chart.lines[3].strokeColor = color04
    self.chart.lines[4].strokeColor = color05
    self.chart.lines[5].strokeColor = color06
    self.chart.lines[6].strokeColor = color07
    self.chart.lines[7].strokeColor = color08
    self.chart.lines[8].strokeColor = color09
    self.chart.lines[9].strokeColor = color10
    self.chart.fillColor = backgroundGrey
    self.chart.lineLabels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontSize = 7
    self.chart.xValueAxis.forceZero = 0
    self.chart.data = [(0, 50), (100,100), (200,200), (250,210), (300,300), (400,500)]
    self.chart.xValueAxis.avoidBoundFrac = 1
    self.chart.xValueAxis.gridEnd = 115
    self.chart.xValueAxis.tickDown = 3
    self.chart.xValueAxis.visibleGrid = 1
    self.chart.yValueAxis.tickLeft = 3
    self.chart.yValueAxis.labels.fontName = 'Helvetica'
    self.chart.yValueAxis.labels.fontSize = 7
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
    self.Title.textAnchor = 'middle'
    self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
    self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
    self.Legend.fontName = 'Helvetica'
    self.Legend.fontSize = 7
    self.Legend.x = 153
    self.Legend.y = 85
    self.Legend.dxTextSpace = 5
    self.Legend.dy = 5
    self.Legend.dx = 5
    self.Legend.deltay = 5
    self.Legend.alignment = 'right'
    self._add(self,Label(),name='XLabel',validate=None,desc="The label on the horizontal axis")
    self.XLabel.fontName = 'Helvetica'
    self.XLabel.fontSize = 7
    self.XLabel.x = 85
    self.XLabel.y = 10
    self.XLabel.textAnchor = 'middle'
    self.XLabel.maxWidth = 100
    self.XLabel.height = 20
    self.XLabel._text = "X Axis"
    self._add(self,Label(),name='YLabel',validate=None,desc="The label on the vertical axis")
    self.YLabel.fontName = 'Helvetica'
    self.YLabel.fontSize = 7
    self.YLabel.x = 12
```

```

self.YLabel.y           = 80
self.YLabel.angle       = 90
self.YLabel.textAnchor  = 'middle'
self.YLabel.maxWidth    = 100
self.YLabel.height      = 20
self.YLabel._text       = "Y Axis"
self.chart.yValueAxis.forceZero = 1
self.chart.xValueAxis.forceZero = 1
self._add(self,0,name='preview',validate=None,desc=None)

```



## radar

#Autogenerated by ReportLab guiedit do not edit

## Classes

### RadarChart(\_DrawingEditorMixin, Drawing)

#### Example

```


def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,SpiderChart(),name='chart',validate=None,desc="The main chart")
    self.chart.width      = 90
    self.chart.height     = 90
    self.chart.x          = 45
    self.chart.y          = 25
    self.chart.strands[0].strokeColor= color01
    self.chart.strands[1].strokeColor= color02
    self.chart.strands[2].strokeColor= color03
    self.chart.strands[3].strokeColor= color04
    self.chart.strands[4].strokeColor= color05
    self.chart.strands[5].strokeColor= color06
    self.chart.strands[6].strokeColor= color07
    self.chart.strands[7].strokeColor= color08
    self.chart.strands[8].strokeColor= color09
    self.chart.strands[9].strokeColor= color10
    self.chart.strands[0].fillColor  = None
    self.chart.strands[1].fillColor  = None
    self.chart.strands[2].fillColor  = None
    self.chart.strands[3].fillColor  = None
    self.chart.strands[4].fillColor  = None
    self.chart.strands[5].fillColor  = None
    self.chart.strands[6].fillColor  = None
    self.chart.strands[7].fillColor  = None
    self.chart.strands[8].fillColor  = None
    self.chart.strands[9].fillColor  = None
    self.chart.strands.strokeWidth   = 1
    self.chart.strandLabels.fontName = 'Helvetica'
    self.chart.strandLabels.fontSize = 6
    self.chart.fillColor              = backgroundGrey

```

```

self.chart.data = [(125, 180, 200), (100, 150, 180)]
self.chart.labels = ['North', 'South', 'Central']
self._add(self, Label(), name='Title', validate=None, desc="The title at the top of the chart")
self.Title.fontName = 'Helvetica-Bold'
self.Title.fontSize = 7
self.Title.x = 100
self.Title.y = 135
self.Title._text = 'Chart Title'
self.Title.maxWidth = 180
self.Title.height = 20
self.Title.textAnchor = 'middle'
self._add(self, Legend(), name='Legend', validate=None, desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
self.Legend.fontName = 'Helvetica'
self.Legend.fontSize = 7
self.Legend.x = 153
self.Legend.y = 85
self.Legend.dxTextSpace = 5
self.Legend.dy = 5
self.Legend.dx = 5
self.Legend.deltay = 5
self.Legend.alignment = 'right'
self.chart.strands.strokeWidth = 1
self._add(self, 0, name='preview', validate=None, desc=None)

```



## scatter

#Autogenerated by ReportLab guiedit do not edit

## Classes

### Scatter(\_DrawingEditorMixin, Drawing)

#### Example

```

def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,ScatterPlot(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.lines[0].strokeColor = color01
    self.chart.lines[1].strokeColor = color02
    self.chart.lines[2].strokeColor = color03
    self.chart.lines[3].strokeColor = color04
    self.chart.lines[4].strokeColor = color05
    self.chart.lines[5].strokeColor = color06
    self.chart.lines[6].strokeColor = color07
    self.chart.lines[7].strokeColor = color08
    self.chart.lines[8].strokeColor = color09


```

```

self.chart.lines[9].strokeColor = color10
self.chart.fillColor = backgroundGrey
self.chart.lineLabels.fontName = 'Helvetica'
self.chart.xValueAxis.labels.fontName = 'Helvetica'
self.chart.xValueAxis.labels.fontSize = 7
self.chart.xValueAxis.forceZero = 0
self.chart.data = [((100,100), (200,200), (250,210), (300,300), (400,500)), ((100,200), (200,300), (250,400), (300,500), (400,600))]
self.chart.xValueAxis.avoidBoundFrac = 1
self.chart.xValueAxis.gridEnd = 115
self.chart.xValueAxis.tickDown = 3
self.chart.xValueAxis.visibleGrid = 1
self.chart.yValueAxis.tickLeft = 3
self.chart.yValueAxis.labels.fontName = 'Helvetica'
self.chart.yValueAxis.labels.fontSize = 7
self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
self.Title.fontName = 'Helvetica-Bold'
self.Title.fontSize = 7
self.Title.x = 100
self.Title.y = 135
self.Title._text = 'Chart Title'
self.Title.maxWidth = 180
self.Title.height = 20
self.Title.textAnchor = 'middle'
self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
self.Legend.fontName = 'Helvetica'
self.Legend.fontSize = 7
self.Legend.x = 153
self.Legend.y = 85
self.Legend.dxTextSpace = 5
self.Legend.dy = 5
self.Legend.dx = 5
self.Legend.deltay = 5
self.Legend.alignment = 'right'
self.chart.lineLabelFormat = None
self.chart.xLabel = 'X Axis'
self.chart.y = 30
self.chart.yLabel = 'Y Axis'
self.chart.yValueAxis.labelTextFormat = '%d'
self.chart.yValueAxis.forceZero = 1
self.chart.xValueAxis.forceZero = 1

self._add(self,0,name='preview',validate=None,desc=None)

```



## scatter\_lines

#Autogenerated by ReportLab guiedit do not edit


## Classes

**ScatterLines(\_DrawingEditorMixin, Drawing)**

*Example*

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,ScatterPlot(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.lines[0].strokeColor = color01
    self.chart.lines[1].strokeColor = color02
    self.chart.lines[2].strokeColor = color03
    self.chart.lines[3].strokeColor = color04
    self.chart.lines[4].strokeColor = color05
    self.chart.lines[5].strokeColor = color06
    self.chart.lines[6].strokeColor = color07
    self.chart.lines[7].strokeColor = color08
    self.chart.lines[8].strokeColor = color09
    self.chart.lines[9].strokeColor = color10
    self.chart.lines[0].symbol = None
    self.chart.lines[1].symbol = None
    self.chart.lines[2].symbol = None
    self.chart.lines[3].symbol = None
    self.chart.lines[4].symbol = None
    self.chart.lines[5].symbol = None
    self.chart.lines[6].symbol = None
    self.chart.lines[7].symbol = None
    self.chart.lines[8].symbol = None
    self.chart.lines[9].symbol = None
    self.chart.fillColor = backgroundGrey
    self.chart.lineLabels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontSize = 7
    self.chart.xValueAxis.forceZero = 0
    self.chart.data = [((100,100), (200,200), (250,210), (300,300), (400,500)), ((100,100), (200,200), (250,210), (300,300), (400,500))]
    self.chart.xValueAxis.avoidBoundFrac = 1
    self.chart.xValueAxis.gridEnd = 115
    self.chart.xValueAxis.tickDown = 3
    self.chart.xValueAxis.visibleGrid = 1
    self.chart.yValueAxis.tickLeft = 3
    self.chart.yValueAxis.labels.fontName = 'Helvetica'
    self.chart.yValueAxis.labels.fontSize = 7
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
    self.Title.textAnchor = 'middle'
    self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
    self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
    self.Legend.fontName = 'Helvetica'
    self.Legend.fontSize = 7
    self.Legend.x = 153
    self.Legend.y = 85
    self.Legend.dxTextSpace = 5
    self.Legend.dy = 5
    self.Legend.dx = 5
    self.Legend.deltay = 5
    self.Legend.alignment = 'right'
    self.chart.lineLabelFormat = None
    self.chart.xLabel = 'X Axis'
    self.chart.y = 30
    self.chart.yLabel = 'Y Axis'
    self.chart.yValueAxis.gridEnd = 115
    self.chart.yValueAxis.visibleGrid = 1
    self.chart.yValueAxis.labelTextFormat = '%d'
    self.chart.yValueAxis.forceZero = 1
    self.chart.xValueAxis.forceZero = 1
    self.chart.joinedLines = 1
    self._add(self,0,name='preview',validate=None,desc=None)
```





## scatter\_lines\_markers

#Autogenerated by ReportLab guedit do not edit

## Classes

### ScatterLinesMarkers(\_DrawingEditorMixin, Drawing)


#### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,ScatterPlot(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.lines[0].strokeColor = color01
    self.chart.lines[1].strokeColor = color02
    self.chart.lines[2].strokeColor = color03
    self.chart.lines[3].strokeColor = color04
    self.chart.lines[4].strokeColor = color05
    self.chart.lines[5].strokeColor = color06
    self.chart.lines[6].strokeColor = color07
    self.chart.lines[7].strokeColor = color08
    self.chart.lines[8].strokeColor = color09
    self.chart.lines[9].strokeColor = color10
    self.chart.fillColor = backgroundGrey
    self.chart.lineLabels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontName = 'Helvetica'
    self.chart.xValueAxis.labels.fontSize = 7
    self.chart.xValueAxis.forceZero = 0
    self.chart.data = [((100,100), (200,200), (250,210), (300,300), (400,500)), ((100,200), (200,300), (250,200), (300,400), (400,600))]
    self.chart.xValueAxis.avoidBoundFrac = 1
    self.chart.xValueAxis.gridEnd = 115
    self.chart.xValueAxis.tickDown = 3
    self.chart.xValueAxis.visibleGrid = 1
    self.chart.yValueAxis.tickLeft = 3
    self.chart.yValueAxis.labels.fontName = 'Helvetica'
    self.chart.yValueAxis.labels.fontSize = 7
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
    self.Title.textAnchor = 'middle'
    self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
    self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
    self.Legend.fontName = 'Helvetica'
    self.Legend.fontSize = 7
```

```

self.Legend.x          = 153
self.Legend.y          = 85
self.Legend.dxTextSpace = 5
self.Legend.dy         = 5
self.Legend.dx         = 5
self.Legend.deltay     = 5
self.Legend.alignment  = 'right'
self.chart.lineLabelFormat = None
self.chart.xLabel      = 'X Axis'
self.chart.y           = 30
self.chart.yLabel      = 'Y Axis'
self.chart.yValueAxis.gridEnd = 115
self.chart.yValueAxis.visibleGrid = 1
self.chart.yValueAxis.labelTextFormat = '%d'
self.chart.yValueAxis.forceZero = 1
self.chart.xValueAxis.forceZero = 1
self.chart.joinedLines = 1
self._add(self,0,name='preview',validate=None,desc=None)

```



## simple\_pie

#Autogenerated by ReportLab guiedit do not edit

## Classes

### SimplePie(\_DrawingEditorMixin, Drawing)


#### Example

```

def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,Pie(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 100
    self.chart.height = 100
    self.chart.x = 25
    self.chart.y = 25
    self.chart.slices[0].fillColor = color01
    self.chart.slices[1].fillColor = color02
    self.chart.slices[2].fillColor = color03
    self.chart.slices[3].fillColor = color04
    self.chart.slices[4].fillColor = color05
    self.chart.slices[5].fillColor = color06
    self.chart.slices[6].fillColor = color07
    self.chart.slices[7].fillColor = color08
    self.chart.slices[8].fillColor = color09
    self.chart.slices[9].fillColor = color10
    self.chart.data = (100, 150, 180)
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100

```

```
self.Title.y = 135
self.Title._text = 'Chart Title'
self.Title.maxWidth = 180
self.Title.height = 20
self.Title.textAnchor = 'middle'
self._add(self, Legend(), name='Legend', validate=None, desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'North'), (color02, 'South'), (color03, 'Central')]
self.Legend.fontName = 'Helvetica'
self.Legend.fontSize = 7
self.Legend.x = 160
self.Legend.y = 85
self.Legend.dxTextSpace = 5
self.Legend.dy = 5
self.Legend.dx = 5
self.Legend.deltay = 5
self.Legend.alignment = 'right'
self.chart.slices.strokeWidth = 1
self.chart.slices.fontName = 'Helvetica'
self.background = ShadedRect()
self.background.fillColorStart = backgroundGrey
self.background.fillColorEnd = backgroundGrey
self.background.numShades = 1
self.background.strokeWidth = 0.5
self.background.x = 25
self.background.y = 25
self.Legend.columnMaximum = 10
self._add(self, 0, name='preview', validate=None, desc=None)
```



## stacked\_bar

#Autogenerated by ReportLab guiedit do not edit


## Classes

### StackedBar(\_DrawingEditorMixin, Drawing)

#### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,HorizontalBarChart(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.bars[0].fillColor = color01
    self.chart.bars[1].fillColor = color02
    self.chart.bars[2].fillColor = color03
    self.chart.bars[3].fillColor = color04
    self.chart.bars[4].fillColor = color05
    self.chart.bars[5].fillColor = color06
```

```
self.chart.bars[6].fillColor = color07
self.chart.bars[7].fillColor = color08
self.chart.bars[8].fillColor = color09
self.chart.bars[9].fillColor = color10
self.chart.fillColor = backgroundGrey
self.chart.barLabels.fontName = 'Helvetica'
self.chart.valueAxis.labels.fontName = 'Helvetica'
self.chart.valueAxis.labels.fontSize = 6
self.chart.valueAxis.forceZero = 1
self.chart.data = [(100, 150, 180), (125, 180, 200)]
self.chart.groupSpacing = 15
self.chart.valueAxis.avoidBoundFrac = 1
self.chart.valueAxis.gridEnd = 80
self.chart.valueAxis.tickDown = 3
self.chart.valueAxis.visibleGrid = 1
self.chart.categoryAxis.categoryNames = ['North', 'South', 'Central']
self.chart.categoryAxis.tickLeft = 3
self.chart.categoryAxis.labels.fontName = 'Helvetica'
self.chart.categoryAxis.labels.fontSize = 6
self.chart.categoryAxis.labels.dx = -3
self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
self.Title.fontName = 'Helvetica-Bold'
self.Title.fontSize = 7
self.Title.x = 100
self.Title.y = 135
self.Title._text = 'Chart Title'
self.Title.maxWidth = 180
self.Title.height = 20
self.Title.textAnchor = 'middle'
self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
self.Legend.fontName = 'Helvetica'
self.Legend.fontSize = 7
self.Legend.x = 153
self.Legend.y = 85
self.Legend.dxTextSpace = 5
self.Legend.dy = 5
self.Legend.dx = 5
self.Legend.deltay = 5
self.Legend.alignment = 'right'
self._add(self,Label(),name='XLabel',validate=None,desc="The label on the horizontal axis")
self.XLabel.fontName = 'Helvetica'
self.XLabel.fontSize = 7
self.XLabel.x = 85
self.XLabel.y = 10
self.XLabel.textAnchor = 'middle'
self.XLabel.maxWidth = 100
self.XLabel.height = 20
self.XLabel._text = "X Axis"
self._add(self,Label(),name='YLabel',validate=None,desc="The label on the vertical axis")
self.YLabel.fontName = 'Helvetica'
self.YLabel.fontSize = 7
self.YLabel.x = 12
self.YLabel.y = 80
self.YLabel.angle = 90
self.YLabel.textAnchor = 'middle'
self.YLabel.maxWidth = 100
self.YLabel.height = 20
self.YLabel._text = "Y Axis"
self.chart.categoryAxis.style='stacked'
self._add(self,0,name='preview',validate=None,desc=None)
```



## stacked\_column

#Autogenerated by ReportLab guiedit do not edit


## Classes

### StackedColumn(\_DrawingEditorMixin, Drawing)

#### Example

```
def __init__(self,width=200,height=150,*args,**kw):
    apply(Drawing.__init__,(self,width,height)+args,kw)
    self._add(self,VerticalBarChart(),name='chart',validate=None,desc="The main chart")
    self.chart.width = 115
    self.chart.height = 80
    self.chart.x = 30
    self.chart.y = 40
    self.chart.bars[0].fillColor = color01
    self.chart.bars[1].fillColor = color02
    self.chart.bars[2].fillColor = color03
    self.chart.bars[3].fillColor = color04
    self.chart.bars[4].fillColor = color05
    self.chart.bars[5].fillColor = color06
    self.chart.bars[6].fillColor = color07
    self.chart.bars[7].fillColor = color08
    self.chart.bars[8].fillColor = color09
    self.chart.bars[9].fillColor = color10
    self.chart.fillColor = backgroundGrey
    self.chart.barLabels.fontName = 'Helvetica'
    self.chart.valueAxis.labels.fontName = 'Helvetica'
    self.chart.valueAxis.labels.fontSize = 7
    self.chart.valueAxis.forceZero = 1
    self.chart.data = [(100, 150, 180), (125, 180, 200)]
    self.chart.groupSpacing = 15
    self.chart.valueAxis.avoidBoundFrac = 1
    self.chart.valueAxis.gridEnd = 115
    self.chart.valueAxis.tickLeft = 3
    self.chart.valueAxis.visibleGrid = 1
    self.chart.categoryAxis.categoryNames = ['North', 'South', 'Central']
    self.chart.categoryAxis.tickDown = 3
    self.chart.categoryAxis.labels.fontName = 'Helvetica'
    self.chart.categoryAxis.labels.fontSize = 7
    self._add(self,Label(),name='Title',validate=None,desc="The title at the top of the chart")
    self.Title.fontName = 'Helvetica-Bold'
    self.Title.fontSize = 7
    self.Title.x = 100
    self.Title.y = 135
    self.Title._text = 'Chart Title'
    self.Title.maxWidth = 180
    self.Title.height = 20
    self.Title.textAnchor = 'middle'
    self._add(self,Legend(),name='Legend',validate=None,desc="The legend or key for the chart")
    self.Legend.colorNamePairs = [(color01, 'Widgets'), (color02, 'Sprockets')]
```

```
self.Legend.fontName      = 'Helvetica'
self.Legend.fontSize      = 7
self.Legend.x             = 153
self.Legend.y             = 85
self.Legend.dxTextSpace  = 5
self.Legend.dy           = 5
self.Legend.dx            = 5
self.Legend.deltay       = 5
self.Legend.alignment     = 'right'
self._add(self,Label(),name='XLabel',validate=None,desc="The label on the horizontal axis")
self.XLabel.fontName      = 'Helvetica'
self.XLabel.fontSize      = 7
self.XLabel.x             = 85
self.XLabel.y             = 10
self.XLabel.textAnchor    = 'middle'
self.XLabel.maxWidth      = 100
self.XLabel.height        = 20
self.XLabel._text         = "X Axis"
self._add(self,Label(),name='YLabel',validate=None,desc="The label on the vertical axis")
self.YLabel.fontName      = 'Helvetica'
self.YLabel.fontSize      = 7
self.YLabel.x             = 12
self.YLabel.y             = 80
self.YLabel.angle         = 90
self.YLabel.textAnchor    = 'middle'
self.YLabel.maxWidth      = 100
self.YLabel.height        = 20
self.YLabel._text         = "Y Axis"
self.chart.categoryAxis.style='stacked'
self._add(self,0,name='preview',validate=None,desc=None)
```



## eventcal

This file is a

## Classes

### EventCalendar(Widget)

## Public Attributes

### Example

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

*Properties of Example Widget*

```
data = []  
day = 0  
endTime = None  
height = 150  
startTime = None  
timeColWidth = None  
trackNames = None  
trackRowHeight = 20  
width = 300  
x = 0  
y = 0
```

## flags

This file is a collection of flag graphics as widgets.

All flags are represented at the ratio of 1:2, even where the official ratio for the flag is something else (such as 3:5 for the German national flag). The only exceptions are for where this would look `_very_` wrong, such as the Danish flag whose (ratio is 28:37), or the Swiss flag (which is square).

Unless otherwise stated, these flags are all the 'national flags' of the countries, rather than their state flags, naval flags, ensigns or any other variants. (National flags are the flag flown by civilians of a country and the ones usually used to represent a country abroad. State flags are the variants used by the government and by diplomatic missions overseas).

To check on how close these are to the 'official' representations of flags, check the World Flag Database at <http://www.flags.ndirect.co.uk/>

The flags this file contains are:

EU Members:

United Kingdom, Austria, Belgium, Denmark, Finland, France, Germany, Greece, Ireland, Italy, Luxembourg, Holland (The Netherlands), Spain, Sweden

Others:

USA, Czech Republic, European Union, Switzerland, Turkey, Brazil

(Brazilian flag contributed by Publio da Costa Melo [publio@planetarium.com.br]).

## Classes

### Flag( `_Symbol` )

This is a generic flag class that all the flags in this file use as a basis.

This class basically provides edges and a tidy-up routine to hide any bits of line that overlap the 'outside' of the flag

possible attributes:

'x', 'y', 'size', 'fillColor'

### Public Attributes

**border** Whether a background is drawn

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** Background color

**kind** Which flag

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate



## **Star(\_Symbol)**

This draws a 5-pointed star.

possible attributes:

'x', 'y', 'size', 'fillColor', 'strokeColor'

## **Public Attributes**

**angle** angle in degrees

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **grids**

#Copyright ReportLab Europe Ltd. 2000-2004

#see license.txt for license details

#history <http://www.reportlab.co.uk/cgi-bin/viewcvs.cgi/public/reportlab/trunk/reportlab/graphics/widgets/grids.py>

## **Classes**

### **DoubleGrid(Widget)**

This combines two ordinary Grid objects orthogonal to each other.

## **Public Attributes**

**grid0** The first grid component.

**grid1** The second grid component.

**height** The grid's height.


**width** The grid's width.

**x** The grid's lower-left x position.

**y** The grid's lower-left y position.

### *Example*

```
def demo(self):
    D = Drawing(100, 100)
    g = DoubleGrid()
    D.add(g)
    return D
```

*Properties of Example Widget*

```
grid0.delta = 20
grid0.delta0 = 0
grid0.deltaSteps = []
grid0.fillColor = Color(1,1,1)
grid0.height = 100
grid0.orientation = 'vertical'
grid0.stripeColors = [Color(1,0,0), Color(0,.501961,0), Color(0,0,1)]
grid0.strokeColor = Color(0,0,0)
grid0.strokeWidth = 1
grid0.useLines = 1
grid0.useRects = 0
grid0.width = 100
grid0.x = 0
grid0.y = 0
grid1.delta = 20
grid1.delta0 = 0
grid1.deltaSteps = []
grid1.fillColor = Color(1,1,1)
grid1.height = 100
grid1.orientation = 'horizontal'
grid1.stripeColors = [Color(1,0,0), Color(0,.501961,0), Color(0,0,1)]
grid1.strokeColor = Color(0,0,0)
grid1.strokeWidth = 1
grid1.useLines = 1
grid1.useRects = 0
grid1.width = 100
grid1.x = 0
grid1.y = 0
height = 100
width = 100
x = 0
y = 0
```

## Grid(Widget)

This makes a rectangular grid of equidistant stripes.

The grid contains an outer border rectangle, and stripes inside which can be drawn with lines and/or as solid tiles. The drawing order is: outer rectangle, then lines and tiles.

The stripes' width is indicated as 'delta'. The sequence of stripes can have an offset named 'delta0'. Both values need to be positive!

## Public Attributes

**delta** Determines the width/height of the stripes.

**delta0** Determines the stripes initial width/height offset.

**deltaSteps** List of deltas to be used cyclically.

**fillColor** Background color for entire rectangle.

**height** The grid's height.

**orientation** Determines if stripes are vertical or horizontal.

**rectStrokeColor** Color for outer rect stroke.

**rectStrokeWidth** Width for outer rect stroke.

**stripeColors** Colors applied cyclically in the right or upper direction.

**strokeColor** Color used for lines.

**strokeWidth** Width used for lines.

**useLines** Determines if stripes are drawn with lines.

**useRects** Determines if stripes are drawn with solid rectangles.

**width** The grid's width.

**x** The grid's lower-left x position.

**y** The grid's lower-left y position.

### *Example*

```
def demo(self):
    D = Drawing(100, 100)

    g = Grid()
    D.add(g)

    return D
```

### *Properties of Example Widget*

```
delta = 20
delta0 = 0
deltaSteps = []
fillColor = Color(1,1,1)
height = 100
orientation = 'vertical'
stripeColors = [Color(1,0,0), Color(0,.501961,0), Color(0,0,1)]
strokeColor = Color(0,0,0)
strokeWidth = 2
useLines = 0
```

```
useRects = 1
width = 100
x = 0
y = 0
```

## ShadedPolygon(Widget, LineShape)

### Public Attributes

**angle** Shading angle

**cylinderMode** True if shading reverses in middle.

**fillColorEnd** None

**fillColorStart** None

**numShades** The number of interpolating colors.

**points** None

**strokeColor** None

**strokeDashArray** None

**strokeLineCap** None

**strokeLineJoin** None

**strokeMiterLimit** None

**strokeWidth** None

### *Example*

```
def demo(self):
    msg = "demo() must be implemented for each Widget!"
    raise shapes.NotImplementedError, msg
```

### *Properties of Example Widget*

```
angle = 90
cylinderMode = 0
fillColorEnd = Color(0,.501961,0)
fillColorStart = Color(1,0,0)
numShades = 50
points = [-1, -1, 2, 2, 3, -1]
strokeColor = Color(0,0,0)
strokeDashArray = None
strokeLineCap = 0
strokeLineJoin = 0
strokeMiterLimit = 0
strokeWidth = 1
```

## ShadedRect (Widget)

This makes a rectangle with shaded colors between two colors.

Colors are interpolated linearly between 'fillColorStart' and 'fillColorEnd', both of which appear at the margins. If 'numShades' is set to one, though, only 'fillColorStart' is used.

### Public Attributes

**cylinderMode** True if shading reverses in middle.

**fillColorEnd** End value of the color shade.

**fillColorStart** Start value of the color shade.

**height** The grid's height.

**numShades** The number of interpolating colors.

**orientation** Determines if stripes are vertical or horizontal.

**strokeColor** Color used for border line.

**strokeWidth** Width used for lines.

**width** The grid's width.


**x** The grid's lower-left x position.

**y** The grid's lower-left y position.

#### Example

```
def demo(self):
    D = Drawing(100, 100)
    g = ShadedRect()
    D.add(g)

    return D
```



#### Properties of Example Widget

```
cylinderMode = 0
fillColorEnd = Color(0,0,0)
fillColorStart = Color(1,.752941,.796078)
height = 100
numShades = 20
orientation = 'vertical'
strokeColor = Color(0,0,0)
strokeWidth = 2
width = 100
x = 0
y = 0
```

## signsandsymbols

This file is a collection of widgets to produce some common signs and symbols.

Widgets include:

- ETriangle (an equilateral triangle),
- RTriangle (a right angled triangle),
- Octagon,
- Crossbox,
- Tickbox,
- SmileyFace,
- StopSign,
- NoEntry,
- NotAllowed (the red roundel from 'no smoking' signs),
- NoSmoking,
- DangerSign (a black exclamation point in a yellow triangle),
- YesNo (returns a tickbox or a crossbox depending on a testvalue),
- FloppyDisk,
- ArrowOne, and
- ArrowTwo

## Classes

### ArrowOne ( \_Symbol )

This widget draws an arrow (style one).

possible attributes:

'x', 'y', 'size', 'fillColor'

### Public Attributes

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

### ArrowTwo ( ArrowOne )

This widget draws an arrow (style two).

possible attributes:

'x', 'y', 'size', 'fillColor'

### Public Attributes

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **Crossbox( \_Symbol )**

This draws a black box with a red cross in it - a 'checkbox'.

possible attributes:

'x', 'y', 'size', 'crossColor', 'strokeColor', 'crosswidth'

## **Public Attributes**

**crossColor** None

**crosswidth** None

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **DangerSign( \_Symbol )**

This draws a 'danger' sign: a yellow box with a black exclamation point.

possible attributes:

'x', 'y', 'size', 'strokeColor', 'fillColor', 'strokeWidth'

## **Public Attributes**

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate



**ETriangle(\_Symbol)**

This draws an equilateral triangle.

**Public Attributes**

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

**FloppyDisk(\_Symbol)**

This widget draws an icon of a floppy disk.

possible attributes:

'x', 'y', 'size', 'diskcolor'

**Public Attributes**

**diskColor** None

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

**NoEntry(\_Symbol)**

This draws a (British) No Entry sign - a red circle with a white line on it.

possible attributes:

'x', 'y', 'size'

**Public Attributes**

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**innerBarColor** color of the inner bar

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **NoSmoking(NotAllowed)**

This draws a no-smoking sign.

possible attributes:

'x', 'y', 'size'

## **Public Attributes**

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **NotAllowed(\_Symbol)**

This draws a 'forbidden' roundel (as used in the no-smoking sign).

possible attributes:

'x', 'y', 'size'

## **Public Attributes**

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **Octagon(\_Symbol)**

This widget draws an Octagon.

possible attributes:

'x', 'y', 'size', 'fillColor', 'strokeColor'

## Public Attributes

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## RTriangle(\_Symbol)

This draws a right-angled triangle.

possible attributes:

'x', 'y', 'size', 'fillColor', 'strokeColor'

## Public Attributes

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## SmileyFace(\_Symbol)

This draws a classic smiley face.

possible attributes:

'x', 'y', 'size', 'fillColor'

## Public Attributes

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **StopSign( \_Symbol )**

This draws a (British) stop sign.

possible attributes:

'x', 'y', 'size'

## **Public Attributes**

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**stopColor** color of the word stop

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **Tickbox( \_Symbol )**

This draws a black box with a red tick in it - another 'checkbox'.

possible attributes:

'x', 'y', 'size', 'tickColor', 'strokeColor', 'tickwidth'

## **Public Attributes**

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**tickColor** None

**tickwidth** None

**x** symbol x coordinate

**y** symbol y coordinate

## **YesNo( \_Symbol )**

This widget draw a tickbox or crossbox depending on 'testValue'.

If this widget is supplied with a 'True' or 1 as a value for testValue, it will use the tickbox widget. Otherwise, it will produce a crossbox.

possible attributes:

'x', 'y', 'size', 'tickcolor', 'crosscolor', 'testValue'

## Public Attributes

**crosscolor** None

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**testValue** None

**tickcolor** None

**x** symbol x coordinate

**y** symbol y coordinate

## \_\_Symbol(Widget)

Abstract base widget

possible attributes:

'x', 'y', 'size', 'fillColor', 'strokeColor'

## Public Attributes

**dx** symbol x coordinate adjustment

**dy** symbol x coordinate adjustment

**fillColor** None

**size** None

**strokeColor** None

**strokeWidth** None

**x** symbol x coordinate

**y** symbol y coordinate